

CAAP CO INC -- FE-AS FLUOROELASTOMER CURING AGENT -- 8030-01-127-1960

=====
Product Identification
=====

Product ID:FE-AS FLUOROELASTOMER CURING AGENT

MSDS Date:06/28/1988

FSC:8030

NIIN:01-127-1960

Kit Part:Y

MSDS Number: BJXSD

=== Responsible Party ===

Company Name:CAAP CO INC

Address:152 PEPES FARM RD

City:MILFORD

State:CT

ZIP:06460-3670

Country:US

Info Phone Num:203-468-0055

Emergency Phone Nu

m:203-877-0375

Preparer's Name:RONALD D. ARENA

CAGE:60922

=== Contractor Identification ===

Company Name:CAAP CO INC

Address:152 PEPE'S FARM RD

Box:City:MILFORD

State:CT

ZIP:06460

Country:US

Phone:203-877-0375

CAGE:60922

=====
Composition/Information on Ingredients
=====

Ingred Name:ALIPHATIC AMINE, NAME WITHELD AS A TRADE SECRET.

Other REC Limits:10 PPM BY MFGR

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Other REC Limits:NONE SPECIFIED

OSHA

PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE: CONTACT-CORROSIVE TO EYES; SKIN
IRRITANT, MAY CAUSE BURNS OR RASH. INHALATION: UPPER RESP
IRRITATION, MAY BE TOXIC IN VERY HIGH DOSES. CHRONIC: WEIGHT LOSS;
ANEMIA; LIVER, KIDNEY SPLEEN POSSIBLE DAMAGE; POSSIBLE SENSITIZER.
R
ROUTES OF INHALATION AND POSSIBLE SIGNIFICANT SKIN PENETRATION.
Effects of Overexposure:PUNGENT ODOR, UPPER RESP. IRRITATION, EYE
IRRITATION-TEARING, BLURRING OF VISION AND HEADACHE.
Medical Cond Aggravated by Exposure:PRE-EXISTING LIVER DISEASE MAY BE
AGGRAVATED.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LUKE WARM WATER 15 MIN AND CALL DOCTOR.
SKIN: WASH WITH SOAP AND WATER; IF IRRITATION PERSISTS CALL DOCTOR.
INHALATION: RE
MOVE TO FRESH AIR, CALL DOCTOR, GIVE ARTIFICIAL
RESPIRATION IF NOT BREATHING. INGESTION: CALL DOCTOR.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:74.0F,23.3C
Lower Limits:0.9
Upper Limits:7.5
Extinguishing Media:DRY CHEMICAL, CO2, FOAM.
Fire Fighting Procedures:USE FULL PROTECTIVE GEAR, INCLUDING
SELF-CONTAINED BREATHING APPARATUS AND RUBBER OR OTHER CHEMICAL
PROTECTIVE SUIT FOR AMINE/AMMONIA TYPE CORROSIVE VAPORS.
Unusual
Fire/Explosion Hazard:NONE. FLAMMABLE LIQUID AND CORROSIVE
LIQUID WHEN WATER ADDED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:DIKE SPILL AND SOAK UP WITH ABSORBENT
MATERIAL. USE PROTECTIVE GLOVES, MASK, GOGGLES AND APRON. PLACE IN
TIGHTLY SEALED CONTAINERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP IGNITION SOURCES AWAY. KEEP
CONTAINERS CLOSED WHEN NOT IN USE.

STORE IN A COOL DRY PLACE.

Other Precautions:DO NOT BREATHE VAPOR MIST. AVOID CONTACT WITH EYES,
SKIN AND CLOTHING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED SPECIAL CARBON CANISTER,
SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED AIR FOR EMERGENCY
USE.

Ventilation:YES; MAINTAINING MIBK CENCENTRATION BELOW 10 PPM SHOULD
CONTROL CONCENTRATION OF MIXTURE WELL BELOW TLV.

Protective Gloves:NEOPRENE OR POLYETHYLENE.

Eye Protection:SPLASH-PROOF GOGGLES, SOLVENT RESISTANT.

Other Protective Equipment:SPRAY BOOTHS FOR INDOOR SPRAY APPLICATIONS.
RUBBER OR POLYETHYLENE APRON, EMERGENCY EYE WASH AND SHOWER.

Work Hygienic Practices:WASH HANDS AFTER USE. KEEP ARE NEAT AND CLEAN.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:231 TO 266F

Vapor Pres:3

Vapor Density:3.7

Spec Gravity:0.83

Evaporation Rate & Reference:< 1 (BUTYL ACETATE=
1)

Solubility in Water:SLIGHT

Appearance and Odor:CLEAR, YELLOW LIQUID WITH PUNGENT ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, ESP. CHLORINE AND HYPOCHLORITES, PURE OXYGEN.
STRONG ACIDS.

Stability Condition to Avoid:IGNITION SOURCES, HOT SURFACES.

Hazardous Decomposition Products:IN A FIRE, NITROGEN/CARBON OXIDES,
AMMONIA, POSSIBLE HCN. FORMS CORROSIVE LIQUID WHEN WATER IS ADDED.

=====

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION PREFERRED. PRODUCT IS IGNITABLE WASTE. RCRA# U 161. DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.