

PRATT AND LAMBERT INC -- EN ALKYD,SEMI GLOSS, LOW VOC WHITE 27875 -- 8010-00-087-0107

=====  
Product Identification  
=====

Product ID:EN ALKYD,SEMI GLOSS, LOW VOC WHITE 27875

MSDS Date:02/13/1991

FSC:8010

NIIN:00-087-0107

MSDS Number: BJXVW

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361 (M-F 8AM-5PM CT)

Em

ergency Phone Num:716-873-6000 OR 800-255-3924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5%

Other REC Limits:LFL 1.0/UFL 7.0

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

D

OT Rpt Qty:1000 LBS

Ingred Name:SOLVENT NAPHTHA, LIGHT AROMATIC

CAS:64742-95-6

Fraction by Wt: < 5%

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Fraction by Wt: 5%

Other REC Limits:LFL 1.7/UFL 7.6

OSHA PEL:150 PPM/200 STEL

ACGIH TLV:150 PPM/200STEL;9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE 2 MM HG)

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 5%

Other REC Limits:LFL 1.0/UFL 7.0

OSHA PEL:100 PPM; 525 MG/M3

ACGIH TLV:

100 PPM; 525 MG/M3

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 20%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:SILICA, AMORPHOUS HYDRATED

CAS:112945-52-5

RTECS #:VV7310000

Fraction by Wt: < 5%

OSHA PEL:6 MG/M3

ACGIH TLV:10 MG/M3

Ingred Name:METHYL ISOAMYL KETONE

CAS:110-12-3

RTECS #:MP3850000

Fraction by Wt: 5%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

Ingred Name:TALC (CONTAINING NO ASBESTOS)

CAS:14807-96-6

RTECS #:WW2710000

Fraction by

Wt: 20%  
OSHA PEL:2 MG/M3 RDUST  
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:SILICA, CRYSTALLINE - QUARTZ  
CAS:14808-60-7  
RTECS #:VV7330000  
Fraction by Wt: < 1%  
OSHA PEL:SEE TABLE Z3  
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 5%  
Other REC Limits:LFL 2.0/UFL 10.0  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:VOC 3.05 LB/GAL LESS WATER & N  
PRS\* 366 G/L LESS WATER  
CALCULATED  
RTECS #:9999999VO

Ingred Name:VOC 5.43 LB/GAL SOLIDS 652 G/L SOLIDS CALCULATED  
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES  
Health Hazards Acute and Chronic:GASTROINTESTINAL, NOSE, THROAT, EYE,  
SKIN IRRITATION. ASPIRATION TO LUNGS/CAUSES CHEMICAL  
PNEUMONITIS/POSS FATAL. OVEREXPOS: ACUTE CTRL  
NERV SYSTEM DEPRESS.  
LIVER, KIDNEY, BLOOD, CORNEAL DAMAGE. PERIP HERAL NEUROPATHY, PERM  
BRAIN/NERV SYST DAMAGE. PNEUMOCONIOSIS-PROGRESSIVE DISABLING LUNG  
DISEASE.  
Explanation of Carcinogenicity:CRYSTALLINE SILICA HAS LIMITED EVIDENCE  
OF CARCINOGENICITY IN HUMANS & SUFFICIENT EVIDENCE IN EXPERIMENTAL  
ANIMALS/IARC.  
Effects of Overexposure:SWALLOWING: NAUSEA, VOMITING. INHALATION:  
HEADACHE, DIZZINESS, NAUSEA, CONFUSION. LIQUID MATERIAL MAY BE  
ABSORBED THROUGH THE SKIN IN

HARMFUL AMOUNTS. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

Medical Cond Aggravated by Exposure:PRE-EXISTING RESPIRATORY CONDITIONS MAY BE AGGRAVATED BY EXPOSURES TO CRYSTALLINE SILICA.

=====  
===== First Aid Measures =====

First Aid:SWALLOW: DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER, HOSPITAL EMERGENCY ROOM, PHYSICIAN. INHALE: REMOVE TO FRESH AIR. BREATHING STOPPED, GIVE CPR. KEEP WARM/QUIET. GET MEDICAL ATTENTION. EYE: FLUSH W/LARGE AMOUNT WATER, LIFT UPPER/LOWER LIDS OCCASIONALLY-15 MIN. GET MEDICAL ATTENTION. SKIN: FLUSH CONTAMINATED AREA W/LARGE AMOUNTS WATER. REMOVE CONTAMINATED CLOTH. GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point:24.0F,-4.4C  
Lower Limits:1.0  
Upper Limits:10.0  
Extinguishing Media:CARBON DIOXIDE, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.  
Fire Fighting Procedures:WATER INEFFECTIVE, BUT MAY BE USED TO COOL EXPOSED CONTAINERS TO PREVENT PRESS BUILD-UP, AUTO-IGNITION, EXPLOSION W/HEAT. IF WATER USED/FOG NOZZLES PREFERRED.  
Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MEDICAL ATTENTION.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY. REMOVE IGNITE SOURCES. DIKE/CONTAIN SPILL W/INERT MATERIAL. TRANSFER LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY/DISPOSAL OR REMOVE W/INERT ABSORB. USE NON-SPARK TOOLS. PREVENT CONTAM OF SEWERS, STREAMS, GROUNDWATER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100 F (38 C) STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CLOSE AFTER

EACH USE.

Other Precautions:KEEP FROM CHILDREN. DO NOT BREATHE SANDING DUST. DO NOT WASH/REUSE EMPTY CONTAINERS. GROUND/BOND CONTAINERS TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT PRESSURE VESSEL.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:MAY NOT REQUIRE RESPIRATORY PROTECTION IF USED IN WELL VENTILATED AREAS. RESTRICTED VENTILATION: USE NIOSH APPROVED CHEM

ICAL CARTRIDGE RESPIRATOR. MAY ALSO NEED MECHANICAL PREFILTER. CONFINED AREAS MA Y NEED APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST VENT IN SUFFICIENT VOLUME/PATTERN/KEEP CONC HZDS INGRED BELOW LOWEST EXPOS LIMIT.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER.

Supplemental Safety and Health

FLAMMABLE. IF TLV'S EXCEEDED, USE A PROPERLY FITTED NIOSH /MSHA APPROVED

RESPIRATOR WITH AN APPROPRIATE PROTECTION FACTOR. LABORATORY STUDIES INVOLVING RATS INDICATE SOME EVIDENCE THAT METHYL ETHYL KET ONE MAY BE EMBRYOTOXIC, FETOTOXIC AND TERATOGENIC.

=====  
===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:139 TO 399F

Vapor Density:> THAN AIR

Spec Gravity:1.4

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Appearance and Odor:PAINT

Percent Volatiles by Volume:43

=====  
===== Stab  
ility and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>100 F (38 C) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:BURNING, INCLUDING WHEN HEATED BY WELDING OR CUTTING, WILL PRODUCE SMOKE, CARBON MONOXIDE, CARBON DIOXIDE.

=====  
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE PER FED, ST

ATE, LOCAL LAWS/REGS.

INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CNTNR. OBSERVE PRECAUTIONS FOR FLAMMABLE MAT'L DISPOSAL. DISPOSE ABSORB DIKING MATERIALS IN COVERED METAL CONTAINERS IN HZDS WASTELANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this inform

ation to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.