

PRATT AND LAMBERT INC -- EN ALKYD LUST QD GREEN 34108 ID 744422 -- 8010-00-598-5939
===== Product Identification =====

Product ID:EN ALKYD LUST QD GREEN 34108 ID 744422

MSDS Date:02/11/1991

FSC:8010

NIIN:00-598-5939

MSDS Number: BJXYT

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361 (M-F 8AM-5PM CT)

Emerge

ncy Phone Num:716-873-6000 OR 800-255-3924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:VM&P NAPTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 10%

Other REC Limits:LFL .9/UFL 6.7

OSHA PEL:300 PPM;400 PPM STEL

ACGIH TLV:300 PPM; 1350 MG/M3

Ingred Name:ISOBUTYL ALCOHOL (VAPOR PRESSURE 10

MM HG)
CAS:78-83-1
RTECS #:NS1752000
Fraction by Wt: 5%
Other REC Limits:LFL 1.0/UFL 11.0
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: < 5%
Other REC Limits:LFL 1.7/UFL 7.1
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 5%
Other REC Limits:LFL 2.0/UF
L 11.0
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
Fraction by Wt: 10%
Other REC Limits:LFL 1.0/UFL 7.0
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

Ingred Name:HEXANE (VAPOR PRESSURE 120 MM HG)
CAS:110-54-3
RTECS #:MN8420000
Fraction by Wt: < 1%
Other REC Limits:LFL 1.0/UFL 8.0
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:CYCLOHEXANE (SARA III)
CAS

:110-82-7
RTECS #:GU6300000
Fraction by Wt: < 5%
Other REC Limits:LFL 1.3/UFL 8.4
OSHA PEL:300 PPM
ACGIH TLV:300 PPM, 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:LEAD CHROMATE (SARA 313)
CAS:7758-97-6
RTECS #:GB2975000
Fraction by Wt: 10%
OSHA PEL:0.05 MG/M3;0.10 CEIL
ACGIH TLV:0.05 MG/M3

Ingred Name:TALC (CONTAINING NO ASBESTOS)
CAS:14807-96-6
RTECS #:WW2710000
Fraction by Wt: 25%
OSHA PEL:2 MG/M3 RDUST
ACGIH TLV:2 MG/M3 RDUST; 9192

Ingred Name:MINERAL SPIRITS (VAPOR PRESSURE
2 MM HG)
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 5%
Other REC Limits:LFL 1.0/UFL 7.0
OSHA PEL:100 PPM; 525 MG/M3
ACGIH TLV:100 PPM; 525 MG/M3

Ingred Name:LEAD COMPOUNDS (SARA 313)
CAS:7439-92-1
RTECS #:OF5250000
Fraction by Wt: < 1%
OSHA PEL:0.05 MG/M3
ACGIH TLV:0.15 MG/M3
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:VOC 4.14 LB/GAL LESS WATER & NPRS* 497 G/L LESS WATER
CALCULATED
RTECS #:9999999VO

Ingred Name:VOC 10.20 LB/GAL SOLIDS 1224 G/L SOLIDS CALCULATED
RTECS #:9999999VO

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:GASTROINTESTINAL/EYE/NOSE/THROAT IRRIT. ASPIRATION INTO LUNG/CAUSE CHEMICAL PNEUMONITIS/POSS FATAL. INHALE: ACUTE CTRL NERV SYST DEPRESS. SKIN IRRIT, DEFATTING. LIVER/PERIPHERAL NERV SYST DAMAGE, PERM BRAIN/NERV SYST DAMAGE; SEVERE DAMAGE TO BLOOD FORMING, URINARY , REPRODUCTIVE SYST.

PERIPHERAL NEUROPATHY. LUNG CANCER.

Explanation of Carcinogenicity:CHROMIUM & CERTAIN CHROMIUM COMPOUNDS ARE LISTED AS POTENTIAL CARCINOGENS BY NTP. LEAD CHROMATE POSS ANIMAL CARCINOGEN.

Effects of Overexposure:SWALLOWING: NAUSEA, VOMITING. INHALATION: HEADACHE, DIZZINESS, NAUSEA, CONFUSION. LOSS OF APPETITE, METALLIC TASTE IN MOUTH, ANXIETY, CONSTIPATION, NAUSEA, WEAKNESS, INSOMNIA, MUSCLE/JOINT PAIN, FINE TREMORS, NUMBNESS, DIZZINESS, HYPERACTI

VITY, COLIC. PURPOSELY INHALING CONTENTS CAN BE HARMFUL/FATAL

Medical Cond Aggravated by Exposure:PRE-EXISTING KIDNEY CONDITIONS MAY BE AGGRAVATED BY EXPOSURES TO LEAD. TOLUENE CAUSES KIDNEY, LUNG AND SPLEEN DAMAGE IN LAB ANIMALS.

===== First Aid Measures =====

First Aid:SWALLOW: DO NOT INDUCE VOMITING. CALL POISON CONTROL CENTER, HOSPITAL EMERGENCY ROOM, PHYSICIAN. INHALE: REMOVE TO FRESH AIR.

BREATHING STOPPED, GIVE CPR. KEEP WARM/QUI

ET. GET MEDICAL

ATTENTION. EYE: FLUSH W/LARGE AMOUNT WATER, LIFT UPPER/LOWER LIDS OCCASIONALLY-15 MIN. GET MEDICAL ATTENTION. SKIN: FLUSH CONTAMINATED AREA W/LARGE AMOUNTS WATER. REMOVE CONTAMINATED CLOTH. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:-9F,-23C

Lower Limits:.9

Upper Limits:11

Extinguishing Media:CARBON DIOXIDE, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM. POLYMER FOAM IS PREFERRED FOR LARGE FIRES.

Fire

Fighting Procedures:FIREFIGHTERS WEAR SCBA. WATER INEFFECTIVE, MAY USE TO COOL EXPOSED CONTAINERS TO PREVENT PRESS BUILD-UP, AUTO-IGNITION, EXPLOS W/HEAT. WATER USED/FOG NOZZLES.

Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MEDICAL ATTENTION.

===== Accidental Release Measures =====

Spill Release Procedures:KEEP SPECTATORS AWAY

. REMOVE IGNITE SOURCES.

DIKE/CONTAIN SPILL W/INERT MATERIAL. TRANSFER LIQUIDS TO COVERED METAL CONTAINERS FOR RECOVERY/DISPOSAL OR REMOVE W/INERT ABSORB. USE NON-SPARK TOOLS. PREVENT CONTAM OF SEWERS, STREAMS, GROUNDWATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100 F (38 C). STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CLOSE AFTER EACH USE.

Other P

recautions:KEEP FROM CHILDREN. DO NOT BREATHE SANDING DUST. DO NOT WASH/REUSE EMPTY CONTAINERS. GROUND/BOND CONTAINERS TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT PRESSURE VESSEL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:MAY NOT REQUIRE RESPIRATORY PROTECTION IF USED IN WELL VENT AREAS. RESTRICTED VENT USE NIOSH APPROVED ORGANIC VAPOR RESPIRATOR. MAY ALSO NEED A MECHANICAL PREFILTER. CONFINED

AREAS OR W/HIGH EXPOS MAY NEED APPROVED AIR SUPPLIED RESPIRATOR.

Ventilation:PROVIDE GENERAL DILUTION/LOCAL EXHAUST VENT IN SUFFICIENT VOLUME/PATTERN/KEEP CONC HZDS INGRED BELOW LOWEST EXPOS LIMIT.

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:SAFETY GLASSES/CHEMICAL SAFETY GOGGLES.

Other Protective Equipment:EYEWASH FACILITY, SAFETY SHOWER. AS REQUIRED TO PREVENT SKIN CONTACT. SEE OSHA STANDARD FOR LEAD.

Work Hygienic Practices:WA

SH HANDS AND FACE THOROUGHLY BEFORE EATING OR DRINKING.

Supplemental Safety and Health

DANGER. EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE. METAL OXIDE OVEREXPOSURE MAY RESULT IN "METAL FUME FEVER"-FEVER, CHILLS, AND COUGH. AN AIR PURIFYING OR SUPPLIED AIR RESPIRATOR MAY BE REQUIRED DEPENDING UPON LEVELS OF EXPOSURE. REMOVE DECOMP PROD GENERATED WHEN WELDING, CUTTING, BRAZING OBJECTS COATED W/PROD.

===== Physical/Chemical Properties =====

B

Boiling Pt:B.P. Text:156 TO 390F

Vapor Density:> THAN AIR

Spec Gravity:1.2

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Appearance and Odor:PAINT

Percent Volatiles by Volume:59

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS. OXIDIZING MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT (>100 F (38 C) AND SOURCES OF IGNITION.

Hazardous Decomposition Products:MAY PRODUCE S

MOKE, CARBON MONOXIDE,

CARBON DIOXIDE, METAL OXIDES. OXIDES OF LEAD AND CHROMIUM MAY BE GENERATED.

Conditions to Avoid Polymerization:KEEP AWAY FROM HEAT, SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE PER FEDERAL, STATE, LOCAL

LAWS/REGULATIONS FOR TOXIC/IGNITABLE WASTE D001/D008. INCINERATE ONLY IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINER.

DISPOSE ABSORB DIKING MATERIALS IN COVERED

METAL CONTAINERS IN

HZDS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of

f this information to their
particular situation.