

TECHNICAL COMPANY -- REFRIGERANT 12 #6012,6022 -- 6830-00-816-6533

===== Product Identification =====

Product ID:REFRIGERANT 12 #6012,6022

MSDS Date:12/29/1988

FSC:6830

NIIN:00-816-6533

MSDS Number: BJXZD

=== Responsible Party ===

Company Name:TECHNICAL COMPANY

Address:10737 SPANGLER ROAD

Box:20098

City:DALLAS

State:TX

ZIP:75220-7101

Country:US

Info Phone Num:214-556-1421 OR 800-527-0885

Emergen

cy Phone Num:214-556-1421

Preparer's Name:KELLY BERRIOCHOA

CAGE:MO029

=== Contractor Identification ===

Company Name:TECHNICAL CHEMICAL COMPANY

Address:10737 SPANGLER ROAD

Box:20098

City:DALLAS

State:TX

ZIP:75220-7101

Country:US

Phone:972-556-1421

CAGE:8X792

Company Name:TECHNICAL COMPANY

Address:10737 SPANGLER ROAD

Box:20098

City:DALLAS

State:TX

ZIP:75220-7101

Country:US

Phone:214-556-1421 OR 800-527-0885

CAGE:MO029

===== Composition/Information on Ingredients =====

Ingred

Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depleting Chemical:1

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (RAT) = 167 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: MAY CAUSE EYE & SK
IN

IRRITATION. INHALATION MAY CAUSE RESPIRATORY TRACT IRRITATION AND
NARCOSIS.MAY EXPERIENCE ASPHYXIATION,CARDIAC ARRHYTHMIAS.

Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:PREEXISTING CONDITIONS MAY BE
WORSEN

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR.

IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. EYE:

FLUSH IMMEDIATELY WITH LAR

GE AMOUNTS OF WATER FOR 15 MINUTES. GET

MEDICAL AT TENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH
SOAP AND WATER PROMPTLY. INGESTION: DO NOT INDUCE VOMITING. GIVE
MILK OR WATER TO DRINK ONLY IF CONSCIOUS. GET IMMEDIATE MEDICAL
ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:NON FLAMMABLE

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPAR

ATUS. EVACUATE AREA. COOL

FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

===== Accidental Release Measures =====

Spill Release Procedures:SMALL SPILL: WIPE UP WITH RAGS OR TOWELS.

LARGE SPILLS: EVACUATE AREA. WEAR NIOSH APPROVED RESPIRATOR.

VENTILATE AREA. DIKE TO RETAIN FLUID. PUMP UP FREE LIQUID. RESIDUE
WILL EVAPORATE QUICKLY. DO NOT F

LUSH TO SEWER OR WATERWAY.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A COOL, DRY, WELL-VENTILATED
LOCATION, AWAY FROM ANY AREA WHERE THE FIRE HAZARD MAY BE ACUTE.
KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN HIGH VAPOR AREA, USE NIOSH/MSHA APPROVED
RE

SPIRATOR WITH ORGANIC VAPOR CARTRIDGE. USE SELF-CONTAINED
BREATHING APPARATUS IF VAPOR LEVELS EXCEED 1000 PPM. LONG-TERM
OVEREXPOSURE MAY CAUSE LIVER/KIDN EY DAMAGE.

Ventilation:LOCAL EXHAUST RECOMMENDED TO CONTROL VAPORS BELOW 50% OF
TLV.

Protective Gloves:NEOPRENE, PVA GLOVES RECOMMENDED.

Eye Protection:CHEMICAL SAFETY GOGGLES & FACE SHIELD.

Other Protective Equipment:APRON AND WORK CLOTHING TO MINIMIZE
EXPOSURE. EYE WASH STATION & SAFETY SHOWER RECOMMENDED.

Work Hygienic Pract

ices:WASH THOROUGHLY AFTER USE AND BEFORE EATING,
SMOKING OR USING TOILET FACILITIES. DO NOT BREATH VAPORS OR MIST.

Supplemental Safety and Health

TARGET ORGANS ARE SKIN, CNS, CVS, AND EYES.

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:=-30.C, -22.F

Vapor Pres:79.8 PSIG

Vapor Density:4.25

Spec Gravity:1.31

Solubility in Water:INSOLUBLE

Appearance and Odor:COLORLESS LIQUID AND VAPOR-VERY SLIGHT EHEREAL TO
ODORLESS.

===== Stability

and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

ALKALI OR ALKALINE EARTH METALS, POWDERED ALUMINUM, ZINC, BERYLLIUM.

Stability Condition to Avoid: HIGH HEAT

Hazardous Decomposition Products: WHEN INVOLVED IN FIRE, IRRITATING
HYDROGEN CHLORIDE, HF AND TRACES OF CARBONYL HALIDE (PHOSGENE
FUMES.)

===== Disposal Considerations =====

Waste Disposal Methods: CONTAMINATED SAWDUST, VERMICULITE OR POROUS
SURFACE MUST BE DISPOSED OF
IN A PERMITTED HAZARDOUS WASTE
MANAGEMENT FACILITY. RECOVERED LIQUIDS MAY BE REPROCESSED OR
INCINERATED OR MUST BE TREATED IN A PERMITTED HAZARDOUS WASTE
MANAGEMENT FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its
use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.