

DIAL CORP THE -- EA 9309 NA PART A -- 8040-01-126-6270

===== Product Identification =====

Product ID:EA 9309 NA PART A
MSDS Date:09/29/1989
FSC:8040
NIIN:01-126-6270
Kit Part:Y
MSDS Number: BJYBS
=== Responsible Party ===
Company Name:DIAL CORP THE
Address:1865 DIAL TOWER
Box:312
City:PHOENIX
State:AZ
ZIP:85077-1865
Country:US
Info Phone Num:602-991-3000
Emergency Phone Num:602-991-3000
CAGE:0EK4
5

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS
Address:2850 WILLOW PASS ROAD
Box:312
City:BAY POINT
State:CA
ZIP:94565-3299
Country:US
Phone:202-483-7616
CAGE:33564
Company Name:DIAL CORP THE
Address:111 W CLARENDON AVE
Box:3223
City:PHOENIX
State:AZ
ZIP:85077
Country:US
Phone:602-991-3000
CAGE:0EK45

===== Composition/Information on Ingredients =====

Ingred Name:EPOXY RESIN SYSTEM

Ingred Name:SILICA
CAS:112945-52-5
RTECS #:VV73

10000
Fraction by Wt: 149C
Extinguishing Media: DRY CHEMICAL OR HALON FIRE EXTINGUISHER, OR WATER SPRAY, FOAM OR FOG.
Fire Fighting Procedures: USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.
Unusual Fire/Explosion Hazard: DENSE SMOKE AND TOXIC GASES MAY BE LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures: WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER.
R. WIPE UP
REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG. F) FOR 12 MONTHS.
Other Precautions: FOLLOW RECOMMENDED CURING SCHEDULE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.
Ventilation: LOCAL EXHAUST RECOMMENDED.
Protective Gloves: IMPERVIOUS PLASTIC OR RUBBER.
Eye Protection: SAFETY GLASSES OR GOGGLES.
Other Protective Equipment: AS NEEDED TO PROTECT SKIN AND CLOTHING.
Work Hygienic Practices: WASH THOROUGHLY AFTER HANDLING.
Supplemental Safety and Health
KEY1: N1. FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD-UP WITH THE RELEASE OF TOXIC GASES. DO NOT HANDLE OR USE UNTIL MSDS HAS BEEN READ & UNDERSTOOD. CONTAINS EPOXY RESINS.

===== Physical/Chemical Properties =====

HCC: B2
Boiling Pt: B.P. Text: DECOMPOSES
Vapor Pres: 1
Evaporation Rate & Reference: NIL
Solubility in Water: NIL
Appearance and Odor: PEARLESCENT PASTE WITH PUNGENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.
Hazardous Decomposition Products: CO, NOX, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.
Conditions to Avoid Polyme

rization:MIXING RESIN/CURING AGENT IN BATCHES
GREATER THAN 1 LB. DO NOT HEAT MIXED ADHESIVE UNLESS CURING
SURFACES TO BE BONDED.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America
in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.