

DEXTER ADHESIVES AND STRUCTURAL MATERIALS -- EA9309 NA PART B -- 8040-01-152-8105
===== Product Identification =====

Product ID:EA9309 NA PART B

MSDS Date:09/29/1989

FSC:8040

NIIN:01-152-8105

Kit Part:Y

MSDS Number: BJYCB

=== Responsible Party ===

Company Name:DEXTER ADHESIVES AND STRUCTURAL MATERIALS

Address:2850 WILLOW PASS ROAD

Box:312

City:PITTSBURG

State:CA

ZIP:94565

Country:US

Info Phone Nu

m:415-687-4201

Emergency Phone Num:800-424-9300 (CHEMTREC)

CAGE:33564

=== Contractor Identification ===

Company Name:DEXTER CORPORATION ADHESIVE & COATING SYSTEMS

Address:2850 WILLOW PASS ROAD

Box:312

City:BAY POINT

State:CA

ZIP:94565-3299

Country:US

Phone:202-483-7616

CAGE:33564

===== Composition/Information on Ingredients =====

Ingred Name:ALKYLAMINES

Ingred Name:VOC 300F,>149C

Extinguishing Media:DRY CHEMICAL OR HALON FIRE EXTINGUISHER, WATER
SPRAY, FOAM OR FOG.

Fire

Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS WHEN FIGHTING FIRES IN CONFINED AREAS.

Unusual Fire/Explosion Hazard:DENSE SMOKE AND TOXIC GASES MAY BE LIBERATED.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE CLOTHING, GLOVES AND SAFETY GLASSES. SCRAPE UP AND TRANSFER TO METAL CONTAINER. WIPE UP REMAINING RESIDUE WITH SOLVENTS, OBSERVING SOLVENT FLAMMABILITY CAUTIONS.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL IN ACCORDANCE WITH LABEL INSTRUCTIONS. STORE AT ROOM TEMPERATURE (77 DEG. F) FOR 12 MONTHS. Other Precautions:FOLLOW RECOMMENDED CURING SCHEDULE. USE ONLY IN WELL VENTILATED AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WITH GOOD INDUSTRIAL VENTILATION.

Ventilation:LOCAL EXHAUST RECOMMENDED.

Protective Gloves:IMPERVIOUS PLASTIC OR RUBBER.

Eye Pr

tection:SAFETY GLASSES OR GOGGLES.

Other Protective Equipment:AS NEEDED TO PROTECT SKIN AND CLOTHING.

Supplemental Safety and Health

AVOID MIXING RESIN AND CURING AGENT IN BATCHES GREATER THAN 1 POUND TOTAL. DO NOT HEAT MIXED ADHESIVE UNLESS CURING SURFACES TO BE BONDED. FAILURE TO OBSERVE CAUTION MAY RESULT IN EXCESSIVE HEAT BUILD -UP W/RELEASE OF TOXIC GASES. PART B CONTAINS ALKYLAMINES. DO NOT HANDLE OR USE UNTIL MSDS HAS BEEN READ & UNDERSTOOD.

===== Physical/Chemical Properties =====

Vapor Density:8.45

Spec Gravity:1.02

Evaporation Rate & Reference:NIL

Appearance and Odor:REDDISH-ORANGE LIQUID WITH AMMONIACAL ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS, STRONG LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products:CO, NOX, ALDEHYDES, ACIDS AND UNDETERMINED ORGANICS.

===== Disposal Considerations =====

=====

Waste Disposal Methods:DISPOSE OF AS HAZARDOUS WASTE ACCORDING TO
FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.