View NSN Online: https://aerobasegroup.com/nsn/3439-01-167-0696

TELEDYNE MCKAY -- 316L STAINLESS STEEL COVERED ELECTRODE -- 3439-01-167-0696

======== Product Identification ============

Product ID:316L STAINLESS STEEL COVERED ELECTRODE

MSDS Date:03/01/1989

FSC:3439

NIIN:01-167-0696

MSDS Number: BJYCC === Responsible Party ===

Company Name: TELEDYNE MCKAY

Address:850 GRANTLEY RD

Box:1509 City:YORK State:PA ZIP:17405 Country:US

Info Phone Num:717-849-2455 FAX:717-849-236

5

Emergency Phone Num:717-845-7581

CAGE:76254

=== Contractor Identification ===

Company Name: HOBART BROS CO MCKAY WELDING PRODUCTS DIV

Address:400 TRADE SQ E

Box:City:TROY

State:OH

ZIP:45373-2900

Country:US

Phone:513-332-5706

CAGE:76254

======= Composition/Information on Ingredients ========

Ingred Name: MANGANESE (SARA III)

CAS:7439-96-5

RTECS #:009275000 Fraction by Wt: 1.5%

Other REC Limits:NONE SPECIFIED OSHA PEL:(C) 5 MG/M3 DUST ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:CHROM

IUM (SARA III) CAS:7440-47-3 RTECS #:GB420

RTECS #:GB4200000 Fraction by Wt: 18%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1 MG/M3

ACGIH TLV:0.5 MG/M3; 9192

EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name: NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000 Fraction by Wt: 13.2%

Other REC Limits: NONE SPECIFIED

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred Name: MOLYBDENUM

CAS:7439-98-7

RTECS #:QA4680000 Fraction by Wt: 2.25%

Other REC Limits: NONE SPECIFIED

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9293

Ingr

ed Name:IRON CAS:7439-89-6 RTECS #:NO4565500

Fraction by Wt: 64.7%

Other REC Limits: NONE SPECIFIED

========== Hazards Identification ===========================

LD50 LC50 Mixture:UNCLASSIFIED WELDING FUMES=5MG/M3 PEL

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO

Health Hazards Acute and Chronic: CHROMIUM: MAY CAUSE LUNG CHANGES.

COBALT: MAY CAUSE RESPIRATORY IRRITATION & DISEASE. IRON: MAY CAUSE

X-RAY CHANGES OF T

- HE LUNGS. MANGANESE: MAY CAUSE METAL FUME FEVER,
 AFFECT THE NERVOUS SYSTEM & RES PIRATORY SYSTEM DISEASE.
 MOLYBDENUM: MAY CAUSE IRRITATION. NICKEL: MAY CAUSE RESPIRATORY
 DISEASE & ALLERGIC SKIN RASH.
- Explanation of Carcinogenicity:NICKEL, COBALT-CHROMIUM ALLOYS, AND CHROMIUM HAVE BEEN IDENTIFIED BY IARC AND/OR NTP AS POTENTIAL CANCER CAUSING AGENTS.
- Effects of Overexposure: EXPOSURE TO WELDING FUMES MAY CAUSE METAL FUME FEVER WITH SYMPTOMS OF CHILLS, FEVER, NAUSEA, COUGH, DRY THROAT.
 - WEAKNESS, MUSCLE ACHES, AND A SWEET OR METALLIC TASTE IN THE MOUTH. PROLONGED OR REPEATE D EXPOSURE MAY CAUSE DIFFICULTY IN WALKING, WEAKNESS OR CRAMPS IN THE LEGS, HOARSENESS, MEMORY LOSS, SKIN SENSITIZATION
- Medical Cond Aggravated by Exposure:PRE-EXISTING CHRONIC SKIN, EYE OR RESPIRATORY DISORDERS MAY BE AGGRAVATED IF INDIVIDUALS ARE REPEATEDLY OVEREXPOSED TO FUMES AND DUST.

=======================================	First Aid Measures	=======================================

First Aid: IN

HALATION: REMOVE TO FRESH AIR. CONSULT A PHYSICIAN. EYE: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INGESTION: WHILE INGESTI ON OF LARGE ENOUGH QUANTITIES TO CAUSE HEALTH EFFECTS IS UNLIKELY, CONSULT A PHYSICIAN IF IT OCCURS.

Autoignition Temp:Autoignition Temp Text:NONE
Extinguishing Media:USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDIN
G

FIRE.

Unusual Fire/Explosion Hazard: NONE

======== Accidental Release Measures ==========

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSU RE.

========== Handling and Storage ============

Handling and Storage Precautions:WEAR GLOVES AND FLAME RETARDANT CL

Respiratory Protection:WEAR NIOSH APPROVED RESPIRATORS FOR PROTECTION

AGAINST AIRBORNE DUST OR FUMES. RESPIRATORS SHOULD BE USED IN ACCORDANCE WITH 29CFR 1910.134.

Ventilation: USE LOCAL AND GENERAL VENTILATION TO KEEP AIRBORNE CONCENTRATIONS OF DUST OR FUMES BELOW THE TLV DURING USE.

Protective Gloves:WELDERS LEATHER GLOVES

Eye Protection: OSHA APPROVED GOGGLES/FACE SHIELD W/LENS

Other Protective Equipment:BARRIER CREAMS MAY BE NECESSARY TO PREVENT SKIN SENSITIZATION AND DERMATITIS.

Work Hygienic Practices: WASH THOROUGHLY BEFORE EATING OR SMOKING.

LAUNDER CONTAMINATIED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY.
THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING
WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR
ELECTRODES USED. OTHER INFLUENCING FACTORS ARE THEPRESENCE OF
CONTAMINANTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES.

=======================================	Physical/Chemical Properties	=======================================

HCC:N1

Vapor Pres:0

Solubility in Water: NEGLIGIBLE

Appearance and Odor:0.156 INCH DIAMETER BY 14 INCH LONG STAINLESS STEEL COVERED WELDING ROD.

Percent Volatiles by Volume:0

	Stability and F	Reactivity Data	
--	-----------------	-----------------	--

Stability Indicator/Materials to Avoid:YES

STRONG MINERAL ACIDS

Hazardous Decomposition Products:WELDING AND CUTTING OPERATION MAY INCLUDE OXIDES OF THE METALS, CHROMATES, FLUORIDES, COMPLEX METALLICS, AND OZONE.

====== Disposal Consid

erations =========

Waste Disposal Methods:RECYCLE OR DISPOSE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek c ompetent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.