

UNI-KEM INTERNATIONAL INC. -- SPOT REMOVER, AMSCO SOLV 1106 -- 6850-01-015-7939

=====
Product Identification
=====

Product ID:SPOT REMOVER, AMSCO SOLV 1106

MSDS Date:01/01/1987

FSC:6850

NIIN:01-015-7939

MSDS Number: BJYLD

=== Responsible Party ===

Company Name:UNI-KEM INTERNATIONAL INC.

Address:513 HICKORY AVE

City:HARAHAN

State:LA

ZIP:70123

Country:US

Info Phone Num:504-738-1623

Emergency Phone

Num:504-738-1623

Preparer's Name:PAUL PFEIFER

CAGE:4S446

=== Contractor Identification ===

Company Name:UNI-KEM INTERNATIONAL

Address:1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA

ZIP:70001

Country:US

Phone:504-835-7600/FAX:504-835-7608

CAGE:4S446

=====
Composition/Information on Ingredients
=====

Ingred Name:HYDROTREATED LIGHT PETROLEUM DISTILLATE

CAS:64742-47-8

Other REC Limits:NONE SPECIFIED

OSHA PEL:100 PPM

ACGIH TLV:100 PPM

=====
Hazards Identifica

tion =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES/SKIN: IRRITATION. INHALATION:LOW
DEGREE OF TOXICITY. BREATHING HIGH CONCENTRATIONS OF VAPORS OR
MISTS MAY RESULT IN IRRITATION OF THE NOSE AND THROAT AND SIGNS OF
NERVOUS SYSTEM DEPRESSION. INGESTION:LOW DEGREE OF TOXICITY;
HOWEVER IT IS AN ASPIRATION HAZARD. DO NOT INDUCE VOMITING.NARCOSIS
IN HIGH

CONCENTRATION

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC.
OVEREXPOSURE MAY RESULT IN FATIGUE, WEAKNESS, CONFUSION EUPHORIA,
DIZZINESS, HEADACHE, DILATED PUPILS, LACRIMATION, NERVOUSNESS,
MUSCLE FATIGUE, INSOMNIA, PARESTHESIA, DERMATITIS, AND
PHOTOPHOBIA. EYE/SKIN:IRRITATION.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY O
F AILMENTS

OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN,
RESPIRATORY TRACT OR NERVOUS SYSTEM MAY BE AT INCREASED RISK FROM
EXPOSURE. DRYING/CRACKING OF SKIN.

===== First Aid Measures =====

First Aid:EYES: FLUSH WITH RUNNING WATER FOR 15 MINUTES WHILE HOLDING
EYELID. GET MEDICAL ATTENTION IMMEDIATELY. SKIN: WASH WITH SOAP &
WATER. REMOVE CONTAMINATED CLOTHING. GET MEDICAL ADVICE.
INHALATION: REMOVE TO FRESH AIR. GIVE MOUT
H-TO-MOUTH RESUSCITATION
IF NOT BREATHING. GET MEDICAL ATTENTION. INGESTION: DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET MEDICAL
ATTENTION IMMEDIATELY.

===== Fire Fighting Measures =====

Flash Point:100F,38C

Autoignition Temp:Autoignition Temp Text:UNKNOW

Extinguishing Media:USE CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGH

TING CHEMICAL FIRE. USE WATER

SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AND REMOVE WITH INERT ABSORBENT. DIKE AHEAD OF SPILL FOR LATER RECOVERY FOR LARGE SPILLS.

===== Handling and Storage =====

==

Handling and Storage Precautions:CONTENTS ARE FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, AND OPEN FLAME. DURING USE AND UNTIL ALL VAPORS ARE GONE: KEEP AREA VENTILATED-DO NOT SMOKE.

Other Precautions:AVOID BREATHING OF VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH/MSHA APPROVED RESPIRATOR IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL/TLV. WEAR SELF-CONTAINED BREATHING APPARATUS IF REQUIRED FOR HIGH LEVELS OF CONTAMINATES.

Ventilation:LOCAL EXHAUST PREFERABLE. GENERAL EXHAUST ACCEPTABLE IF THE EXPOSURE IS MAINTAINED BELOW APPLICABLE EXPOSURE LIMITS.

Protective Gloves:NEOPRENE OR NATURAL RUBBER GLOVES

Eye Protection:PAINT GOGGLES/SAFETY GLASSES AS REQUIRED

Other Protective Equipment:INDUSTRIAL-TYPE WORK CLOTHING, HAT AND APRON AS REQUIRED.

Work Hygienic Practices:USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR/SPRAY MIST. AVOID CONTACT WITH SKIN & EYES. WASH HANDS AFTER USE.

Supplemental Safety and Health

KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS WITH COMPLETE AND APPROPRIATE LABELING. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. USE APPROVED BONDING AND GROUNDING PROCEDURES.

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:367F,186C

Vapor Density:>1 AIR=1

Spec Gravity:0.782

Evaporation Rate & Reference: