

FISHER SCIENTIFIC, CHEMICAL DIVISION -- ETHYL ACETATE -- 6810-01-327-4568

=====
Product Identification
=====

Product ID:ETHYL ACETATE

MSDS Date:10/09/1990

FSC:6810

NIIN:01-327-4568

MSDS Number: BJYNQ

=== Responsible Party ===

Company Name:FISHER SCIENTIFIC, CHEMICAL DIVISION

Address:1 REAGENT LANE

City:FAIR LAWN

State:NJ

ZIP:07410

Country:US

Info Phone Num:201-796-7100

Emergency Phone Num:201-796

-7100

CAGE:1B464

=== Contractor Identification ===

Company Name:FISHER SCIENTIFIC CO. CHEMICAL MFG DIV

Address:1 REAGENT LANE

Box:City:FAIRLAWN

State:NJ

ZIP:07410-2802

Country:US

Phone:201-796-7100

CAGE:1B464

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 6.0 G/KG

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGESTING CAN CAUSE HEADACHE,
DROWSINESS AND UNCONSCIOUSNESS. PRACTICALLY NON-TOXIC TO ANIMALS.
INHALING IS IRRITATING TO NASAL PASSAGES AND THROAT. CAN CAUSE
STUPOR AND HEADACHES. CAN CAUSE DRYING TO THE SKIN. IRRITATING TO
THE EYES. CHRO

NIC: PPROLONGED EXPOSURE CAN CAUSE NARCOTIC EFFECTS.

Explanation of Carcinogenicity:NONE OF THE COMPOUNDS IN THIS PRODUCT IS
LISTED BY IARC, NTP, OR OSHA AS A CARCINOGEN.

Effects of Overexposure:SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:PERSONS WITH A HISTORY OF AILMENTS
OR WITH A PRE-EXISTING DISEASE INVOLVING THE EYES, SKIN, OR
RESPIRATORY TRACT MAY BE AT INCREASED RISK FROM EXPOSURE.

=====
First Aid Measures
=====

First Aid:INH

ALATION:REMOVE TO FRESH AIR. RESUSCITATE IF NOT BREATHING.

GET MEDICAL ATTENTION. EYES:IMMEDIATELY FLUSH WITH PLENTY OF WATER
FOR 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION.

SKIN:REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER. IF
IRRITATION PERSISTS, GET MEDICAL ADVICE. INGESTION:DO NOT INDUCE
VOMITING. GIVE NOTHING BY MOUTH IF UNCONSCIOUS. GET IMMEDIATE
MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash P

oint Method:CC

Flash Point:24.0F,-4.4C

Autoignition Temp:Autoignition Temp Text:800 F

Lower Limits:2

Upper Limits:11.5

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A
FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL
FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPOR

S.

===== Accidental Release Measures =====

Spill Release Procedures: SHUT OFF IGNITION SOURCES. STOP LEAK IF YOU CAN WITHOUT RISK. USE WATER SPRAY TO REDUCE VAPORS. TAKE UP WITH SAND OR OTHER ABSORBENT OR DIKE IF THE SPILL IS LARGE. ISOLATE AREA.

Neutralizing Agent: NOT APPLICABLE.

===== Handling and Storage =====

Handling and Storage Precautions: STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.

Other Precautions: DO NOT TAKE INTERNALLY. DO NOT BREATHE MIST. AVOID PROLONGED OR REPEATED BREATHING OF VAPOR. AVOID CONTACT WITH EYES. USE WITH ADEQUATE VENTILATION. WASH THOROUGHLY AFTER HANDLING. FOR INDUSTRIAL USE ONLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: IF VENTILATION DOES NOT MAINTAIN INHALATION EXPOSURES BELOW PEL(TLV), USE NIOSH/MSHA APPROVED ORGANIC VAPOR CARTRIDGE AND DUST/MIST PRE-FILTER RESPIRATORS AS PER CURRENT 29 CFR 1910.134, INSTRUCTIONS/ WARNINGS AND NIOSH-RESPIRATOR SELECTION.

Ventilation: MECHANICAL (GENERAL) ROOM VENTILATION IS NORMALLY ADEQUATE. LOCAL EXHAUST MAY BE REQUIRED IF WORK AREA NOT VENTED.

Protective Gloves: NEOPRENE OR RUBBER

Eye Protection: SAFETY GOGGLES WITH OPTIONAL FACE SHIELD

Other Protective Equipment: EYE WASH STATION AND SAFETY SHOWER. INDUSTRIAL-TYPE WORK CLOTHING AND APRON AS REQUIRED.

W

ork Hygienic Practices: OBSERVE GOOD PERSONAL HYGIENE PRACTICES AND RECOMMENDED PROCEDURES. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO NOT BREATHE VAPORS OR MISTS.

===== Physical/Chemical Properties =====

HCC: F2

Boiling Pt: =77.C, 170.6F

Melt/Freeze Pt: =-84.C, -119.2F

Vapor Pres: 73

Vapor Density: 3.04

Spec Gravity: 0.9003

pH: NEUTR.

Evaporation Rate &

; Reference:6.2 (BUTYL ACETATE=1)

Solubility in Water:8.7%

Appearance and Odor:TRANSPARENT, COLORLESS, VOLATILE LIQUID HAVING SLIGHTLY FRUITY ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS, STRONG BASES, CHLOROSULFONIC ACID, LITHIUM TETRAHYDRALUMINATE, NITRATES, OLIUM, OXIDIZERS.

Stability Condition to Avoid:ABNORMAL TEMPERATURES AND PRESSURES.

Hazardous Decomposition Products:MAY INCLUDE TOXIC OXIDES OF CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSAL SHOULD BE MADE IN ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaim

s all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.