

MOBIL OIL CORP -- MOBIL DTE OIL HEAVY MEDIUM -- 9150-00-027-3098

===== Product Identification =====

Product ID:MOBIL DTE OIL HEAVY MEDIUM

MSDS Date:02/28/1991

FSC:9150

NIIN:00-027-3098

MSDS Number: BJYQB

=== Responsible Party ===

Company Name:MOBIL OIL CORP

Address:3225 GALLONS ROAD

City:FAIRFAX

State:VA

ZIP:22037-0001

Country:US

Info Phone Num:800-424-9300

Emergency Phone Num:703-849-3265 OR 212

-883-4411

CAGE:3U728

=== Contractor Identification ===

Company Name:CONVOY OIL CORP

Address:1410 N FRONT STREET

Box:29366

City:PHILADELPHIA

State:PA

ZIP:19125

Country:US

Phone:215-739-5281

CAGE:6A438

Company Name:MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA

ZIP:22037

Country:US

Phone:800-662-4525/ 856-224-4644

CAGE:3U728

===== Composition/Information on Ingredients =====

Ingred Name:DISTILLATES, HYDROTREATED HEAVY P

ARAFFINIC  
CAS:64742-54-7  
RTECS #:PY8035500  
Fraction by Wt: >95.00%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:300 PPM  
ACGIH TLV:300 PPM

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS SLIGHTLY TOXIC  
Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER.  
Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS

LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.  
Effects of Overexposure:EFFETS OF OVEREXPOSURE: SLIGHT SKIN  
IRRITATION.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER. SKIN: WASH CONTACTED AREA WITH SOAP  
AND WATER. INHALATION: NOT EXPECTED TO BE A PROBLEM. INGESTION: NOT  
EXPECTED TO BE A PROBLEM HOWEVER, IF GREATER THAN 1/2 LITER (PINT)  
INGEST ED, IMMEDIA  
TELY GIVE 1 TO 2 GLASSES OF WATER AND CALL A  
PHYSICIA. DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN  
UNCONSCIOUS PERSON.

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:>400F,>204C  
Lower Limits:0.6  
Upper Limits:7.0  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY  
CHEMICAL.  
Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS FOR  
ENCLOSED AREA. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRA

Y.

PREVENT RUNOFF OR DILUTION FROM ENTERING WATERWAYS.

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:ABSORB ON FIRE RETARDANT TREATED SAWDUST,  
DIATOMACEOUS EARTH, ETC. SHOVEL UP & DISPOSE OF AT AN APPROPRIATE  
WASTE DISPOSAL FACILITY.

===== Handling and Storage =====

Handling and Storage Precautions:NONE SPECIFIED BY MANUFACTURER.  
Other Precautions:NO SPECIAL PRECAUTIONS REQUIRED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQUIREMENTS UNDER ORDINARY  
CONDITIONS OF USE AND WITH ADEQUATE VENTILATION.  
Ventilation:NO SPECIAL REQUIREMENTS UNDER ORDINARY CONDITIONS OF USE  
AND WITH ADEQUATE VENTILATION.  
Protective Gloves:NO SPECIAL EQUIPMENT REQUIRED.  
Eye Protection:NO SPECIAL EQUIPMENT REQUIRED.  
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.  
Work Hygienic Practices:GOOD PERSONAL HYGIENE SHOULD ALWAYS BE  
FOLLOWED.  
Supplemental Safety and Health  
NONE

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>600F,>316C  
Vapor Pres: