

TURNER ENGINEERING, INC. -- CHEMICAL CONVERSION -- 8030-00-811-3723

===== Product Identification =====

Product ID:CHEMICAL CONVERSION

MSDS Date:06/16/1987

FSC:8030

NIIN:00-811-3723

MSDS Number: BJZDL

=== Responsible Party ===

Company Name:TURNER ENGINEERING, INC.

Address:3730 EASTSIDE HIGHWAY

City:STEVENSVILLE

State:MT

ZIP:59870

Country:US

Info Phone Num:406-777-2751

Emergency Phone Num:406-777-2

751

CAGE:4S444

=== Contractor Identification ===

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

Company Name:TURCO PRODUCTS, INC.

Address:7300 BOLSA AVE

Box:6200

City:WESTMINSTER

State:CA

ZIP:92684-3600

Country:US

Phone:614-387-6200

CAGE:0BYN5

Company Name:TURNER ENGINEERING, INC.

Address:3730 EASTSIDE HIGHWAY

City:STEVENSVELLE

State:MT

ZIP:59870

Country:US

Phone:406-777-2751

CAGE:4S444

===== Compos

Information on Ingredients =====

Ingredient Name: CHROMIC ACID

CAS: 1333-82-0

RTECS #: GB6650000

Fraction by Wt: 52% *

Other REC Limits: HEXAVALENT CHROM CPD

OSHA PEL: C 0.1 MG/M3 CRO

ACGIH TLV: 0.05 MG/M3 CR3

===== Hazards Identification =====

Routes of Entry: Inhalation: YES Skin: YES Ingestion: NO

Reports of Carcinogenicity: NTP: YES IARC: YES

Explanation of Carcinogenicity: OVEREXPOSURE TO HEXAVALENT CHROME MAY CAUSE LUNG CANCER RISK.

Effects of Over

Exposure: EYES: SEVERE IRRITATION, CONJUNCTIVITIS, CHEMICAL BURN, PERMANENT

TISSUE DAMAGE/BLINDNESS. SKIN: SEVERE IRRITATION, CHEMICAL

BURNS, ULCERATION. CHROMIC ACID IS A SKIN

SENSITIZER. INHALED: ULCERATION/PERFORATION OF NASAL SEPTUM & IRRITATION

& DAMAGE TO RESPIRATORY SYSTEM. SYMPTOMS RESEMBLE THOSE OF

ASTHMA. INGESTION: HARMFUL/FATAL. TOXIC EFFECTS MAY BE DELAYED.

Medical Condition Aggravated by Exposure: CHROMIC ACID IS A SYSTEMIC POISON

AFFECTING THE LIVER, KIDNEYS AND GASTROINTESTINAL TRACT. REPEATED OVER

EXPOSURE MAY AGGRAVATE ANY PRE-EXISTING DYSFUNCTION OF THESE SYSTEMS.

===== First Aid Measures =====

First Aid: EYES: IMMEDIATELY FLUSH WITH LOTS OF H₂O FOR 15 MIN. HOLD LID APART. GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP/H₂O IMMEDIATELY. IRRITATION EVIDENT/BLISTER, GET MEDICAL ATTENTION. INHALED: REMOVE TO FRESH AIR. GIVE O₂ IF BREATH DIFFICULT. GET MEDICAL ATTENTION. INGESTED: IF CONSCIOUS IMMEDIATELY DILUTE BY GIVING LARGE VOLUME OF H₂O. INDUCE VOMIT BY GIVING SYRUP OF IPECAC/TOUCH BACK OF THROAT WITH FINGER. REPEAT

UNTIL VOMIT FLUID IS CLEAR. FOLLOW WITH MORE H₂O/MUCILAGIN. DRINK. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point: NONE

Extinguishing Media: DRY CHEMICAL, CARBON DIOXIDE. AVOID CONTACT OF DRY CHROMIC ACID WITH H₂O IF POSSIBLE. DRY CHROMIC ACID EXPOSED TO HIGH HEAT MAY DECOMPOSE

Fire Fighting Procedures: USE SELF-CONTAINED BREATHING RESPIRATORY PROTECTION & FULL PROTECTIVE GEAR. ANY WATER RUNOFF MAY CONTAIN HEXAVALENT CHROME & SHOULD NOT BE ALLOWED TO ENTER SEWER

S/WATERWAY

Unusual Fire/Explosion Hazard:MAY INCREASE INTENSITY OF FIRE WHEN IN CONTACT W/COMBUSTIBLE MAT'L COOL FIRE EXPOSED CONTAINER CAUTIONLY WITH WATER SPRAY, BEING ALERT FOR POSSIBLE OF STEAM EXPO

===== Accidental Release Measures =====

Spill Release Procedures:USE PROTECT EQUIP.SHOVEL DRY SPILL IN DOT-APPROVED DRUM FOR DISPOSAL.KEEP SOIL DRY UNTIL SWEEP UP/SHOVELED INTO DISPOSAL DRUMS.RESIDUAL AMNTS SHOULD BE DISSOLVED IN WATER & SOLUTION C OLLECTED IN DRUMS FOR DISPOSAL.DO NOT ALLOW TO ENTER SEWER.WATERWAY

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN DRY PROTECTED AREA AWAY FROM STRONG ACIDS OR BASES,REDUCING COMPOUNDS,FLAMMABLE OR COMBUSTIBLE MATERIAL.

Other Precautions:WARNING!SLOWLY ADD TO SOLUTION WHILE MIXING,TAKING CARE TO AVOID SPLASHING OR SPATTERING. USE APPROPRIATE PROTECTIVE EQUIPMENT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR DUST CONDITIONS, A NIOSH-APPROVED RESPIRATOR FOR TOXIC DUST IS ADVISED. IF RESPIRATORS ARE USED, A FORMAL TRAINING AND SCREENING PROGRAM MUST BE INITIATED.

Ventilation:MAINTAIN SUFFICIENT MECHANICAL VENTILATION TO KEEP PARTICULATE CONCENTRATION BELOW TLV.

Protective Gloves:MATERIAL RESISTANT CHROMIC GLOVES

Eye Protection:CHEMICAL FACE SHIELD OR GOGGLES.

Other Protective Equipment:CHEMICAL RESISTANT BOOTS AND APRON.SUIT IS NOT NORMALLY REQUIRED.

Work Hygienic Practices:WASH HANDS/FACE W/SOAP/WATER BEFORE SMOKING OR EATING.IMMED REMOVE CONTAM CLOTHES.WASH BEFORE REUSE.DO NOT WASH AT HOME.

Supplemental Safety and Health

REPAIR AND MAINTENANCE OF CONTAMINATED EQUIP:RELIEVE ANY PRESSURE.COVER OPENINGS TO AVOID SPLASHING.CLEAN EXTERIOR AND INTERIOR BY FLUSHING WITH WATER.COLLECT FLUSHING FOR DISPOSAL.USE PROTECTIVE EQUIPMENT FOR EYES, SKIN AND INHALATION.

===== Physical/Chemical Properties =

=====

HCC:D3

pH:2.0(3%

Solubility in Water:APPRECIABLE

Appearance and Odor:DARK RED FLAKES OF POWDER, LITTLE OR NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:CONTACT WITH STRONG ACIDS,STRONG ALKALI,
REDUCING COMPOUNDS, FLAMMABLE OR COMBUSTIBLE MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:TRANSFER TO RECLAIM CNTR FOR

RECYCLE/REUSE.TRANSFER TO LICENSED HAZARD WASTE TREATMENT/DISPOSAL
SITE FOR DISPOS UNDER APPLICABLE LOCAL,STATE/REGIONAL REGS AS
HAZARDOUS WASTE.SMALL AMTS MAY BE DISSOLVE D IN
H2O,TREATED/RELEASED TO SEWER IF REGS PERMIT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to
be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.