

PERMATEX INDUSTRIAL CORP -- PLASTIC CLEANER 80183 -- 7930-00-935-3794

=====  
Product Identification  
=====

Product ID:PLASTIC CLEANER 80183

MSDS Date:03/30/1990

FSC:7930

NIIN:00-935-3794

MSDS Number: BJZGH

=== Responsible Party ===

Company Name:PERMATEX INDUSTRIAL CORP

Address:30 TOWER LANE

City:AVON

State:CT

ZIP:06001

Country:US

Info Phone Num:203-677-7727

Emergency Phone Num:203-677-7727

Preparer

's Name:STEPHEN REPETTO

CAGE:DO527

=== Contractor Identification ===

Company Name:PERMATEX INDUSTRIAL CORP; LOCTITE CORP

Address:30 TOWER LANE; AVON PARK SOUTH

Box:11915

City:AVON

State:CT

ZIP:06001

Phone:203-677-7727

CAGE:DO527

=====  
Composition/Information on Ingredients  
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 65-70%

Other REC Limits:NONE SPECIFIED

Ingred Name:VM&P NAPHTHA

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 20-25%

Other REC Limi

ts:NONE SPECIFIED  
OSHA PEL:300 PPM/1370 MG/M3  
ACGIH TLV:300 PPM/1350 MG/M3

Ingred Name:CALCIUM CARBONATE  
CAS:471-34-1  
RTECS #:FF9335000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:15MG/M3DUST/5MG/M3RE  
ACGIH TLV:10 MG/M3 DUST

Ingred Name:POLY (DIMETHYLSILOXANE)  
CAS:63148-62-9  
Fraction by Wt: < 1%  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Health Hazards Acute and Chronic:LONG TERM EXPOSURE TO LIQUID MAY CAUSE DRY  
ING AND CRACKING OF SKIN. NARCOSIS AT HIGH CONCENTRATION.  
Effects of Overexposure:DIZZINESS, HEADACHE, NAUSEA. LONG TERM EXPOSURE  
TO LIQUID MAY CAUSE DRYING AND CRACKING OF SKIN. NARCOSIS AT HIGH  
CONCENTRATION.

=====  
First Aid Measures  
=====

First Aid:INGESTION:DO NOT INDUCE VOMITING. OBTAIN MEDICAL ATTENTION.  
INHALATION:REMOVE TO FRESH AIR. IF SYMPTOMS PERSIST, OBTAIN MEDICAL  
ATTENTION. SKIN CONTACT:FLUSH WITH SOAP AND WATER. EYE  
CONTA  
CT:FLUSH WITH WATER AT LEAST 15 MINUTES AND OBTAIN MEDICAL  
ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC  
Flash Point:80F/27C  
Lower Limits:1  
Upper Limits:12  
Extinguishing Media:CARBON DIOXIDE, FOAM, DRY CHEMICAL

=====  
Accidental Release Measures  
=====

Spill Release Procedures:SOAK UP IN ANY INERT ABSORBENT AND STORE IN A  
CLOSED CONTAINER UNTIL DISPOSAL.

=====  
Handling and Storage  
=====

=====

Handling and Storage Precautions:STORE AWAY FROM HEAT OR FLAME. AVOID PROLONGED BREATHING OF FUMES. AVOID PROLONGED SKIN CONTACT. DO NOT USE NEAR HEAT OR FLAMES.

===== Exposure Controls/Personal Protection =====

Ventilation:MUST BE ADEQUATE TO AVOID EXCEEDING TLV.  
Protective Gloves:IMPERMEABLE GLOVES FOR PROLONGED USE.  
Eye Protection:SAFETY GLASSES OR GOGGLES.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3  
Vapor Density:4.7  
Spec Gravity:0.99 @ 60F  
pH:7  
Solubility in Water:MISCIBLE  
Appearance and Odor:WHITE CREAMY LIQUID, MILD PETROLEUM ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS  
Hazardous Decomposition Products:BY FIRE OR THERMAL DECOMP:IRRITATING ORGANIC VAPORS.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE FOLLOWING EPA AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information

to their  
particular situation.