

RED DEVIL INCORPORATED -- WOOD PUTTY POWDER P/N 0511 -- 8030-01-010-9289

=====  
Product Identification  
=====

Product ID:WOOD PUTTY POWDER P/N 0511

MSDS Date:01/01/1987

FSC:8030

NIIN:01-010-9289

MSDS Number: BJZHK

=== Responsible Party ===

Company Name:RED DEVIL INCORPORATED

Address:WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74362

Country:US

Info Phone Num:918-825-5744

Emergency Phone Num:918-825-57

44

CAGE:DO902

=== Contractor Identification ===

Company Name:RED DEVIL INCORPORATED

Address:WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74362

Country:US

CAGE:DO902

Company Name:RED DEVIL, INCORPORATED

Address:ONE WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74361

Country:US

Phone:918-825-5744

CAGE:23577

=====  
Composition/Information on Ingredients  
=====

Ingred Name:GYPSUM & ALUMINUM SILICATE (AS NUISANCE PARTICULATE, TOTAL)

CAS:8031-18-3

Fraction by Wt: 100%

Other REC Limits:NONE

SPECIFIED  
OSHA PEL:15 MG/M3  
ACGIH TLV:10 MG/M3

Ingred Name:SILICA (AS QUARTZ, RESPIRABLE DUST)  
CAS:112945-52-5  
RTECS #:VV7310000  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:10 MG/M3

Ingred Name:WOOD FLOUR (AS WOOD DUST)  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:1 MG/M3

=====  
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:CHRONIC OVEREXPOSURE TO DUSTS  
CONTAINING QUARTZ MAY RESULT IN LUNG DAM  
AGE.  
Effects of Overexposure:INHALATION OF DUST MAY CAUSE RESPIRATORY  
IRRITATION. POSSIBLE SKIN IRRITATION. EYE CONTACT CAUSES  
IRRITATION.

=====  
===== First Aid Measures =====

First Aid:EYES:FLUSH EYES WITH LARGE AMOUNTS OF WATER. GET MEDICAL  
ATTENTION IF IRRITATION PERSISTS. SKIN:WASH THOROUGHLY WITH SOAP  
AND WATER. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.  
INHALATION:MOVE VICTI M TO FRESH AIR. GET MEDICAL HELP IF  
IRRITATION PERSISTS  
. INGESTION:CONTACT LOCAL POISON CONTROL CENTER  
OR PHYSICIAN IMMEDIATELY.

=====  
===== Fire Fighting Measures =====

Flash Point:NONE  
Extinguishing Media:USE MEDIA SUITABLE FOR ADJACENT MATERIALS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:CAREFULLY CLEAN UP SPILLED MATERIAL AND PLACE  
IN DRY CONTAINERS FOR DISPOSAL. AVOID DUST GENERATION.

=====  
===== Handling and Storage =====

H

Handling and Storage Precautions:STORE IN CLOSED CONTAINER IN DRY AREA.  
THIS PRODUCT DOES NOT CONTAIN INGREDIENTS LISTED IN SARA TITLE III.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF  
OVEREXPOSURE, WEAR NIOSH-APPROVED RESPIRATOR FOR DUST AND MISTS.

Ventilation:LOCAL EXHAUST MAY BE NECESSARY UNDER SOME HANDLING/USE  
CONDITIONS.

Protective Gloves:NOT NORMALLY REQUIRED

Eye Protection:WEAR CHEMICAL GOGG  
LES.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

Spec Gravity:> 2.0

Solubility in Water:SLIGHT

Appearance and Odor:POWDER, ODORLESS

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE,  
SULFUR DIOXIDE.

=====  
Disposal Considerations  
=====

Waste Disposal Methods:DISPOSE OF IN ACCO  
RDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.