View NSN Online: https://aerobasegroup.com/nsn/7930-00-559-9481

Product ID:SODIUM BISULFATE/CID AA460

MSDS Date:04/07/1986

FSC:7930

NIIN:00-559-9481

MSDS Number: BJZVY === Responsible Party ===

Company Name: JONES-HAMILTON CO Address: ENTERPRISE AT WILLOW

Box:464

City:NEWARK

State:CA ZIP:94560 Country:US

Info Phone Num:415-797-2471 OR 419-666-9838

Emergency Ph

one Num:415-797-2471(CHEMTREC 800-424-9300)

CAGE:93594

=== Contractor Identification ===

Company Name: JONES-HAMILTON CO. Address: 8400 ENTERPRISE DRIVE

Para Cita NEWADIA

Box:City:NEWARK

State:CA ZIP:94560 Country:US

Phone:510-797-2471/510-792-4500

CAGE:93594

======= Composition/Information on Ingredients ========

Ingred Name: SODIUM BISULFATE ANHYDROUS GLOBULAR (SODIUM ACID SULFATE,

NITRE CAKE) CAS:7681-38-1

RTECS #:VZ1860000 Fraction by Wt: 94.5%

Other REC Limits: NONE SPECIFIED

| ==== Hazards Identification ============= |
|--|
| Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INCLUDING SIGNIFICANT ROUTES EFFECTS, SYMPTOMS OF OVER EXPOSURE & MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE. Effects of Overexposure:WATERING OF EYES, MILD SKIN BURNS, MILD BURNING SENSATION MAY OCCUR TO MUCOUS MEMBRANES & UPPER RESPIRATORY TRACT. INHALATION: IRRITANT. SKIN: MILD TO SEV ERE IRRITANT. INGESTION: IRRITANT. |
| ====================================== |
| First Aid:EYES:FLUSH THOROUGHLY WITH WATER FOR 15 MINUTES, GET PROMPT MEDICAL ATTENTION. SKIN:FLUSH WITH WATER FOR 15 MINUTES. IF BURNS OCCUR OBTAIN MEDICAL HELP. INHALE:MOVE TO FRESH AIR LOCATION. SWALLOW:DRIN K LARGE QUANTITIES OF WATER/MILK, FOLLOW WITH MILK OF MAGNESIA, BEATEN EGGS OR VEGETABLE OIL. DO NOT INDUCE VOMITING. CONTACT PHYSICIAN IMMEDIATELY. |
| ======= |
| ======= Fire Fighting Measures ========== |
| Flash Point:NONE Extinguishing Media:WATER OR DRY CHEMICAL AS APPROPRIATE FOR COMBUSTIBLES IN AREA Fire Fighting Procedures:WHEN WATER USED TO EXTING COMBUSTIBLES/PRODUCT IS DISSOLVED IN WATER FORMING SULFURIC ACID.USE ACID PROTECTIVE EQUIP. ELEVATED TEMPS(+570F)IS REACHED, USE SCBA Unusual Fire/Explosion Hazard:PRODUCT READILY DISSOLVES IN WATER TO FORM WEAK SULFURIC ACID SOLUTION. NO GASES, TOXIC FUMES ARE EMITTED |
| FROM REACTION, BUT PRECAUTIONS SHOULD BE FOLLOWED. |
| ========= Accidental Release Measures ========== |
| Spill Release Procedures:SMALL:MATERIAL IS A GRANULAR PRODUCT & CAN BE SWEPT UP FROM SURFACES. LARGE:PICK UP AS MUCH AS POSSIBLE W/SHOVEL OR OTHER TOOL. NEUTRALIZE BALANCE OF SPILL W/WEAK ALKALINE SOLUTION & WASH DOWN TO SEWE R IF FEDERAL, STATE & LOCAL REGULATIONSPERMITS. |
| ====================================== |
| Handling and Storage P |

| /Chemical Properties ========== |
|--|
| HCC:C1 Melt/Freeze Pt:M.P/F.P Text:350F,177C Solubility in Water:100% Appearance and Odor:OFF-WHITE, BEAD LIKE, GRANULAR, DRY MATERIAL |
| ======== Stability and Reactivity Data ======== |

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH STRONG ALKALINE MATERIAL SUCH AS CAUSTIC. REACT WITH WATER TO FORM WEAK SULFURIC ACID SOLUTION.

Stability Condition to Avoid:STORE IN DRY AREA TO AVOID MOISTURE CONTACT

Hazardous Deco

mposition Products: NONE UNLESS HEATED OVER 570F AT WHICH SULFUR DIOXIDE & SULFUR TRIOXIDE ARE FORMED.

======= Disposal Considerations ==========

Waste Disposal Methods: COMPLY WITH ALL THE STATE, FEDERAL & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrant

s this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.