View NSN Online: https://aerobasegroup.com/nsn/7930-00-633-9849

## FRANK MILLER & SONS, INC. -- GSA TYPE II SWEEPING COMPOUND -- 7930-00-633-9849

Product ID:GSA TYPE II SWEEPING COMPOUND

MSDS Date:04/07/1989

FSC:7930

NIIN:00-633-9849

MSDS Number: BJZWF === Responsible Party ===

Company Name: FRANK MILLER & SONS, INC. Address: 13831 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL ZIP:60627 Country:US

Info Phone Num:312-468-3500

Emergen

cy Phone Num:312-468-3500

Preparer's Name: RICHARD L. KUDIA

CAGE:DO285

=== Contractor Identification ===

Company Name:FRANK MILLER & SONS, INC Address:13831 SOUTH EMERALD AVENUE

City:CHICAGO

State:IL ZIP:60627

Phone:312-468-3500

CAGE:DO285

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000 Fraction by Wt: 15-18% OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name: CELLULOSE (PAPE

OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3; 9192 Ingred Name:SAND CAS:112945-52-5 RTECS #: VV7310000 Fraction by Wt: 40-50% =========== Hazards Identification ========================== Health Hazards Acute and Chronic:EYE IRRITATION. SKIN IRRITATION OR DERMATITIS. First Aid:RINSE EYE WITH COPIOUS AMOUNTS OF WATER, SEEK PHYSICIAN IF NECESSARY. WA SH SKIN WITH SOAP AND WATER. Autoignition Temp: Autoignition Temp Text:>250F Extinguishing Media: NORMAL AGENTS FOR EXTINGUISHING WOOD FIRES--WATER SPRAY, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures: MAT'L WILL SUPPORT COMBUSTION. MAY BE DRENCHED W/WATER TO REDUCE FIRE HAZARD. MAT'L MAY SMOLDER AFTER INVOLVED IN FIRE. SPREAD MAT'L OUT TO BE SURE FIRE EXTING. ======= Accidental Release Measures Spill Release Procedures: SWEEP UP MATERIAL AND RETURN TO CONTAINER OR DISCARD. ============ Handling and Storage =========================== Handling and Storage Precautions: KEEP OUT OF THE REACH OF CHILDREN. KEEP CONTAINER CLOSED WHEN NOT IN USE. STORE IN A COOL, DRY PLACE. USE NORMAL GOOD HOUSEKEEPING PRACTICES. Other Precautions: READ LABEL CAUTIONS AND DIRECTIONS BEFORE USE. ====== Exposure Controls/Personal Protection ======== Respira

R FIBER)

CAS:9004-34-6

RTECS #:FJ5691460 Fraction by Wt: 26-36%

Eye Protection:GENERALLY NOT REQUIRED. Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:V7 Spec Gravity:4.50-4.90 #/GAL Solubility in Water:INSOLUBLE Appearance and Odor:BROWN TO TAN GRANULAR MATERIAL, WAX ODOR.
========= Stability and Reactivity Data ==========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:IGNITION SOURCES Hazardous Decomposition Products:CARBON DIOXIDE AND CARBON MONOXIDE IF BURNED.
======== Disposal Considerations ===========
Wasto Disposal Mothods:MATERIAL MAY BE DUMPED BUT FOULOW LOCAL

Waste Disposal Methods:MATERIAL MAY BE DUMPED, BUT FOLLOW LOCAL POLLUTION ORDINANCES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

Protective Gloves: RECOMMENDED IF SENSITIVE TO PETROLEUM.

tory Protection: USUALLY NOT REQUIRED.

Ventilation:FRESH AIR.

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.