View NSN Online: https://aerobasegroup.com/nsn/3439-00-968-3557

## AUFHAUSER BROTHERS CORP -- SILVER ALLOY A -- 3439-00-968-3557

Product ID:SILVER ALLOY A MSDS Date:02/21/1990 FSC:3439 NIIN:00-968-3557 MSDS Number: BJZXH === Responsible Party === Company Name: AUFHAUSER BROTHERS CORP Address:39 WEST MALL City:PLAINVIEW State:NY ZIP:11803-4209 Country:US Info Phone Num:516-694-8696 Emergency Phone Num:516-694-8696 CAGE:59401 === Contractor Identification === Company Name: AUFHAUSER CORP Address:39 WEST MALL Box:City:PLAINVIEW State:NY ZIP:11803-4209 Country:US Phone:212-757-6824/FAX: 516-694-8690 CAGE:59401 Ingred Name:SILVER (SARA III) CAS:7440-22-4 RTECS #:VW3500000 Fraction by Wt: 20-50% Other REC Limits:NONE SPECIFIED OSHA PEL:0.01 MG/M3 ACGIH TLV:0.1 MG/M3; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:COPPER (SARA III) CAS:7440-50-8 RTEC S #:GL5325000 Fraction by Wt: 15-45% Other REC Limits:NONE SPECIFIED OSHA PEL:0.1MG/M3 FUME/1 DUST ACGIH TLV:0.2MG/M3 FUME; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ZINC (SARA III) CAS:7440-66-6 RTECS #:ZG8600000 Fraction by Wt: 15.5-30% Other REC Limits:5 MG/M3 AS OXIDE FUM OSHA PEL:10 MG ZNO/M3 ACGIH TLV:10 MG ZNO/M3; 9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:NICKEL (SARA III) CAS:7440-02-0 RTECS #:QR5950000 Fraction by Wt: 0-3% Other REC Limits:NONE SPEC IFIED OSHA PEL:1 MG/M3 ACGIH TLV:1 MG/M3; 9192

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO Health Hazards Acute and Chronic:SHORT TERM EXPOSURE TO WELDING FUMES, GASES OR DUST MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE NOTED. L ONG TERM EXPOSURE TO

FUMES/GASES/DUST MAY CAUSE PULMONARY IRRITATION OR PNEUMOCONIOSIS. Explanation of Carcinogenicity:NICKEL IS CONSIDERED CARCINOGEN NTP AND IARC. RESPIRATORY CANCER FROM WELDING/BRAZING IS UNCONFIRMED. Effects of Overexposure:EXPOSURE TO WELDING/BRAZING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, FEVER, DRYNESS AND/OR IRRITATION OF NOSE, THROAT AND EYES. SKIN SENSITIVITY MAY ALSO BE NOTED. WATERY EYES, HEADAC HE, BREATHING DIFFICULTY, FREQUENT COUGHING AND/OR CH EST PAINS MAY OCCUR FROM ACUTE EXPOSURE. TOXIC GASES CAN BE FATAL. Medical Cond Aggravated by Exposure: INDIVIDUALS WITH IMPAIRED PULMONARY FUNCTION OR ILLNESS MAY HAVE SYMPTOMS EXACERBATED BY IRRITANTS CONTAINED IN WELDING FUMES. First Aid:IN CASE OF ELECTRICAL SHOCK, TURN OFF POWER PRIOR TO REMOVAL FROM EXPOSURE AREA AND ADMINISTRATION OF FIRST AID. REMOVE FROM EXPOSURE AREA AND CALL FOR MEDICAL AID. ADMI NISTER OXYGEN IF BREATHING IS D IFFICULT. IF NOT BREATHING, BEGIN ARTIFICIAL RESPIRATION. IF NO DETECTABLE PULSE, BEGIN EXTERNAL HEART MASSAGE. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS. Extinguishing Media: USE DRY CHEMICAL. Fire Fighting Procedures: WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. EVACUATE AREA. COOL FIRE EXPOSED CONTAINER S WITH WATER SPRAY. Unusual Fire/Explosion Hazard: MAY PRODUCE HAZARDOUS METAL FUMES Spill Release Procedures: CLEAN UP ANY GRINDING DUST OR WASTE RESIDUES AND PLACE IN SUITABLE DOT APPROVED CONTAINERS AND DISPOSE OF IN FULL COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. AVOID INHALATION AND SKIN EXPOSU RE. Handling and Storage Precautions:W EAR GLOVES AND FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING. Other Precautions: PROVIDE PROTECTIVE SCREENS TO SHIELD OTHERS. WHEN ELECTRODES AND FLUXES ARE CONSUMED, THE FUME AND GAS DECOMPOSITION PRODUCTS GENERATED ARE DIFFERENT IN FORM FROM THE INGREDIENTS LISTED. NEW COMPOUNDS NOT IN THE ELECTRODES MAY FORM.

======= Exposure Controls/Personal Protection ==========

**Respiratory Protection** 

:USE WELD FUME RESPIRATOR OR AIR SUPPLIED RESPIRATOR WHEN CUTTING, GRINDING OR WELDING IN A CONFINED SPACE OR WHERE LOCAL EXHAUST OR GENERAL VENTILATION DOES NOT KEEP EXPOSURE BELOW RECOMMENDED LIMITS. USE ONLY NIOSH APPROVED RESPIRATORS. Ventilation: USE ENOUGH VENTILATION WHEN CUTTING, GRINDING OR WELDING TO KEEP THE DUST, FUMES & GASES FROM THE WORKERS BREATHING ZONE Protective Gloves: FLAMEPROOF GAUNTLER GLOVES Eye Protection: OSHA APPROVED GOGGLES/FACE SHIELD W/LENS Other Prot ective Equipment: FLAME RETARDANT CLOTHING WHEN CUTTING, GRINDING OR WELDING. DO NOT EXPOSE SKIN TO RADIATION WHEN HOT CUTTING OR WELDING. Work Hygienic Practices: WASH THOROUGHLY BEFORE EATING OR SMOKING. LAUNDER CONTAMINATIED CLOTHING BEFORE REUSE. Supplemental Safety and Health WELDING AND HOT CUTTING FUMES & GASES CANNOT BE CLASSIFIED SIMPLY. THEIR COMPOSITION AND QUANTITY ARE DEPENDENT ON THE METAL BEING WELDED, THE PROCEDURES, PROCESSES AND THE TYPE OF WIRE OR **ELECTRO** DES USED. OTHER INFLUENCING FACTORS ARE THEPRESENCE OF CONTAMINANTS. CHLORINATED SOLVENTS MAY DECOMPOSE TO TOXIC GASES. HCC:N1 Melt/Freeze Pt:M.P/F.P Text:1125F,607C Spec Gravity:9.5 Solubility in Water: INSOLUBLE Appearance and Odor:ROD Stability Indicator/Materials to Avoid:YES STRONG ACIDS AND BASES Stability Condition to Avoid:NONE Hazardous Decompos ition Products:WELDING/CUTTING OPERATIONS MAY INCLUDE ELEMENTAL METALS, OXIDES OF THE METALS, FUMES/GASES &

ELECTROMAGNETIC RADIATION.

Waste Disposal Methods: DISPOSE I/A/W FEDERAL, STATE & LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, exp ressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.