View NSN Online: https://aerobasegroup.com/nsn/7930-01-054-2097

Product ID:CONQ-R-DUST PRESSURIZED, 14750-005 MSDS Date:11/19/1984 FSC:7930 NIIN:01-054-2097 MSDS Number: BJZXX === Responsible Party === Company Name:S C JOHNSON & SON, INC Address:1520 HOWE ST. City:RACINE State:WI ZIP:53403-5011 Country:US Info Phone Num:414-631-2777 **Emergency Ph** one Num:414-631-2777 Preparer's Name: GORDON B. BRADSHAW CAGE:0U826 === Contractor Identification === Company Name:S C JOHNSON & SON INC/PROF WAX DIV Address:1525 HOWE ST City:RACINE State:WI ZIP:53403 Country:US Phone:800-725-6737/414-886-1480 INTNL# CAGE:0U826 Company Name:SC JOHNSON AND SON INC Address:1525 HOWE ST Box:City:RACINE State:WI ZIP:53403-2236 Country:US Phone:800-725-6737 CAGE:32204

Ingred Name: MINERAL SEAL OIL

CAS:64742-48-8 RTECS #:PY8036500 Fraction by Wt: 75-85% Other REC Limits:5 MG/M3 (MIST)

Ingred Name:ISOPARAFFINIC HYDROCARBON Fraction by Wt: 7-12% Other REC Limits:400-500 PPM (EST)

Ingred Name:N-AMYL ACETATE (SARA III) CAS:628-63-7 RTECS #:AJ1925000 Fraction by Wt: < 1% Other REC Limits:100 PPM OSHA PEL:100 PPM ACGIH TLV:100 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTANE/PROPANE Fraction by Wt: 10-20% Other REC Limits:1000 PPM (EST)

====== Hazard

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES Health Hazards Acute and Chronic:IF TAKEN INTERNALLY, ASPIRATION OF LIQUID PRODUCT CAN CAUSE CHEMICAL PNEUMONITIS.

First Aid:IF PRODUCT IS SWALLOWED, DO NOT INDUCE VOMITING. SEEK MEDICAL AID AT ONCE.

Flash Point:NR
Extinguishing Media:FOAM, CO2, DRY CHEMI
CAL, WATER FOG.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHES. FIGHT FIRE FROM MAXIMUM DISTANCE OR PROTECTED AREA. COOL & USE CAUTION AROUND EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:AEROSOL PRODUCT-FIRE EXPOSED CNTNRS MAY ROCKET/EXPLODE. MISTS/SPRAYS MAY BE FLAMMABLE AT TEMPS BELOW FLASH PT. VAPORS ACCUMULATE IN CONFINED/POOR VENTED AREAS.

Spill Release Procedure

SELIMINATE ALL IGNITION SOURCES. DO NOT LET SPILLED OR LEAKING MATERIAL ENTER WATERCOURSES. CONTAINS AMYL ACETATE. MAY BE TOXIC TO AQUATIC LIFE. ABSORB WITH OIL-DRI OR SIMILAR INERT MATERIAL. SWEEP OR SCRAPE UP AND CONTAINERIZE.

Handling and Storage Precautions:STORE IN COOL, DRY PLACE WITH GOOD VENTILATION. KEEP OUT OF REACH OF CHILDREN. DO NOT STORE NEAR HEAT OR WHERE TEMPS ARE ABOVE 120F.

Other Precaut

ions:DO NOT PUNCTURE OR THROW IN FIRE. PRODUCT RESIDUE MAY REMAIN ON/IN EMPTY CONTAINERS. ALL PRECAUTIONS FOR HANDLING THE PRODUCT MUST BE USED IN HANDLING THE EMPTY CONTAINER AND RESIDUE. DO NOT PRESSURIZ E, CUT, HEAT, WELD, OR FLAME EXPOSE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NSR Ventilation:GENERAL ROOM VENTILATION ADEQUATE. Protective Gloves:NSR Eye Protection:NSR Work Hygienic Practices:USE GOOD PERSONAL HYGIENE PRACTICES.

Supplemental Safety and Health

HCC:V3 Boiling Pt:B.P. Text:ND Vapor Pres:ND Vapor Density:ND Spec Gravity:0.9 Evaporation Rate & amp; Reference:NA Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR, SLIGHTLY YELLOW MIST, BANANA ODOR

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:ALL FIRES PRODUCE IRRITATING/POISONOUS G Waste Disposal Methods:DISPOSE OF AEROSOL CAN BY WRAPPING AND PLACING IN TRASH. DO NOT PUNCTURE OR BURN CONTAINER. DISPOSE OF SPILLED RESIDUES AND MULTIPLE UNITS IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no m anner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.