

CREST INDUSTRIAL CHEMICALS INC -- PBW 20 -- 6850-00-559-2836

=====  
Product Identification  
=====

Product ID:PBW 20  
MSDS Date:01/01/1987  
FSC:6850  
NIIN:00-559-2836  
MSDS Number: BKBCX  
=== Responsible Party ===  
Company Name:CREST INDUSTRIAL CHEMICALS INC  
Address:6341 BEVERLY HILL  
Box:42242  
City:HOUSTON  
State:TX  
ZIP:77242  
Country:US  
Info Phone Num:713-780-8169  
Emergency Phone Num:713-780-8169  
CAGE:7751

3  
=== Contractor Identification ===  
Company Name:CREST INDUSTRIAL CHEMICALS INC  
Address:6341 BEVERLY HILL  
Box:42242  
City:HOUSTON  
State:TX  
ZIP:77057-6500  
Country:US  
Phone:713-780-1828  
CAGE:77513

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIESEL FUEL  
Fraction by Wt: 80%  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:200 PPM

=====  
Hazards Identification  
=====

Health Hazards Acute and Chronic:INHALATION:CAUSES SEVERE LUNG  
IRR

ITATION. INGESTION: CAUSES NAUSEA, VOMITING & CRAMPING. SIGNS OF KIDNEY & LIVER DAMAGE MAY BE DELAYED.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:LOCAL IRRITATION. DROWSINESS, NAUSEA, VOMITING, CRAMPING & DEPRESSION OF CENTRAL NERVOUS SYSTEM RANGING FROM MILD HEADACHE TO ANETHYSIA, COMA & POSSIBLE DEATH.

Medical Cond Aggravated by Exposure:ASPIRATION CAUSES SEVERE LUNG IRRITATION WITH COUGHING, GAGGING, DYSPNEA, SUBSTERNAL DISTRESS & RAPIDLY DEVELOPING PULMONARY EDEMA.

=====  
First Aid Measures  
=====

First Aid:SKIN CONTACT:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER, OBTAIN MEDICAL ATTENTION. INGESTION:DO NOT INDUCE VOMITING. ASPIRATION:ENFORCE BED REST, ADMINISTER OXYGEN, SEEK MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point Method:TCC

Flash Point:142F,61C

Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICAL

Fire Fighting Procedures:AS FOR PETROLEUM FIRE

Unusual Fire/Explosion Hazard:WATER MAY BE INEFFECTIVE ON FIRE. USE WATER TO COOL CONTAINER.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VENTILATE AREA. WIPE UP SPILLAGE. CONTAIN AS NECESSARY. TRANSFER TO METAL CONTAINERS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:TRANSPORT & STORE IN CLOSED CONTAINERS AT TEMPERATURES BETWEEN 32F & 120F

=====  
Exposure Controls/Personal Protection  
=====

Ventilation:MECHANICAL (GENERAL)

Protective Gloves:YES

Eye Protection:FACE SHIELD

Work Hygienic Practices:IF SPILLED ON CLOTHING REMOVE & WASH CLOTHING.

Supplemental Safety and Health

OTHER COMPONENTS NOT DEFINED AS HAZARDOUS BY THE U.S. DEPT. OF LABOR.

=====  
Physical/Chemical Properties  
=====

HCC:V4

Boiling Pt:B.P. Text:355F,179C

Melt/Freeze Pt:M.P/F.P Text:5

Vapor Pres:10MM

Vapor Density:1

Spec Gravity:0.87

Evaporatio

n Rate & Reference:1 (BUTYL ACETATE=1)

Solubility in Water:MODERATE

Appearance and Odor:CLEAR AMBER LIQUID, SOLVENT ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:AS FOR PETROLEUM SOLVENTS. MUST BE IN COMPLIANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. DO NOT DUMP INTO SEWERS, ON THE GROUND OR ANY BODY OF WATER.

Disclaim

er (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.