

CREST INDUSTRIAL CHEMICALS INC -- PBW 20 -- 6850-00-965-2331

=====
Product Identification
=====

Product ID:PBW 20
MSDS Date:01/01/1987
FSC:6850
NIIN:00-965-2331
MSDS Number: BKCFG
=== Responsible Party ===
Company Name:CREST INDUSTRIAL CHEMICALS INC
Box:42242
City:HOUSTON
State:TX
ZIP:77242
Country:US
Info Phone Num:713-780-1828
Emergency Phone Num:800-255-3924
CAGE:77513
=== Contractor Identific
ation ===
Company Name:CREST INDUSTRIAL CHEMICALS INC
Address:6341 BEVERLY HILL
Box:42242
City:HOUSTON
State:TX
ZIP:77057-6500
Country:US
Phone:713-780-1828
CAGE:77513

=====
Composition/Information on Ingredients
=====

Ingred Name:DIESEL FUEL
Fraction by Wt: 80%
Other REC Limits:NONE SPECIFIED
ACGIH TLV:200 PPM

=====
Hazards Identification
=====

Health Hazards Acute and Chronic:INHALATION: SEVERE LUNG IRRITATION.
INGESTION: NAUSEA, VOMI

TING AND CRAMPING. SIGNS OF KIDNEY AND LIVER
DAMAGE MAY BE DELAYED.

Effects of Overexposure:LOCAL IRRITATION. DROWSINESS, NAUSEA, VOMITING,
CRAMPING AND DEPRESSION OF CENTRAL NERVOUS SYSTEM RANGING FROM
MILD HEADACHE TO ANETHYSIA, COMA AND POSSIBLE DEATH. ASPIRATION
CAUSES SEVERE LUNG IRRITATION WITH COUGHING, GAGGING, DYSPNEA,
SUBSTERNAL DISTRESS AND RAPIDLY DEVELOPING PULMONARY EDEMA.

=====
===== First Aid Measures =====

First Aid:SKIN CONTACT: WASH WITH SOAP AND WATER. EYES: FLUSH WITH
WATER, OBTAIN MEDICAL ATTENTION. INGESTION: DO NOT INDUCE VOMITING.
ASPIRATION: ENFORCE BED REST. ADMINISTER OXYGEN, SEEK MEDICAL
ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:142F,61C
Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICAL.
Fire Fighting Procedures:AS FOR PETROLEUM FIRE.
Unusual Fire/Explosion Hazard:WATER MAY BE INEFFECTIVE ON FIRE. USE
WATER TO COOL CONTAINER.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA. WIPE UP SPILLAGE. CONTAIN AS
NECESSARY. TRANSFER TO METAL CONTAINERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:TRANSPORT AND STORE IN CLOSED
CONTAINERS AT TEMPERATURES BETWEEN 32F AND 120F.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:MECHANICAL VENTILATION.
Pr

Protective Gloves: YES.

Eye Protection: FACESHIELD.

Work Hygienic Practices: IF SPILLED ON CLOTHING REMOVE AND WASH CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: V4

Boiling Pt: B.P. Text: 355F, 179C

Melt/Freeze Pt: M.P/F.P Text: 5

Vapor Pres: 10MM

Vapor Density: 1

Spec Gravity: 0.87

Evaporation Rate & Reference: 1 (BU AC=1)

Solubility in Water: MODERATE

Appearance and Odor: CLEAR AMBER LIQUID, SOLVENT ODOR.

===== Stability

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

===== Disposal Considerations =====

Waste Disposal Methods: AS FOR PETROLEUM SOLVENTS. MUST BE IN COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. DO NOT DUMP INTO SEWERS, ON THE GROUND OR ANY BODY OF WATER.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The

United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.