View NSN Online: https://aerobasegroup.com/nsn/3439-00-246-0566

THERMACOTE- WELCO CO, SUB OF FOSTER WHEELER CORP -- W 1200 (RG 60) -- 3439-00-246-0566

============= Product Identification ================

Product ID:W 1200 (RG 60) MSDS Date:07/12/1990

FSC:3439

NIIN:00-246-0566

MSDS Number: BKHJS === Responsible Party ===

Company Name: THERMACOTE- WELCO CO, SUB OF FOSTER WHEELER CORP

Address:1051 YORK RD City:KINGS MOUNTAIN

State:NC ZIP:28086 Country:US

Info Phone Num:704-739-642

1

Emergency Phone Num:704-739-6421

CAGE:3U142

=== Contractor Identification ===

Company Name: HOLOX Address: 4310 N PALAFOX

Box:8284

City:PENSACOLA

State:FL

ZIP:32505-2921 Country:US

Phone:904-438-1436

CAGE:9F235

Company Name: THERMACOTE- WELCO CO, SUB OF FOSTER WHEELER CORP

Address:1051 YORK RD

Box:828

City:KINGS MOUNTAIN

State:NC ZIP:28086 Country:US

Phone:800-424-9300

CAGE:3U142


======= Composition/Information on Ingredients ========

Ingred Name: NO INGREDIENT FOR THIS FORMULATION_

INGREDIENT
======================================
LD50 LC50 Mixture:ORAL LD50 (RAT) IS NOT RELEVANT. Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE- OVEREXPOSURE TO WELDING FUMES MAY RESULT IN DISCOMFORT SUCH AS DIZZINESS, NAUSEA, DRYNESS/IRRITATION OF NOSE, THROAT, EYES. ARC RAYS CAN INJURE EYES & BURN SKIN. ELECTRIC SHOCK CAN KILL. CHRONI C- OVEREXPOSU RE MAY LEAD TO SIDEROSIS (IRON DEPOSITS IN LUNG). TARGET ORGANS:EYES, SKIN, RESPIRATORY TRACT. Explanation of Carcinogenicity:NONE Effects of Overexposure:DIZZINESS, NAUSEA, HEADACHE, DRYNESS OR IRRITATION OF NOSE, THROAT OR EYES, EYE INJURY, SKIN BURN Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THE WELDING FUMES.
======================================
First Aid:CA LL PHYSICIAN IN ALL CASES. EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY THE AMERICAN RED CROSS. PROVIDE OXYGEN/CPR IF NEEDED. IN CASE OF ELECTRIC SHOCK, DISCONNECT EQUIPMENT.
======================================
Flash Point:NONE Extinguishing Media:THIS ALLOY IS NONCOMBUSTIBLE. TO EXTINGUISH A METAL FIRE, USE DRY SAND. Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXP OSED CONTAINERS WITH WATER SPRAY. Unusual Fire/Explosion Hazard:NONE. IN CONTACT WITH ACIDS, HYDROGEN GAS WILL BE FORMED WHICH IS FLAMMABLE AND EXPLOSIVE. WELDING ARC AND SPARKS CAN IGNITE COMBUSTIBLE MATERIALS.
======== Accidental Release Measures ==========
Spill Release Procedures:NOT RELEVANT Neutralizing Agent:NOT RELEVANT

Handling and Storage Precautions: KEEP AWAY FROM STRONG ACIDS.

Othe



r Precautions: NO FOOD OR SMOKING IN WORK AREAS. WASH THOROUGHLY

LINER IN AN ENVIRONMENTALLY ACCEPTABLE MANNER, IN FULL COMPLIANCE WITH FEDERAL, STATE AN D LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling

agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.