

EVERSEAL MFG CO INC -- C-16081 DARK GRAY GLOSS ALKYD ENAMEL -- 8010-00-616-7496
===== Product Identification =====

Product ID:C-16081 DARK GRAY GLOSS ALKYD ENAMEL

MSDS Date:09/03/1988

FSC:8010

NIIN:00-616-7496

MSDS Number: BKHQB

=== Responsible Party ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Info Phone Num:201-943-4986 / FAX 201-943-1123

Emergency Phone Num:201-943-4986

Preparer's Name:FRANK PRIMERANO

CAGE:72988

=== Contractor Identification ===

Company Name:EVERSEAL MFG CO INC

Address:475 BROAD AVE

Box:City:RIDGFIELD

State:NJ

ZIP:07657-2329

Country:US

Phone:201-943-4986

CAGE:72988

===== Composition/Information on Ingredients =====

Ingred Name:RESIN

Fraction by Wt: 35%

Other REC Limits:10 MG/CUM (DUST)

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 13%

OSHA PEL:15 MG/

M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:CARBON BLACK
CAS:1333-86-4
RTECS #:FF5800000
Fraction by Wt: 2%
Other REC Limits:3.5 MG/CUM (NIOSH)
OSHA PEL:3.5 MG/M3
ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:IRON OXIDE
CAS:1309-37-1
RTECS #:NO7400000
Fraction by Wt: 5%
OSHA PEL:10 MG/M3 (FE)
ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:ADDITIVES
Fraction by Wt: 2%

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPHTHANES
MINERAL SPIRITS
CAS:64742-88-7
Fraction by Wt: 43%
Oth
er REC Limits:100 PPM
OSHA PEL:500 PPM
ACGIH TLV:100 PPM

===== Hazards Identification =====

LD50 LC50 Mixture:ORAL LD50 (LAB ANIMAL): 5 G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: DIZZINESS, NAUSEA, &
UNCONSCIOUSNESS. SKIN/EYES: IRRITATION.
Explanation of Carcinogenicity:CARBON BLACK IS A SUSPECTED A2
CARCINOGEN BY ACGIH.
Effects of Overex

posure:INHALATION: DIZZINESS, NAUSEA, &
UNCONSCIOUSNESS. SKIN/EYES: IRRITATION.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION
IF NECESSARY. EYES: FLUSH W/WATER. SKIN: WASH W/SOAP & WATER.
OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point:105F

Lower Limits:1%

Extinguishing Media:FOAM, CO2, & DRY CHEMICAL. WATER ISN'T A
SUITABLE

EXTINGUISHING MEDIUM.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:COMBUSTIBLE LIQUID.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITION SOURCES. ENSURE ADEQUATE
VENTILATION. ABSORB SMALL SPILLS ON DRY ABSORPTION MATERIAL. USE
SPARK-PROOF SCOOP FOR LARGE SPILLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:

AVOID EXCESSIVE HEAT & OPEN IGNITION
SOURCES.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IF >TLV, USE CARTRIDGE MASK.

Ventilation:PROVIDE SUFFICIENT VENTILATION TO KEEP AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:DARK GRAY LIQUID.

Percent Volatiles by Volume:59%

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condi

tion to Avoid:EXCESSIVE HEAT & OPEN IGNITION SOURCES

Hazardous Decomposition Products:CO & CO2

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL & FEDERAL REGULATIONS FOR HAZARDOUS WASTE. COMBUSTIBLE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, express
ly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.