View NSN Online: https://aerobasegroup.com/nsn/9150-00-657-4959

VALVOLINE INC, SUBSIDIARY OF ASHLAND OIL -- AUTOMATIC TRANSMISSION FLUID DEXRON II -- 9150-00-657-4959

Product ID:AUTOMATIC TRANSMISSION FLUID DEXRON II MSDS Date:07/20/1989 FSC:9150 NIIN:00-657-4959 MSDS Number: BKHQH === Responsible Party === Company Name: VALVOLINE INC, SUBSIDIARY OF ASHLAND OIL Box:14000 City:LEXINGTON State:KY ZIP:40512 Info Phone Num:(606) 264-7000 Emergency Phone Num: (606) 264-7000 CAGE:LO750 === Contractor Identification === Company Name: VALVOLINE INC, SUBSIDIARY OF ASHLAND OIL Box:14000 City:LEXINGTON State:KY ZIP:40512 Phone:(606) 264-7000 CAGE:LO750 Company Name: VALVOLINE OIL CO Address:3499 BLAZER PKY Box:14000 City:LEXINGTON State:KY ZIP:40512 Country:US Phone:606-357-7206 / 800-274-5263 CAGE:72527

Ingred Name:ALIPHATIC HYDROCARBONS Fraction by Wt: 85-10 Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Explanation of Carcinogenicity:NONE

- First Aid:SKIN: THOROUGHLY WASH EXPOSED AREA W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER. INGESTION: DON'T INDUCE VOMITING. INHALATION: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHIN
- G IS DIFF ICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET & OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point:>390F

Extinguishing Media:REGULAR FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS W/FULL
FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE. WATER/FOAM
MAY CAUSE FROTHING WHICH CAN BE VIOLENT.
Unusual

Fire/Explosion Hazard:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

Spill Release Procedures: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT OR OTHER ABSORBENT MATERIAL. PREVENT RUN-OFF TO SEWERS, STREAMS ON OTHER BODIES OF WATER. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREA DING, PUMP LIQUID TO SALVAGE TANK.

=

- Handling and Storage Precautions:DON'T TRANSFER TO UNLABELED CONTAINER. DON'T USE CUTTING OR WELDING TORCH ON THIS CONTAINER (EVEN EMPTY). FOR INDUSTRIAL USE ONLY.
- Other Precautions: CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, &/OR SOLID). CONTAINS: PETROLEUM OIL.

======= Exposure Controls/Personal Protection ==========

0%

spiratory Protection:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE Ventilation:NOT REQUIRED UNDER NORMAL CONDITIONS OF USE Protective Gloves:NOT NORMALLY REQUIRED Eye Protection:NOT NORMALLY REQUIRED Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS. Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE. Supplemental Safety and Health

Boiling Pt:B.P. Text:>425F Vapor Density:>AIR Spec Gravity:0.875 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Appearance and Odor:LIQUID HOMOGENEOUS SOLUTION.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. DESTROY BY LIQUID INCINERATION.

Disclaimer (provided with this information by the com piling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.