View NSN Online: https://aerobasegroup.com/nsn/9150-00-843-1636

FORD MOTOR CO, PARTS & SERVICE DIV -- FNHI 2G134 TRACTOR HYDRAULIC OIL, 3-2 GAL CANS -- 9150-00-843-1636

Product ID:FNHI 2G134 TRACTOR HYDRAULIC OIL, 3-2 GAL CANS MSDS Date:04/06/1988 FSC:9150 NIIN:00-843-1636 MSDS Number: BKHRW === Responsible Party === Company Name: FORD MOTOR CO, PARTS & SERVICE DIV Address:3000 SCHAFER RD Box:1902 City:DEARBORN State:MI ZIP:4 8121 Info Phone Num: (313) 337-3182 OR (313) 323-0045 Emergency Phone Num: (313) 337-3182 OR (313) 323-0045 CAGE:FO849 === Contractor Identification === Company Name: FORD MOTOR CO, GOVERNMENT PART SALES Address:3000 SCHAEFER ROAD Box:1902 City:DEARBORN State:MI ZIP:48121 Country:US Phone:313-323-0045 CAGE:23040 Company Name: FORD MOTOR CO, PARTS & SERVICE DIV Address:3000 SCHAFER RD Box:1902 **City:DEARBORN** State:MI ZIP:48121 Phone: (313) 337-3182 OR (313) 323-0045 CAGE:FO849

====== Compositi

on/Information on Ingredients ========

Ingred Name:MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT-REFINED HEAVY PARAFFINIC, LUBRICATING OIL BASE STOCK CAS:64741-88-4 RTECS #:PY8040500 Fraction by Wt: >60% OSHA PEL:5 MG/CUM ACGIH TLV:5 MG/CUM

Ingred Name:PETROLEUM DISTILLATE - STREIGHT RUN MIDDLE CAS:64741-89-5 RTECS #:PY8041500 Fraction by Wt: 10-30% OSHA PEL:5 MG/CUM ACGIH TLV:5 MG/CUM

Ingred Name:MAGNESIUM SULFONATE CAS:61789-87-5 Fraction by Wt: 1-5%

Ingred Name:MINERAL OIL (EXPOSU RE REGULATED AS 'OIL MIST') CAS:8012-95-1 RTECS #:PY8030000 Fraction by Wt: 1-5% Other REC Limits:10 MG/CUM STEL OSHA PEL:5 MG/M3 ACGIH TLV:5 MG/M3/10 STEL;9192

LD50 LC50 Mixture:ORAL LD50 (RAT): 22 GM/KG Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN/EYE/INGESTION: IRRITATION. Explanation of Carcinogenicity:NONE Effects of Over exposure:SKIN/EYE/INGESTION: IRRITATION.

First Aid:EYES: FLUSH W/PLENTY OF WATER. SKIN: WASH THOROUGHLY W/WATER. INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:COC
Flash Point:>390.2F
Extinguishing Media:USE EXTINGUISHING MEDIA FOR CLASS B HAZARDS.

Spill Release

Procedures: TREAT AS OIL SPILL.

Handling and Storage Precautions: USE W/ADEQUATE VENTILATION. Other Precautions: AVOID CONTACT W/EYES & SKIN.

======= Exposure Controls/Personal Protection ==========

Ventilation:PROVIDE ADEQUATE VENTILATION. Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING. Supplemental Safety and Health

Spec Gravity:0.890 Appearance and Odor:LIQUID

Stability Indicator/Materials to Avoid:YES

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Departmen t

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.