

3M MINNESOTA MINING & MFG/INDUSTRIAL TAPE DIV -- SCOTCH-GRIP BRAND 1300-L RUBBER & GASKET ADHESIVE -- 8040-00-832-6173

===== Product Identification =====

Product ID:SCOTCH-GRIP BRAND 1300-L RUBBER & GASKET ADHESIVE

MSDS Date:11/11/1994

FSC:8040

NIIN:00-832-6173

MSDS Number: BKHSQ

=== Responsible Party ===

Company Name:3M MINNESOTA MINING & MFG/INDUSTRIAL TAPE DIV

Address:3M CENTER

City:ST PAUL

St

ate:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:52152

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING & MFG CO INDUSTRIAL TAPE & SPECIALTIES
DIV

Address:3M CENTER

Box:City:ST PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:1-800-364-3577

CAGE

:52152

=====
Composition/Information on Ingredients
=====

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES
MINERAL SPIRITS

CAS:64742-88-7

Fraction by Wt: 25-35%

Other REC Limits:100 PPM

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:2-BUTANONE (METHYL ETHYL KETONE) (MEK)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 20-30%

Other REC Limits:590 MG/CUM

OSHA PEL:200 PPM

ACGIH TLV:590 MG/CUM

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NEOPRE

NE, 2 CHLORO-1, 3-BUTADIENE HOMOPOLYMER, CHLOROPRENE

POLYMER

CAS:9010-98-4

RTECS #:EI9640000

Fraction by Wt: 10-20%

Ingred Name:MAGNESIUM RESINATE *94-4*

CAS:68611-24-5

Fraction by Wt: 10-20%

Ingred Name:HEXANE, N-HEXANE

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: 7-13%

Other REC Limits:50 PPM

OSHA PEL:1800 MG/CUM

ACGIH TLV:176 MG/CUM

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (IARC - GROUP 3) *94-4*

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 7-13%

Other REC Limi

ts:375 MG/CUM
OSHA PEL:100 PPM
ACGIH TLV:100 PPM
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:VOLATILE ORGANIC COMPOUNDS: 630 G/L
RTECS #:9999999VO

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:EYES: MODERATE IRRITATION. SKIN: MILD IRRITATION. MAY BE ABSORBED. INHALATION: CNS DEPRESSION, UPPER RESPIRATORY IRRITATION, PERIPHERAL NEUROPATHY. INGESTION: GI IRRITATION, CNS DEPRESSION, ASPIRATION PNEUMONITIS. OVEREXPOSURE TO TOLUENE DURING PREGNANCY MAY CAUSE BIRTH DEFECTS. (SEE SUPP)
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION/REDNESS/SWELLING/PAIN/TEARING/HAZY VISION/ITCHING/HEADACHE/DIZZINESS/DROWSINESS/INCOORDINATION/SLOWED REACTION TIME/SLURRED SPEECH/GIDDINESS/UNCONSCIOUSNESS/SORENESS OF NOSE & THROAT/COUGHING/SNEEZING/TINGLING OF EXTREMITIES/NUMBNESS/WEAKNESS/TREMORS/VOMITING/NAUSEA/ABDOMINAL TENDERNESS (SEE SUPP)

=====
First Aid Measures
=====

First Aid:EYES/SKIN: IMMEDIATELY FLUSH W/LARGE AMOUNTS OF WATER.
INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING GIVE CPR.
INGESTION: ONLY INDUCE VOMITING AT INSTRUCTION OF A PHYSICIAN.
ASPIRATION HAZARD. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC
Flash Point:-14F (SEE SUPP)
Lower Limits:1
Upper Limits:11.5
Extinguishing Media:CO2, FOAM, & DRY CHEMICAL
Fire Fighting Procedures:WEAR SELF-CONTAINED/POSITIVE PRESSURE/PRESSURE DEMAND BREATHING APPARATUS & FULL PROTECTIVE CLOTHING.
Unusual Fire/Explosion Hazard:CLOSED CONTAINER EXPOSED TO HEAT FROM FIRE MAY BUILD PRESSURE & EXPLODE. VAPORS MAY TRAVEL ALONG GROUND/FLOOR TO DISTANT IGNITION SOURCE & FLASH BACK.

=====

= Accidental Release Measures =====

Spill Release Procedures: VENTILATE AREA. EXTINGUISH ALL IGNITION SOURCES. COVER W/ ABSORBENT MATERIAL. COLLECT USING NON-SPARKING TOOLS. PLACE IN A U.S. DOT APPROVED CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions: KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME, OTHER IGNITION SOURCES. USE IN WELL VENTILATED AREA.

Other Precau

tions: KEEP OUT OF REACH OF CHILDREN. FLAMMABLE LIQUID & VAPOR. GROUND CONTAINERS SECURELY WHEN TRANSFERRING CONTENTS. WEAR LOW STATUS/ PROPERLY GROUNDED SHOES. AVOID PROLONGED BREATHING OF VAPORS. AVOID SKIN / EYE CONTACT. DON'T TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: WEAR NIOSH APPROVED HALF MASK/ ORGANIC VAPOR RESPIRATOR BASED ON AIRBORNE CONCENTRATION OF CONTAMINANTS.

Ventilation: SUFFICIENT TO MAINTAIN EMISSION

S