

EXXON COMPANY, U.S.A. -- 376018-01186 TERESSTIC EP 32 -- 9150-00-935-9808

=====
Product Identification
=====

Product ID:376018-01186 TERESSTIC EP 32

MSDS Date:06/01/1989

FSC:9150

NIIN:00-935-9808

MSDS Number: BKHSY

=== Responsible Party ===

Company Name:EXXON COMPANY, U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Info Phone Num:(713) 656-2443

Emergency Phone Num:(713) 656-2443

CAGE:DO850

=

== Contractor Identification ==

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY, USA, A DIV OF EXXON CORP.

Address:800 BELL ST

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 FAX: 713-656-3631

CAGE:DO850

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENT REFINED HYDROTREATED HEAVY PARAFFINIC DISTILLATE,
HYDROT

REATED HEAVY PARAFFINIC DISTILLATE, LUBRICATING OIL.

CAS:64742-54-7

RTECS #:PY8035500

Fraction by Wt: >99%

OSHA PEL:5 MG/CUM (MIST)

Ingred Name:PROPRIETARY ADDITIVES

Fraction by Wt: 5 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:SKIN: PROLONGED/REPEATED CONTACT CAUSE IRRITATION, DERMATITIS. EYES: IRRITATION. INGESTION: AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION OR VOMITING MAY CAUSE UASE

MILD TO SEVERE PULMONARY INJURY & POSSIBLY DEATH.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:SKIN: PROLONGED/REPEATED CONTACT CAUSE IRRITATION, DERMATITIS. EYES: IRRITATION. INGESTION: AMOUNTS ASPIRATED INTO THE LUNGS DURING INGESTION OR VOMITING MAY CAUSE MILD TO SEVERE PULMONARY INJURY & POSSIBLY DEATH.

Medical Cond Aggravated by Exposure:DERMATITIS

=====
===== First Aid Measures =====

First Aid:INHALATION: IF OVERCOME BY VAPOR FROM HOT PRODUCT, REMOVE FROM EXPOSURE. IF BREATHING IS IRREGULAR OR HAS STOPPED, START RESUSCITATION; ADMINISTER OXYGEN. EYES: FLUSH W/WATER FOR 15 MINUTES. INGESTION : DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:399F

Lower Limits:0.9%

Upper Limits:7%

Extinguishing Media:FOAM, WATER SPRAY FOG, DRY CHEMICAL, CO2

Fire Fighting Procedures:USE WATER TO K

KEEP FIRE-EXPOSED CONTAINERS

COOL. WATER SPRAY MAY BE USED TO FLUSH SPILLS AWAY FROM EXPOSURES.

Unusual Fire/Explosion Hazard:IF A LEAK OR SPILL HASN'T IGNITED, USE

WATER SPRAY TO DISPERSE THE VAPOR/TO PROVIDE PROTECTION FOR MEN ATTEMPTING TO STOP A LEAK. AUTOIGNITION TEMPS: >500F.

=====
===== Accidental Release Measures =====

Spill Release Procedures:RECOVER FREE PRODUCT. ADD SAND/EARTH OR OTHER SUITABLE ABSORBENT TO SPILL AREA. OPEN ALL WINDOWS/DOORS. KEEP

