

BAKER SEALANTS & COATINGS COMPANY -- CORROSION PREVENT COMPOUND --
8030-00-938-1947

=====
Product Identification
=====

Product ID:CORROSION PREVENT COMPOUND

MSDS Date:11/16/1989

FSC:8030

NIIN:00-938-1947

MSDS Number: BKHSZ

=== Responsible Party ===

Company Name:BAKER SEALANTS & COATINGS COMPANY

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07804

Info Phone Num:(201) 333-6955

Emerg

ency Phone Num:(201) 333-6955

CAGE:FO833

=== Contractor Identification ===

Company Name:BAKER SEALANTS & COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City:JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name:BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

=====
Composition/Information on Ingredients
=====

Ingred Name:MEDIUM ALIPHATIC NAPHTHA (AROMATIC

100), PARAFFIN-NAPHTHANES

MINERAL SPIRITS

CAS:64742-88-7

Fraction by Wt: 12.5%

Other REC Limits:100 PPM

OSHA PEL:500 PPM

ACGIH TLV:100 PPM

Ingred Name:DICHLOROTETRAFLUOROETHANE (SARA III)

CAS:76-14-2

RTECS #:K11101000

Fraction by Wt: 75%

Other REC Limits:1000 PPM

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ozone Depleting Chemical:1

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO

IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: LIGHT HEADEDNESS,
GIDDINESS, SHORTNESS OF BREATH, POSSIBLE NARCOSIS, CARDIAC
ARRHYTHMIA AT HIGH CONCENTRATIONS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION: LIGHT HEADEDNESS, GIDDINESS,
SHORTNESS OF BREATH, POSSIBLE NARCOSIS, CARDIAC ARRHYTHMIA AT HIGH
CONCENTRATIONS.

=====
===== First Aid Measures =====

First Aid:EYES/SKIN: FLUSH W/WATER. INHALATION: REMOVE
TO FRESH AIR.

DON'T GIVE APINEPHRINE OR SIMILAR DRUGS. OBTAIN MEDICAL ATTENTION
IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:263F,128C

Extinguishing Media:MECHANICAL FOAM, DRY CHEMICAL, WATER FOG, CO2

Unusual Fire/Explosion Hazard:VAPOR ACCUMULATION WOULD FLASH/EXPLODE IF
IGNITED.

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA-ESPECIALLY LOW PLACE

S WHERE

HEAVY VAPORS MIGHT COLLECT, REMOVE OPEN FLAME.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE CONTAINERS IN A CLEAN, DRY AREA,
DON'T HEAT >125F.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE AIR MASK IN HIGH CONCENTRATIONS
Ventilation:LOCAL EXHAUST: WHEN LARGE AMOUNT ARE RELEASE ESPECIALLY IN
LOW PLACES
Protective Gloves:WHEN HANDLING LIQUID
Eye Protection:WHEN HAN
DLING LIQUID
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

Boiling Pt:B.P. Text:117-390F
Vapor Pres:334
Vapor Density:6.5
Spec Gravity:1.25-1.30
Evaporation Rate & Reference:0.3
Solubility in Water:NEGLIGIBLE
Appearance and Odor:DARK AMBER ORGANIC ODOR.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
ALKALI OR ALKALINE EARTH METALS-POWERED
Stability Condition to Avoid:OPEN
FLAME OR HIGH TEMPERATURE. DON'T HEAT
>125F.
Hazardous Decomposition Products:HYDROCHLORIC/HYDROFLUORIC ACIDS

=====
Disposal Considerations
=====

Waste Disposal Methods:RECLAIM BY DISTILLATION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be a

ccurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.