View NSN Online: https://aerobasegroup.com/nsn/8030-01-034-0394

Product ID:WAKEFIELD W-120-5 THERMAL JOINT COMPOUND, 5 OZ TUBE MSDS Date:11/01/1988 FSC:8030 NIIN:01-034-0394 MSDS Number: BKHVD === Responsible Party === Company Name: EG & G WAKEFIELD ENGINEERING Address:60 AUDUBON ROAD City:WAKEFIELD State:MA ZIP:01880 Info Phone Num:(617) 245-5900 Emergency Phone Num:(617) 245-5900 Preparer's Name: DAVID F. HEGARTY CAGE:05820 === Contractor Identification === Company Name: EG & G WAKEFIELD ENGINEERING Address:80 AUDUBON RD Box:City:WAKEFIELD State:MA ZIP:01880 Country:US Phone:617 245 5900 CAGE:05820 Ingred Name:ZINC OXIDE

CAS:1314-13-2 RTECS #:ZH4810000 Fraction by Wt: 60-80% OSHA PEL:15MG/M3 TDUST/5 FUME ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Na

me:DIMETHYL POLYSILOXANE (MONOMER: DIMETHYL SILOXANE), SILICONE FLUID, DOW CORNING 200, POLYMETHYLSILOXANE CAS:63148-62-9 RTECS #:JT6484500 Fraction by Wt: 20-40%

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:EYE/INHALATION: IRRITATION. INGESTION: HARMFUL. SKIN: IRRITATION & ABSORPTION. Explanation of Carcinogenicity:NONE Effects of Overexposure:EYE/INHALATION: IRRITATION. INGESTION: HARMFUL. SKIN: IRRITATION & ABSORPTION.

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. INGESTION: DILUTE W/WATER. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point:>250

F

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, & WATER FOG. Fire Fighting Procedures:FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS.

Spill Release Procedures:SMALL SPILL: WIPE UP OR ABSORB W/VERMICULITE OR OTHER ABSORBENT MATERIAL. SCRUB AREA W/SOAPY WATER & RINSE. LARGE SPILL: SCRAPE OR SHOVEL ABSORBED WASTE & ABSORBENT INTO CONTAINERS. SCRUB AREA W/SOAPY WATER & RINSE.

Handling and Storage Precautions:STORE IN A COOL, DRY PLACE. KEEP AWAY FROM HEAT & OPEN FLAME. SHELF LIFE IS 5 YEARS. NOT RECOMMENDED FOR VACUUM APPLICATION.

Other Precautions: PREVENT CONTACT W/SKIN/EYES/CLOTHING. DON'T INGEST. EXPOSURE TO FILLER MATERIAL IS UNLIKELY UNLESS APPLIED IN A MANNER WHICH RESULTS IN GENERATING MISTS/FUMES/MACHINING, CURED PRODUCT RESULTS IN GENER ATING DUST PARTICLES.

======= Exposure Controls/P

ersonal Protection =========

Protective Gloves:PROTECTIVE Eye Protection:GOGGLES Other Protective Equipment:PROTECTIVE CLOTHING Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Supplemental Safety and Health ALL COMPONENTS OF THIS PRODUCT ARE LISTED ON THE EPA TOXIC SUBSTANCE ACT INVENTORY.

Vapor Pres:AIR Spec Gravity:2.20 Solubility in Water:NEGLIGIBLE Appearance and Odor:OPAQUE WHITE PASTE Percent Volatiles by Volume:NEGL

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:HEAT, OPEN FLAME, & UNCONTROLLED MIXING. Hazardous Decomposition Products:CO, CO2, SILICON DIOXIDE, & ZINC OXIDE.

Waste Disposal Methods:SPILLED MATERIAL & WATER RINSES ARE CLASSIFIED AS CHEMICAL WASTE, & MUST BE DISPOSED OF IN ACCORDANCE W/LOCAL, STATE, & FEDERAL REGULATIONS. PREVENT RINSES FROM ENTERING DRAINS OR OTHER WATERWAYS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent profes sional advice to verify and assume responsibility for the suitability of this information to their particular situation.