

ESGARD INC. -- PL-2 -- 8030-00-244-1295

===== Product Identification =====

Product ID:PL-2  
MSDS Date:08/09/1990  
FSC:8030  
NIIN:00-244-1295  
MSDS Number: BKJHJ  
=== Responsible Party ===  
Company Name:ESGARD INC.  
Box:2698  
City:LAFAYETTE  
State:LA  
ZIP:70502  
Country:US  
Info Phone Num:318-234-7436  
Emergency Phone Num:318-234-6327  
Preparer's Name:EMILIO BELTRAN  
CAGE:KO815  
=== Contractor Identification ===  
Company Name:ESGARD INC.  
Box:2698  
City:LAFAYETTE  
State:LA  
ZIP:70502  
Country:US  
Phone:318-234-7436  
CAGE:KO815

===== Composition/Information on Ingredients =====

Ingred Name:OIL AS A MIST  
Other REC Limits:NONE SPECIFIED  
ACGIH TLV:5 MG/M3

Ingred Name:VOC: < 10 G/L (0.1 LBS/GL)  
RTECS #:9999999VO  
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chron

ic:EXPOSURE TO VAPORS OR MISTS MAY CAUSE PULMONARY IRRITATION, DIZZINESS AND NAUSEA. PROLONGED OR REPEATED CONTACT MAY CAUSE VARIOUS SKIN DISORDERS SUCH AS DERMATITIS, FOLLICULITIS OR OIL ACNE.

=====  
First Aid Measures  
=====

First Aid:INHALATION: REMOVE VICTIM TO UNCONTAMINATED AREA. IF BREATHING IS IRREGULAR OR STOPPED, PROVIDE OXYGEN OR RESUSCITATION. SEEK MEDICAL AID. SKIN: FLUSH SKIN THOROUGHLY WITH WATER. REMOVE CONTAMINATED CLOTHING. EYE: FLUSH EYES THOROUGHLY FOR 15 MINUTES WITH WATER. SEEK MEDICAL AID. INGEST: DO NOT INDUCE VOMITING. SEEK IMMEDIATE MEDICAL AID.

=====  
Fire Fighting Measures  
=====

Flash Point Method:COC  
Flash Point:355F,179C  
Extinguishing Media:FOAM, CO2, DRY CHEMICAL.  
Fire Fighting Procedures:PREHEATED MAT'L MAY BURN. DO NOT ENTER CONFINED AREA W/OUT FULL BUNKER GEAR, AND POSITIVE PRESSURE NIOSH APPR'D SCBA. COOL FIRE EXPOSED CONTAINERS WITH WATER.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:CONTAIN THE SOURCE OF THE LEAK IF POSSIBLE. DIKE AND CONTAIN THE SPILL USING VACUUM OR PUMPS TO REMOVE THE MATERIAL. SOAK UP ANY EXCESS WITH OIL ABSORBENT MATERIAL. DISPOSE OF PROPERLY.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE NEAR HEAT, SPARKS OR OPEN FLAMES.  
Other Precautions:EMPTY CONTAINERS MAY RETAIN HAZARDOUS PROPERTIES. DO NOT CUT, WELD OR PUNCTURE ON OR NEAR CONTAINERS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:RECOMMENDED  
Ventilation:RECOMMENDED  
Protective Gloves:RUBBER/OIL RESISTANT  
Eye Protection:CHEMICAL SPLASH GOGGLES  
Work Hygienic Practices:MINIMIZE SKIN CONTACT.  
Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

HCC:T6  
Vapor Density:> AIR  
Viscosity:1750 CP  
Evaporation Rate & Refe

rence:SLOWER THAN ETHER  
Percent Volatiles by Volume:1/2

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Stability Condition to Avoid:HEAT, OPEN FLAMES, OXIDIZING MATERIALS

Hazardous Decomposition Products:CARBON MONOXIDE AND UNIDENTIFIED  
ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

Conditions to Avoid Polymerization:HEAT, OPEN FLAMES, OXIDIZING  
MATERIALS.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF MATERIAL IN ACCORDANCE WITH FEDERAL,  
STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek  
competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.