

PRATT AND LAMBERT INC -- LACQUER ACRYLIC N/C GLOSS CLEAR -- 8010-00-527-1508

=====
Product Identification
=====

Product ID:LACQUER ACRYLIC N/C GLOSS CLEAR

MSDS Date:03/15/1991

FSC:8010

NIIN:00-527-1508

MSDS Number: BKJKP

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Pho

ne Num:716-873-6000 DOT EMER 8002553924

Preparer's Name:W. A. ELLISON

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 35%

Other REC Limits:NONE SPECIFIED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT

Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:NITROCELLULOSE (RESIN)

CAS:9004-70-0

RTECS #:WG2934500

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA III)

CAS:117-81-7

RTECS #:TI0350000

Fraction by Wt: 5%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3/10 ST

EL

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:100 LBS

DOT Rpt Qty:100 LBS

Ingred Name:CYCLOHEXANONE (SARA III)

CAS:108-94-1

RTECS #:GW1050000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:S, 50 PPM

ACGIH TLV:S, 25 PPM; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:VM&P NAPHTHA (SOLVENT) (LFL: .9 UFL: 6.7)

CAS:8030-30-6

RTECS #:DE3030000

Fraction by Wt: 10%

Other REC Limits:NONE SPECIFIED

OSHA PEL:300 PPM/400 PPM STEL

ACGIH TLV:300 PPM / 1350 MG/M3

Ingred Name:VOC: 5.36 LB/GL LESS WATER & NPRS*; 643 G/L LESS WATER;
CALCULATED (*NEGLIGIBLY PHOTOCHEMICALY REACTIVE MATERIALS)

RTECS #:9999999VO

Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 22.77 LB/GAL SOLIDS; 2732 G/L SOLIDS; CALCULATED

RTECS #:9999999VO

Other REC Li

imits:NONE SPECIFIED

=====
===== Hazards Identification =====

Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:YES

Health Hazards Acute and Chronic:INGEST/INHALE/EYE/SKIN: IRRITATION

(GASTROINTESTINAL, NOSE, THROAT, EYE, SKIN). LUNG ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. CENTRAL NERVOUS SYSTEM DEPRESSION. CORNEAL DAMAGE. SKIN ABSORPTION. OVEREXPOSURE: PERIPHERAL NEUROPATHY, PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE.

Explana

tion of Carcinogenicity:DI(2-ETHYLHEXYL)PHTHALATE IS LISTED AS A POTENTIAL CARCINOGEN BY THE NTP.

Effects of Overexposure:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES, DIZZINESS, NAUSEA, CONFUSION.

Medical Cond Aggravated by Exposure:LAB STUDIES INVOLVING RATS INDICATE SOME EVIDENCE THAT METHYL ETHYL KETONE MAY BE EMBRYOTOXIC, FETOTOXIC AND TERATOGENIC.

=====
===== First Aid Measures =====

First Aid:INGEST: DO NOT INDUCE VOMITING. CALL POISON CONTR

OL,
EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM & QUIET. GET IMMEDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE AMOUNT OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED CLOTHES. WASH AFFECTED AREA WITH SOAP & WATER. PERSISTANT IRRIT SEE A DOCTOR

=====
Fire Fighting Measures
=====

Flash Point:24.0F,-4.4C
Autoignition Temp:Autoignition Temp Text:572F
Lower Limits:0.9
Upper Limits:13.0
Extinguishing Media:USE NFPA CLASS B(CO2, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE, USE TO COOL CONTAINERS (FOG NOZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP & AUTO-IGNITION OR EXPLOSION WHEN EXPOSED TO EXTREME HEAT
Unusual Fire/Explosion Hazard:DURING EMERGENCY CONDITIONS, OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY CAUSE A HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMEDIATELY APPARENT. GET MEDICAL ATTENTION.

=====
Accidental Release Measures
=====

Spill Release Procedures:KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE SOURCES. DIKE, CONTAIN & REMOVE WITH INERT MATERIAL (SAND, EARTH, ETC). USE COVERED METAL CONTAINERS FOR RECOVERY AND DISPOSAL. USE NON-SPARKING TOOLS. PREVENT CONTAMINATION OF SEWERS, STREAMS & GROUNDWATER.

=====
Handling and Storage
e =====

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. LARGE QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. KEEP FROM CHILDREN. DO NOT REUSE CONTAINERS.
Other Precautions:CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL. KEEP CONTAINERS CLOSED WHEN NOT IN USE.

=====
Exposure Controls/Pe

Personal Protection =====

Respiratory Protection:RESTRICTED AREA: NIOSH APPR'D CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING: MECHANICAL PREFILTER MAY BE REQUIRED.
CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR.
EXCEEDED TLV AREA: NIOSH/MSHA APPROVED RESPIRATOR W/RIGHT FACTOR.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW EXPOSURE LIMITS.

Protective Gloves:REPEAT/PROLONG: IMPERMEABLE GLOVES.

Eye

Protection:SAFETY GLASSES W/SIDESHIELD, FACESHIELD.

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 314F

Melt/Freeze Pt:M.P/F.P Text:-50F,-46C

Decomp Temp:Decomp Text:1832F,1000C

Vapor Pres:70 @ 68F

Vapor Density:> AIR

Spec Gravity:0.9

pH:4-7

Viscosity:> 200 CST

Evaporation Rate & Reference:SLOWER THAN DIETHYL ETHER

Solubility in Water:SLIGHT

Appearance

and Odor:LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:76

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESS HEAT (>100F) & IGNITION SOURCES.

Hazardous Decomposition Products:BURNING, (INCLUDE HEAT BY WELDING/CUTTING) PRODUCES SMOKE, CARBON MONOXIDE & CARBON DIOXIDE, POSSIBLE NITROGEN OXIDE.

===== Disposal Considerations ===

=====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS & LAWS. INCINERATE IN EPA FACILITY. DO NOT INCINERATE CLOSED CONTAINERS USE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MATERIAL-D001. USE HAZ ARDOUS WASTE LANDFILL FOR USED ABSORBENTS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.