

METECH, INCORPORATED -- 6090B -- 8040-00-728-2887

=====  
Product Identification  
=====

Product ID:6090B  
MSDS Date:01/01/1991  
FSC:8040  
NIIN:00-728-2887  
Kit Part:Y  
MSDS Number: BKJNQ  
=== Responsible Party ===  
Company Name:METECH, INCORPORATED  
Address:ROUTE 401  
City:ELVERSON  
State:PA  
Country:US  
Info Phone Num:215-286-0420  
Emergency Phone Num:215-286-0420  
CAGE:1Y738  
=== Contractor Identification ===  
Co  
Company Name:METECH, INCORPORATED  
Address:ROUTE 401  
Box:City:ELVERSON  
State:PA  
Country:US  
Phone:215-286-0420  
CAGE:1Y738

=====  
Composition/Information on Ingredients  
=====

Ingred Name:DIETHYLENE TRIAMINE  
CAS:111-40-0  
RTECS #:IE1225000  
Fraction by Wt: 10-20%  
Other REC Limits:NONE SPECIFIED  
OSHA PEL:1 PPM  
ACGIH TLV:S, 1 PPM; 9192

Ingred Name:TETA  
CAS:112-24-3  
RTECS #:YE6650000  
Fraction by Wt: 5-10%  
Other REC Limits:NONE SPECIFIED

Ingred Name:4,4'-ISOPROPYLIDENEDIPHENOL (SARA II

l)  
CAS:80-05-7  
RTECS #:SL6300000  
Fraction by Wt: 10-20%  
Other REC Limits:NONE SPECIFIED

Ingred Name:FATTY POLYAMIDE  
Fraction by Wt: 55-65%  
Other REC Limits:NONE SPECIFIED

=====  
Hazards Identification  
=====

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:EYES: MAY CAUSE BURNS. SKIN: MAY CAUSE  
SENSITIZATION AND OTHER ALLERGIC RESPONSES.  
Effects of Overexposure:SKIN RASH OR IRRITATION, DERMATITIS.  
Medical Cond Aggravated  
by Exposure:ALLERGIC REACTIONS, RESPIRATORY  
CONDITIONS.

=====  
First Aid Measures  
=====

First Aid:EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH WITH SOAP  
AND WATER. INGESTION: DO NOT INDUCE VOMITING, CALL A PHYSICIAN.  
INHALATION: REMOVE TO FRESH AIR.

=====  
Fire Fighting Measures  
=====

Flash Point Method:SCC  
Flash Point:>200F,>93C  
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM OR WATER.  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND  
COMPLETE PROTECTIVE EQUIPMENT. COOL FIRE EXPOSED CONTAINERS WITH  
WATER. MAY FORM NITROGEN OXIDES ON COMBUSTION.  
Unusual Fire/Explosion Hazard:HEAT MAY VOLATILIZE OR RELEASE FREE  
POLYAMINES WHICH MAY PRODUCE SKIN &/OR RESPIRATORY  
IRRITATION/SENSITIZATION. CLOSED CONTAINER MAY RUPTURE WITH EXTREME  
HEAT.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:CONTAIN SPILL. COMPLETELY

Y ABSORB WITH INERT  
MATERIAL, SWEEP OR SCOOP INTO DISPOSAL CONTAINER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 80F.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE ADEQUATE VENTILATION. NIOSH APPROVED  
RESPIRATOR.

Ventilation:LOCAL EXHAUST.

Protective Gloves:USE PROTECTIVE GLOVES.

Eye Protection:SPLASH PROOF GOGGLES.

Work Hygienic Practices:AVOID CONTACT WITH S

KIN, WASH BEFORE EATING OR

SMOKING. LAUNDRER CONTAMINATED CLOTHING.

Supplemental Safety and Health

=====  
Physical/Chemical Properties  
=====

Solubility in Water:PARTIALLY

Appearance and Odor:GREENISH BROWN LIQUID WITH AMINE ODOR

=====  
Stability and Reactivity Data  
=====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS, ACIDS OR BASES.

Stability Condition to Avoid:HIGH HEAT

Hazardous Decomposition Products:CARBON MONOXIDE, CAR  
BON DIOXIDE,  
ALDEHYDES.

Conditions to Avoid Polymerization:STRONG OXIDIZERS, ACIDS, BASES.

=====  
Disposal Considerations  
=====

Waste Disposal Methods:IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this inf

ormation to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.