

TEXWIPE CO -- MICRODUSTER OS,ACCUDUSTER II OS,ACCUDUSTER -- 6830-01-334-7026

===== Product Identification =====

Product ID:MICRODUSTER OS,ACCUDUSTER II OS,ACCUDUSTER

MSDS Date:11/01/1992

FSC:6830

NIIN:01-334-7026

MSDS Number: BKJXK

=== Responsible Party ===

Company Name:TEXWIPE CO

Address:650 E CRESENT AVE

Box:575

City:UPPER SADDLE RIVER

State:NJ

ZIP:07458-1827

Country:US

Info Phone Num:201-327-9

100

Emergency Phone Num:201-327-9100

CAGE:21994

=== Contractor Identification ===

Company Name:TEXWIPE CO

Address:650 E CRESENT AVE

Box:308

City:UPPER SADDLE RIVER

State:NJ

ZIP:07458-1827

Country:US

Phone:201-327-5577

CAGE:21994

===== Composition/Information on Ingredients =====

Ingred Name:CHLORODIFLUOROMETHANE

CAS:75-45-6

RTECS #:PA6390000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000PPM; 9192

Ozone Depleting Chemical:2

=====

===== Hazards Identification =====

LD50 LC50 Mixture:TLV IS 1000 PPM.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: VAPOR IS HEAVIER THAN AIR AND CAN CAUSE SUFFOCATION BY REDUCING OXYGEN AVAILABLE FOR BREATHING. BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND MAY LEAD TO NARCOSIS, CARDIAC IRREGULAR

ITIES, UNCONSCIOUSNESS OR DEATH.

SKIN/EYE: IRRITATION AND FROSTBITE.

Explanation of Carcinogenicity:CHLORODIFLUOROMETHANE (FREON 22) IS NOT LISTED AS A CARCINOGEN BY IARC, NTP OR OSHA.

Effects of Overexposure:BREATHING HIGH CONCENTRATIONS OF VAPOR MAY CAUSE LIGHT-HEADEDNESS, GIDDINESS, SHORTNESS OF BREATH, AND MAY LEAD TO NARCOSIS, CARDIAC IRREGULARITIES, UNCONSCIOUSNESS OR DEATH. LIQUID IS IRRITATING TO SKIN AND EYES, AND MAY CAUSE FROSTBITE.

Medical Cond Aggravated by Expo

sure:PERSONS WITH KNOWN HISTORY OF HEART

DISEASE OR IRREGULARITIES OF HEARTBEAT SHOULD BE PARTICULARLY CAREFUL TO AVOID OVEREXPOSURE TO THESE VAPORS.

===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS DIFFICULT, GIVE OXYGEN. DO NOT GIVE EPINEPHRINE OR SIMILAR DRUGS. EYE: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. GET MEDICAL ATTENTION.

SKIN:

WASH WITH SOAP AND WATER. IF FROSTBITE, WARM SKIN SLOWLY. GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:NONE

Extinguishing Media:WATER SPRAY, CO2, FOAM/DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.

Fire Fighting Procedures:WEAR PROTECTIVE CLOTHING AND NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:OTHER BURNING MATERIALS CAN CA

USE
COMPOUND TO BURN.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENTS. VENTIALTE AREA,
ESPECIALLY LOW PLACES WHERE HEAVY VAPORS MIGHT COLLECT. REMOVE
GLOWING METAL SURFACES.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN A CLEAN, COOL, DRY AND
WELL-VENTILATED AREA OF LOW FIRE RISK. PROTECT CONTAINERS FROM
PHYSICAL DAMAGE AND KEEP TIGHTLY C
LOSED.

Other Precautions:AVOID BREATHING VAPOR, LIQUID CONTACT WITH EYES, SKIN
OR CLOTHING. DO NOT DROP, REUSE, OR REFILL CONTAINER. DO NOT STORE
NEAR HEAT OR IN DIRECT SUN. KEEP CONTAINERS BELOW 120 F. READ LABEL
BEFORE USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED FOR ADEQUATELY VENTED WORK
SITUATIONS. FOR ACCIDENTAL OR NON-VENTILATED SITUATIONS, USE A
SELF-CONTAINED BREATHING APPARATUS OR SUPPLIED-AIR RESPIR
ATOR,
APPROVED BY NIOSH.

Ventilation:PROVIDE LOCAL AND MECHANICAL EXHAUST WHEN USED.

Protective Gloves:SYNTHETIC INSULATED RUBBER GLOVE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other Protective Equipment:USE IMPERVIOUS CLOTHING TO PROTECT EXPOSED
SKIN FROM LIQUID CONTACT.

Work Hygienic Practices:DO NOT SMOKE IN AREA WHILE PRODUCT IS IN USE.

Supplemental Safety and Health

AVOID BREATHING OF VAPORS AND CONTACT WITH EYES/SKIN.

===== Physical/Chemical Properties =====
===

HCC:G3

Boiling Pt:B.P. Text:-41F,-41C

Melt/Freeze Pt:M.P/F.P Text:NOT KNOWN

Decomp Temp:Decomp Text:NOT KNOWN

Vapor Pres:7807 @ 77F

Vapor Density:3.03 @ 77F

Spec Gravity:1.194

Evaporation Rate & Reference:GAS

Solubility in Water:0.30% @ 77F (25C)

Appearance and Odor:CLEAR, LIQUEFIED GAS, SLIGHT ETHEREAL ODOR

Percent Volatiles by Volume:100

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
ALKALI OR ALKALINE EARTH METALS, POW

DERED ALUMINUM, ZINC, BERRYLIUM.

Stability Condition to Avoid:EXCESSIVE HEAT, OPEN FLAMES, GLOWING METAL SURFACES

Hazardous Decomposition Products:HYDROCHLORIC ACID, HYDROFLUORIC ACID AND POSSIBLY CARBONYL HALIDES

===== Disposal Considerations =====

Waste Disposal Methods:BEST TO RECYCLE OR RECLAIM, IF POSSIBLE. WASTE MATERIAL MAY BE A LAND-BANNED HAZARDOUS WASTE. CONSULT FEDERAL, STATE, OR LOCAL AUTHORITIES FOR PROPER DISPOSAL PROCEDURES.

Disc

laimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.