View NSN Online: https://aerobasegroup.com/nsn/8010-00-285-4870

PRATT & LAMBERT INC., INDUSTRIAL COATINGS DIV. -- ENAMEL, DECK INTERIOR GRAY ID 707750 -- 8010-00-285-4870

Product ID: ENAMEL, DECK INTERIOR GRAY ID 707750 MSDS Date:04/18/1991 FSC:8010 NIIN:00-285-4870 MSDS Number: BKLJL === Responsible Party === Company Name: PRATT & LAMBERT INC., INDUSTRIAL COATINGS DIV. Box:2153 City:WICHITA State:KS ZIP:67201 Country:US Info Phone Num:316-733-1361 Emergency Phone Num:716-873-6000/DOT:800-255-3924 Preparer's Name:W. A. ELLISON CAGE:PRATT === Contractor Identification === **Company Name: PRATT & LAMBERT** Address:250 PETTIT AVE Box:2153 City:BELLMORE State:NY ZIP:11710 Country:US Phone:800-647-2253 CAGE:PRATT Company Name: PRATT AND LAMBERT INC Address:Box:6027 City:CLEVELAND State:OH ZIP:44101-1027 Country:US Phone:216-566-2902 CAGE:61196 

Ingred Name:M

INERAL SPIRITS (SOLVENT) (VAPOR PRESSURE 2 MM HG @ 20C) (LFL: 1.0 UFL: 7.0) CAS:64742-88-7 Fraction by Wt: 30% Other REC Limits:NONE SPECIFIED OSHA PEL:100 PPM/ 525 MG/M3 ACGIH TLV:100 PPM/ 525 MG/M3

Ingred Name:TITANIUM DIOXIDE CAS:13463-67-7 RTECS #:XR2275000 Fraction by Wt: 5% Other REC Limits:NONE SPECIFIED OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:TALC (PIGMENT) CAS:14807-96-6 RTECS #:VV7720000 Fraction by Wt: 30% Other REC Limits:NONE SPECIFIED OSHA PEL:2 MG/ M3 /20 MPPCF ACGIH TLV:2 MG/M3 /15 MPPCF

Ingred Name:VOC: 3.27 LB/GL LESS WATER & NPRS\*; 392 G/L LESS WATER; CALCULATED \*NEGLIGIBLY PHOTOCHEMICALLY REACTIVE MATERIALS RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Ingred Name:VOC: 6.58 LB/GAL SOLIDS; 790 G/L SOLIDS; CALCULATED RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:INGEST/INHALE/EYE/SKIN: IRRITATION

(GASTROINTESTINAL, NOSE, THROAT, EYE, SKIN). LUNG ASPIRATION MAY CAUSE CHEMICAL PNEUMONITIS, WHICH CAN BE FATAL. CENTRAL NERVOUS SYSTEM DEPRESSION. SKIN DEFATTING. O VEREXPOSURE: SOLVENTS ARE ASSOCIATED WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. Effects of Overexposure:INGEST: NAUSEA/VOMITING. INHALE: HEADACHES, DIZZINESS, NAUSEA, CONFUSION.

======================== First Aid Measures

First Aid:INGEST: DO NOT INDUCE VOMITING. CALL POISON CONTROL, EMERGENCY ROOM OR PHYSICIAN IMMEDIATELY. INHALE: REMOVE TO FRESH AIR IMMEDIATELY. GIVE ARTIFICIAL RESPIRATION IF NEEDED. KEEP WARM & QUIET. GET IMM EDIATE MEDICAL AID. EYE: FLUSH THOROUGHLY WITH LARGE AMOUNT OF WATER FOR 15 MIN. GET MEDICAL AID. SKIN: REMOVE CONTAMINATED CLOTHES. WASH AFFECTED AREA WITH SOAP & WATER. PERSISTANT IRRIT GET MED AID.

======= Fire Fighting

Flash Point:>108F,>42C

Autoignition Temp:Autoignition Temp Text:572F

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:USE NFPA CLASS B(CO2, ALL PURPOSE DRY CHEMICAL OR ALCOHOL FOAM) FOR LIQUID FIRES. POLYMER FOAM PREFERRED FOR LARGE FIRES

Fire Fighting Procedures:USE SCBA. WATER MAY BE INEFFECTIVE, USE TO COOL CNTNRS(FOG NOZZLE PREFERABLE) TO PREVENT PRESSURE BUILD-UP&AUTO- IGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT Unusual Fire/Explosio

n Hazard:OVEREXPOSURE-DECOMP PRODUCTS MAY CAUSE HEALTH HAZARD. SYMPTOMS MAY NOT BE IMMED APPARENT. GET MED AID. KEEP CNTNRS CLOSED, AWAY FROM IGNITE SOURCES-MAY EXPLODE.

Spill Release Procedures: KEEP SPECTATORS AWAY. ELIMINATE ALL IGNITE SOURCES. DIKE, CONTAIN & REMOVE WITH INERT MATERIAL (SAND, EARTH, ETC). USE COVERED METAL CONTAINERS FOR RECOVERY AND DISPOSAL. USE NON-SPARKING TOOLS. PREVE NT CONTAMINATI ON OF SEWERS, STREAMS & GROUNDWATER.

Handling and Storage Precautions:DO NOT STORE ABOVE 100F. LARGE QUANTITY STORAGE: COMPLY WITH OSHA 29CFR1910.106. DO NOT TAKE INTERNALLY. CONTAINERS CLOSED AFTER USE.
Other Precautions:DO NOT REUSE CONTAINER FOR ANY PURPOSE. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD, BRAZE OR CUT ON EMPTY CONTAINER. NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PR ESSURE VESSEL.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:RESTRICTED AREA: NIOSH APPR'D CHEMICAL CARTRIDGE RESPIRATOR. SPRAYING: MECHANICAL PREFILTER MAY BE REQUIRED. CONFINED AREAS: NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR. EXCEEDED TLV AREA: NIOSH/MSHA APPROVED RESPIRATOR W/RIGHT FACTOR. Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN SUFFICIENT VOLUME & PATTERN TO KEEP CONCENTRATIONS BELOW EXPOSUR E LIMITS. Protective Gloves:REPEAT/PROLONG USE: IMPERMEABLE GLOVES. Eye Protection:SAFETY SPECTACLES. Other Protective Equipment:NOT LIKELY TO BE NEEDED. Supplemental Safety and Health

HCC:F4 Boiling Pt:B.P. Text:277 TO 388F Melt/Freeze Pt:M.P/F.P Text:-50F,-46C Decomp Temp:Decomp Text:1832F,1000C Vapor Pres:2 Vapor Density:> THAN AIR Spec Gravity:1.2 pH:4-7 Viscosity:70-80 Evaporation Rate & amp; Reference:SLOWER THAN DIETHYL ETHER Solubility in Water:SLIGHT Appearance and Odor:LIQUID, SOLVENT ODOR Percent Volatiles by Volume:50

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID EXCESS HEAT (>100F) & IGNITION
SOURCES.
Hazardous Decomposition Products:BURNING,INCLUDING WHEN HEATED BY
WELDING OR CUTTING WILL PRODUCE SMOKE, CARBON MONOXIDE AND CARBON DIOXIDE.

\_\_\_\_\_

==== Disposal Considerations =============

Waste Disposal Methods:FOLLOW FEDERAL, STATE AND LOCAL REGULATIONS & LAWS. INCINERATE IN EPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS. USE PRECAUTIONS FOR DISPOSAL OF HAZARDOUS MATERIAL-D001. USE HAZARDOUS WA STE LANDFILL FOR USED ABSORBENT.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of

America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.