

TEXACO INC -- 00435 DIESEL FUEL 2 (BURNER OIL #2) -- 9140-00-286-5297

=====
Product Identification
=====

Product ID:00435 DIESEL FUEL 2 (BURNER OIL #2)

MSDS Date:03/12/1991

FSC:9140

NIIN:00-286-5297

MSDS Number: BKLQH

=== Responsible Party ===

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Info Phone Num:914-831-3400 EXT 204

Emergency Phone Num:914-831-3400 EXT
204

Preparer's Name:R.T. RICHARD

CAGE:7B131

=== Contractor Identification ===

Company Name:COOL FUEL INCORPORATED (310-630-6000)

CAGE:COOL1

Company Name:STAR ENTERPRISE

Address:12700 NORTHBOROUGH

Box:City:HOUSTON

State:TX

ZIP:77067

Country:US

Phone:914-838-7204

CAGE:STARE

Company Name:TEXACO INC

Box:509

City:BEACON

State:NY

ZIP:12508-0509

Country:US

Phone:914-831-3400

CAGE:7B131

=====
Composition/Information on Ingredients
=====

Ingred Name:PETROLEUM DISTILLATES (BLENDS OF PE

TROLEUM DISTILLATE

CONSISTING OF MAINLY HYDROCARBONS RANGING FROM C6 TO C20)

Fraction by Wt: 100.0%

Other REC Limits:5MG/CUM,AS OIL MIST

=====
Hazards Identification
=====

LD50 LC50 Mixture:ORAL LD50 (RAT) IS 9.0 ML/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION- NARCOSIS OR DROWSINESS. EYES- IRRITATION. SKIN- SEVERE IRRITATION. BURNS AND

BLISTERING. INGESTION- IRRITATION, BURNS, BLITERING OF MOUTH, ESOPHAGUS AND STOMACH. CHRONIC: MANUFACTURER STATES POSSIBLE CANCER OR KIDNEY DAMAGE.

Explanation of Carcinogenicity:MANUFACTURER STATES POSSIBLE CARCINOGEN FROM "MIDDLE DISTILLATES".

Effects of Overexposure:INHALATION: DIZZINESS, DROWSINESS. EYES: BURNING SENSATION, REDNESS. SKIN: BURNS, RASH, BLISTERS. INGESTION: BURNING OF MOUTH AND ESOPHAGUS. NAUSEA, VOMITING, STOMACH PAIN.

Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN DISORDERS MAY BE AGGAVATED BY EXPOSURE.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR. SKIN: WASH WITH SOAP AND WATER. INGESTION: DO NOT INDUCE VO MITING! SEE DOCTOR. SEE DOCTOR IF ANY SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Po

int Method:PMCC

Flash Point:160F,71C

Autoignition Temp:Autoignition Temp Text:500F

Lower Limits:0.52 %

Upper Limits:4.1 %

Extinguishing Media:WATER SPRAY, DRY CHEMICAL, FOAM, OR CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. USE WATER FOG TO COOL FIRE EXPOSED CONTAINERS AND TO DIPERSE VAPORS.

Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill

Release Procedures:CONTAIN SPILL. ABSORB ON SUITABLE MATERIAL,
SCOOP UP AND PLACE IN CONTAINER FOR DISPOSAL. VENTILATE AREA. AVOID
BREATHING VAPORS. AVOID ALL PERSONAL CONTACT. USE SELF-CONTAINED
BREATHING APPARATUS IN CONFINED AREA.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM HEAT AND IGNITION
SOURCES. HANDLE AND STORE IN ACCORDANCE WITH OSHA REG. 1910.106.

Other Precautions:USE
ONLY AS A FUEL.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SELF-CONTAINED BREATHING APPARATUS IF
PEL/TLV EXCEEDED AS IN A LARGE SPILL OR CONFINED AREA.

Ventilation:USE ADEQUATE MECHANICAL VENTILATION.

Protective Gloves:NITRILE, PVA

Eye Protection:SAFETY GLASSES/CHEMICAL SPLASH GOGGLES

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:USE GOOD PERSONAL HYGENE. LAUNDRY CONTAMINATED
CLOTHING BEFORE REUSE.

Supplemental Safety and Health

AVOID PROLONGED OR REPEATED EXPOSURE. DO NOT GET ON SKIN OR IN EYES. DO
NOT BREATHE VAPORS OR MISTS. NOTE TO PHYSICIAN: ASPIRATION OF THIS
PRODUCT DURING INDUCED EMESIS CAN RESULT IN LUNG INJURY. IF E
VACUATION OF STOMACH CONTENTS IS CONSIDERED NECESSARY, USE METHOD
LEAST LIKELY TO CAUSE ASPIRATION.

=====
===== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:650F,343C

Spec Gravity:0.8521

Viscosity:3.0CST @ 100

F

Solubility in Water:NEGLIGIBLE

Appearance and Odor:CLEAR, BRIGHT LIQUID

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:HEAT, FLAME AND OTHER SOURCES OF IGNITION.

Hazardous Decomposition Products:OXIDES OF CARBON

=====
===== Disposal Considerations =====

Waste Disposal Methods:IF DISCARDED IN ORIGINAL FORM, DISPOSE OF AS AN
IGNITABLE MATE

RIAL (D001) UNDER RCRA. OTHERWISE CONTACT LOCAL
ENVIRONMENTAL MANAGER AND DISPOSE OF IN ACCORDANCE WITH LOCAL,
STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.