

AMOCO OIL CO -- AMOCO LDO SG MOTOR OIL 10W-40 -- 9150-00-116-0506

=====  
Product Identification  
=====

Product ID:AMOCO LDO SG MOTOR OIL 10W-40

MSDS Date:10/02/1989

FSC:9150

NIIN:00-116-0506

MSDS Number: BKMWP

=== Responsible Party ===

Company Name:AMOCO OIL CO

Address:200 E RANDOLPH DR

City:CHICAGO

State:IL

ZIP:60601

Country:US

Info Phone Num:312-856-3907

Emergency Phone Num:800-447-8735;800-424-9

300(CHEMTREC)

CAGE:15958

=== Contractor Identification ===

Company Name:AMOCO OIL CO

Address:200 E RANDOLPH DR

Box:City:CHICAGO

State:IL

ZIP:60601-6401

Country:US

Phone:312-856-3907- EM HLTH: 800 447-8735

CAGE:15958

=====  
Composition/Information on Ingredients  
=====

Ingred Name:REFINED HEAVY PARAFFINIC DISTILLATES (SOLVENT REFINED  
PARAFFINIC PETROLEUM OIL) PEL/TLV AS OIL MIST.

CAS:64741-88-4

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3;10 MG/M3STEL

=====  
Hazards I  
=====

dentification =====

LD50 LC50 Mixture:LD50:(ORL,RAT)5 G/KG; (DRM,RBT)2 G/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:EYE/INHAL/INGEST:NO SIGNIFICANT HEALTH HAZARDS IDENTIFIED. SKIN:NONE EXPECTED FOR SINGLE SHORT-TERM EXPOSURES. PRLNGD/RPTD CONTACT MAY PRODUCE SOME IRRITATION. CAUTION! CONTINUOUS LONG- TERM CON TACT W/USED MOTOR OILS HAS CAUSED CANCER IN AN

IMAL TESTS. (MFR.)

Explanation of Carcinogenicity:NOT RELEVANT

Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE:FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES.

SKIN:NONE REQUIRED FOR UNUSED MOTOR OIL. CNTCT W/USED MOTOR OIL, WASH AREA THOROUGHLY W/SOAP & WATER OR USE WATERLESS HAND CLEANERS. DO NOT USE GAS OLIN, THINNERS OR

SOLVENTS. INHAL:IF ADVERSE

EFFECTS OCCUR, REMOVE TO UNCONTAMINATED AREA. INGEST:IF LG AMT SWALLOWED, INDUCE VOMITING. GET MD.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:401F,205C

Extinguishing Media:AGENTS APPROVED FOR CLASS B HAZARDS (E.G.,DRY CHEMICAL, CARBON DIOXIDE, HALOGENATED AGENTS, FOAM, STEAM) OR WATER FOG.

Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA AND FULL PROTECTIVE EQUIPMENT .

Unusual Fire

/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN ON ABSORBENT MATERIAL (E.G., SAND, SAWDUST, DIRT, CLAY). KEEP OUT OF SEWERS AND WATERWAYS.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:WEAR PROTECTIVE CLOTHING AND IMPERVIOUS GLOVES WHEN WORKING W/USED MOTOR OILS.

Other Precautions:NONE SPECIFIED BY MANUF

ACTURER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED; HOWEVER, USE OF ADEQUATE VENTILATION IS GOOD INDUSTRIAL PRACTICE.

Ventilation:NONE SPECIFIED BY MANUFACTURER.

Protective Gloves:IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:PROTECTIVE CLOTHING.

Work Hygienic Practices:REMOVE OIL-SOAKED CLTHG, INCLUDING SHOES, & THOROUGHLY CLEAN & DRY BEFORE RE-USE.

Supplemental Safety and Health

N

ONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.88

Solubility in Water: