

COLUMBUS CHEMICAL INDUSTRIES INC -- AMMONIUM HYDROXIDE -- 6810-00-243-4436

=====
Product Identification
=====

Product ID:AMMONIUM HYDROXIDE

MSDS Date:04/06/1989

FSC:6810

NIIN:00-243-4436

MSDS Number: BKMWV

=== Responsible Party ===

Company Name:COLUMBUS CHEMICAL INDUSTRIES INC

Address:N 4335 TEMKIN RD

City:COLUMBUS

State:WI

ZIP:53925

Country:US

Info Phone Num:414-623-2140

Emergency Phone Num:414-

623-2140/CHEMTREC 800-424-9300

CAGE:5Y144

=== Contractor Identification ===

Company Name:COLUMBUS CHEMICAL INDUSTRIES INC

Address:N 4335 TEMKIN RD

Box:8

City:COLUMBUS

State:WI

ZIP:53925-0008

Country:US

Phone:920-623-2140

CAGE:5Y144

=====
Composition/Information on Ingredients
=====

Ingred Name:AMMONIUM HYDROXIDE (SARA III)

CAS:1336-21-6

RTECS #:BQ9625000

Fraction by Wt: 58%

Other REC Limits:NONE SPECIFIED

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazar

ds Identification =====

LD50 LC50 Mixture:LD50 (ORAL RAT) IS 350 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INHALATION MAY CAUSE COUGHING,SORE THROAT AND LABORED BREATHING.INGESTION MAY CAUSE PAIN IN THE MOUTH,CHEST & ABDOMEN WITH COUGHING,VOMITING AND COLLAPSE.VAPORS MAY CAUSE SKIN BURNS WITH VESICATION.EYE CONTACT MAY CAUSE PAIN AND

IRIS ATROPHY
AND CATARACTS.

Medical Cond Aggravated by Exposure:PRE-EXISTING EYE DISORDERS OR IMPAIRED RESPIRATORY FUNCTION MAY BE MORE SUSCEPTIBLE TO THE EFFECTS OF THIS MATERIAL.

===== First Aid Measures =====

First Aid:SEEK MEDICAL CARE.EYES AND SKIN:FLUSH WITH LARGE AMOUNT OF WATER FOR ABOUT 15-20 MINUTES.INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NEEDED.INGESTION:GIVE SEVERAL GLASSES OF WATER TO DRINK TO DILUTE.VOMITIN

G MAY OCCUR SPONTANEOUSLY,BUT DO NOT INDUCE.

===== Fire Fighting Measures =====

Autoignition Temp:Autoignition Temp Text:1204F

Lower Limits:16

Upper Limits:27

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.USE WATER TO FLUSH NON-IGNITED SPILLS/VAPORS AWAY FROM FIRE.

Fire Fighting Procedures:USE NIOSH-APPROVED SCBA & FULL FACEPIECE OPERATED IN THE PRESSURE DEMAND/OTHER POSITIVE PRESSURE MODE.USE WATER SPRAY TO COOL

NEARBY CONTAINERS EXPOSED TO FIRE.

Unusual Fire/Explosion Hazard:NOT CONSIDERED TO BE AN EXPLOSION HAZARD.

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE & EVACUATE AREA.USE PROTECTIVE CLOTHING & RESPIRATORS.SPILLS MAY BE NEUTRALIZED BY DILUTE HCL/H2SO4 & DISCHARGED TO SEWER WITH LARGE AMOUNT OF WATER.DON'T FLUSH DIRECTLY TO SEWERS.ALTERNATIVELY,SPILLS MAY BE ABSORBED WITH DRY INERT MATERIAL

Neutralizing Agent:DILUTE HCL

OR H2SO4

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY & VENTILATED
AREA.KEEP CONTAINER TIGHTLY CLOSED.PROTECT FROM DIRECT SUNLIGHT.
Other Precautions:WASH THOROUGHLY AFTER EACH USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE A DUST/MIST RESPIRATOR WITH CHEMICAL GOGGLES
IF THE TLV IS EXCEEDED.ALTERNATIVELY, A SUPPLIED AIR FULL FACEPIECE
RESPIRATOR OR AIRLIN
ED HOOD MAY BE WORN.

Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:PROTECTIVE CLOTHINGS.EYE-WASH
FACILITIES,SAFETY SHOWER.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE
VAPORS/MIST/DUST.WASH THOROUGHLY AFTER EACH USE;DO NOT
EAT,DRINK,SMOKE.

Supplemental Safety and Health

FORMULA CHANGED. TO CHECK THE PREVIOUS FORMULA, SEE P/N A SAME NSN.

=====
Physical/Chemical Properties
=====

HCC:G6

Boiling Pt:B.P. Text:97.0F,36.1C

Melt/Freeze Pt:M.P/F.P Text:-98F,-72C

Vapor Pres:115 @ 68F

Vapor Density:1.2

Spec Gravity:0.9

Solubility in Water:INFINITE

Appearance and Odor:CLEAR,COLORLESS SOLUTION, AMMONIA ODOR

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

ACIDS,ACROLEIN,DIMETHYL SULFATE,HALOGENS,SILVER NITRATE,PROPYLENE
OXIDE,NITROMETHANE,SILVER OXIDES/PERMANGANATE,OLEUM

Stability Condition to Avoid:HIGH TEMPERATURES AND OPEN FLAMES
Hazardous Decomposition Products:EMITS TOXIC FUMES OF AMMONIA AND
NITRIC OXIDES WHEN HEATED TO DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods:CONSULT LOCAL AUTHORITIES;DISPOSAL MUST BE IN
ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements o
f the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.