View NSN Online: https://aerobasegroup.com/nsn/9140-00-286-5294

Product ID:NO. 2 DIESEL FUEL MSDS Date:01/01/1987 FSC:9140 NIIN:00-286-5294 MSDS Number: BKNTP === Responsible Party === **Company Name: FRONTIER OIL & REFINING COMPANY** Address:1600 BROADWAY City:DENVER State:CO ZIP:80202 Country:US Info Phone Num:307-634-3551 Emergency Phone Num:800-424-9300(CHEMTREC) CAGE: JO753 === Contractor Identification === Company Name: FRONTIER OIL & REFINING CO Address:1600 BROADWAY Box:City:DENVER State:CO ZIP:80202 Country:US CAGE: JO753 Company Name: FRONTIER OIL AND REFINING COMPANY Address:1600 BROADWAY Box:City:DENVER State:CO ZIP:80202 Country:US Phone:307-634-3551 CHEMTREC 800-424-9300 CAGE:0A0Y5

Ingred Name:HYDROCARBONS Other REC Limits:NONE SPECIFIED

====== Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:THE PRODUCT MAY CAUSE IRRITATION TO EYES, SKIN, AND LUNGS AFTER PROLONGED OR REPEATED EXPOSURE. EXTREME EXPOSURE OR ASPIRATION INTO THE LUNGS MAY CAUSE PNEUMONIA. Explanation of Carcinogenicity:STUDIES WITH RODENTS HAVE SHOWN THAT PETROLEUM DISTILLATES HAVE CAUSED KIDNEY DAMAGE & KIDNEY OR LIVER TUMOR S. Effects of Overexposure:OVEREXPOSURE MAY CAUSE WEAKNESS, HEADACHE,

Effects of Overexposure:OVEREXPOSURE MAY CAUSE WEAKNESS, HEADACHE, DROWSINESS, CONFUSION, BLURRED VISION, OR NAUSEA; GREATER EXPOSURE MAY CAUSE DIZZINESS, SLURRED SPEECH, FLUSHED FACE, UNCONSCIOUSNESS, OR CONVULSION.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

First Aid:EYE-IMMEDIATELY FLUSH WITH WATER FOR 15 MINUTES & SEEK MEDICAL ATTENTION. SKIN-REMOVE SOILED CLOTHES. WASH SKIN WIT H SOAP

& WATER. IF IRRITATION DEVELOPS, CONSULT A PHYSICIAN. INHALE-REMOVE TO FRESH A IR. IF STOP BREATHING, GIVE CPR. SEEK MEDICAL ATTENTION. INGEST-DO NOT INDUCE VOMITING. IF VOMIT OCCURS, LOWER HEAD IN AN EFFORT TO PREVENT VOMITUS FROM ENTERING LUNGS. SEEK MEDICAL ATTENTION.

Flash Point Method:TCC Flash Point:130F,54C Autoignition Temp:Autoignition Temp Text:494F Extinguishing Media:USE WATER SPRAY, CAR BON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures: IF LEAK/SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE VAPORS & TO FLUSH SPILLS AWAY FROM EXPOSURES. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:PRODUCT OF COMBUSTION MAY CONTAIN CARBON MONOXIDE & DIOXIDE & OTHER TOXIC MATERIALS. DO NOT ENTER ENCLOSED SPACE WITHOUT PROPER PROTECTIVE EQUIPMENT/RESPIRATOR.

Spill

Release Procedures:MATERIAL IS COMBUSTIBLE. CONTAIN SPILL IMMEDIATELY. RECOVER BY VACUUMING, THEN SOAK UP RESIDUAL FLUID BY USING ABSORBENT MATERIALS. NONRECOVERABLE PRODUCT, CONTAMINATED SOIL, DEBRIS & OTHER MATERIAL S HOULD BE PLACED IN PROPER CONTAINERS FOR DISPOSAL.

Handling and Storage Precautions:PRODUCT IS CLASS II COMBUSTIBLE LIQUID PER NFPA CODE NO. 30-1987. STORE AND HANDLE ACCORDINGLY. Other Prec

autions:AVOID WASHING, DRAINING OR DIRECTING SPILLED MATERIAL TO STORM OR SANITARY SEWER. IF CONDITIONS WARRANT, WEAR PROTECTIVE AND IF APPLICABLE USE EXPLOSION-PROOF EQUIPMENT.

Respiratory Protection: USE AIR MASK OR HYDROCARBON ABSORBING RESPIRATOR WHEN EXPOSED TO OIL SPRAY OR MISTS.

Ventilation: GENERAL MECHANICAL VENTILATION IS NORMALLY ADEQUATE. Protective Gloves: VINYL, NEOPRENE OR NBR.

Eye Protection: FACE SHIEL

D RECOMMENDED.

Other Protective Equipment:COVERALLS OR OTHER PROTECTIVE APPAREL NEEDED IF SPLASH IS PROBABLE. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. Work Hygienic Practices:KEEP BODY CONTACT AND SPLASH TO A MINIMUM. Supplemental Safety and Health

AVOID ALL IGNITION SOURCES UNTIL THE CONTAMINATED STORAGE CONTAINER IS ISOLATED AND CLEAR OF ALL FLAMMABLE AND TOXIC VAPOR CONCENTRATIONS. USE ADEQUATE VENTILATION TO REMOVE VAPOR FROM CONTAINER.

======= Physical/Chemical P

roperties ==============

HCC:F4 Boiling Pt:B.P. Text:350F,177C Vapor Pres:1 Spec Gravity:0.85-0.93 Solubility in Water:INSOLUBLE Appearance and Odor:CLEAR OR LIGHT YELLOW LIQUID; AROMATIC ODOR. Percent Volatiles by Volume:NIL

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING MATERIALS. Stability Condition to Avoid:HIGH HEAT, OPEN FLAMES. Hazardous Decomposition Products:INCOMPLETE COMBUSTION MAY PRODUCE CAR

BON MONOXIDE.

Waste Disposal Methods:RECYCLE AS MUCH OF THE RECOVERABLE PRODUCT AS POSSIBLE. DISPOSE OF NONRECYCLABLE MATERIAL BY SUCH METHODS AS INCINERATION, COMPLYING WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.