

UNI-KEM INTERNATIONAL CORPORATION/MFR OXYCHEM -- RIFLE BORE CLEANER --  
6850-00-224-6658

===== Product Identification =====

Product ID:RIFLE BORE CLEANER

MSDS Date:07/31/1995

FSC:6850

NIIN:00-224-6658

MSDS Number: BKSJW

=== Responsible Party ===

Company Name:UNI-KEM INTERNATIONAL CORPORATION/MFR OXYCHEM

Address:513 HICKORY AVENUE

Box:23384

City:HARAHAN

State:LA

ZIP:70183

Country:US

Info Phone Num:

504-738-1623/713-623-2246

Emergency Phone Num:504-738-1623/800-533-2246

CAGE:4S446

=== Contractor Identification ===

Company Name:UNI-KEM INTERNATIONAL

Address:1001 HARIMAW COURT EAST

Box:City:METAIRIE

State:LA

ZIP:70001

Country:US

Phone:504-835-7600/FAX:504-835-7608

CAGE:4S446

===== Composition/Information on Ingredients =====

Ingred Name:SOLVENT PETROLEUM HYDROCARBON

Fraction by Wt: 60%

Other REC Limits:200 PPM

Ingred Name:LIGHTWEIGHT OIL

Fraction by Wt: 35%

Other REC Limi

ts:NONE RECOMMENDED

Ingred Name:CORROSION INHIBITOR

Fraction by Wt: 5%

Other REC Limits:NONE RECOMMENDED

=====  
===== Hazards Identification =====

LD50 LC50 Mixture:PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED

Health Hazards Acute and Chronic:MFR GAVE NO INFORMATION OF MSDS. SEE SIGNS & SYMPTOMS.

Explanation of Carcinogenicity:MFR GAVE THE ABOVE LISTINGS ON THE MSDS BUT NO OTHER COMMENTS ABOUT CARCINOGENICITY WERE RECORDED.

Effects of Overexposure:PROLONGED SKIN

CONTACT MAY CAUSE IRRITATION & DERMATITIS. PROLONGED EXPOSURE TO VAPOR MAY CAUSE EYE & RESPIRATORY TRACT IRRITATION & HEADACHE.

=====  
===== First Aid Measures =====

First Aid:SKIN:WASH W/SOAP & WATER. EYE:FLUSH W/LARGE AMOUNT OF WATER. IF IRRITATION PERSISTS, SEEK MEDICAL AID. INHALATION:REMOVE TO FRESH AIR. INGESTION:DO NOT INDUCE VOMITING-ADMINISTER 2-4 OZ OLIVE OIL OR VEGTABLE OIL & 1-2 OZ ACTIVATED CHARCOAL; SEEK MEDICAL AID.

=====  
===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:255F,124C

Lower Limits:0.7

Upper Limits:5.0

Extinguishing Media:DRY CHEMICAL PREFERRED. FOAM & WATER ALSO APPLICABLE

Fire Fighting Procedures:USE FOAM & WATER SPRAY CAREFULLY TO PREVENT EXCESSIVE FROTHING.

Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT OR OPEN FLAME. CAN REACT WITH OXIDIZING MATERIAL, COMBUSTIBLE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW. ELIMINATE IGNITION SOURCES.YABSSORB  
OR SCRAPE UP.

Neutralizing Agent:MFR GAVE NO INFORMATION OF MSDS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM POSSIBLE SOURCES OF  
IGNITION.

Other Precautions:MFR GAVE NO INFORMATION OF MSDS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE DURING NORMAL USAGE. VAPOR REMOVING AIR  
PURIFYING

RESPIRATOR FOR MIST & SPRAY.

Ventilation:USE LOCAL EXHAUST TO KEEP EXPOSURE