

BEESTON -- DAMPING FLUID, SILICONE BASE -- 9150-00-269-8246

=====
Product Identification
=====

Product ID:DAMPING FLUID, SILICONE BASE

MSDS Date:06/01/1988

FSC:9150

NIIN:00-269-8246

MSDS Number: BKSMC

=== Responsible Party ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Info Phone Num:207-883-5541

Emergency Phone Num:800-424-9300

Preparer's

Name:N. J. HILL

CAGE:43728

=== Contractor Identification ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Phone:207-883-5541

CAGE:43728

=====
Composition/Information on Ingredients
=====

Ingred Name:NON HAZARDOUS INGREDIENT

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

LD50 LC50 Mixture:LD50 > 5 G/KG (RAT)

Routes of Entry: Inhalation:NO Skin:NO

Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:HUMAN EXPERIENCE WITH SILICONE FLUIDS HAS NOT INDICATED ANY SERIOUS EFFECTS RELATED TO EXPOSURE BY ANY ROUTE. DIRECT EYE CONTACT CAN CAUSE A TRANSITORY IRRITATION BUT IS NOT INJURIOUS. THIS IRRITATION MAY PERSIST FOR UP TO 24 HOURS.

Effects of Overexposure:SEE "HEALTH HAZARD"

Medical Cond Aggravated by Exposure:NONE STATED.

=====
===== First Aid Measures =====
=====

First Aid:NONE STATED.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:OC

Flash Point:275F/135C

Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY CHEMICAL.

Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A FULL FACED SELF CONTAINED BREATHING APPARATUS.

Unusual Fire/Explosion Hazard:UNDER FIRE CONDITIONS IRRITATING AND/OR TOXIC VAPORS OR GASES MAY BE PRESENT.

=====
===== Accidental Release

Measures =====

Spill Release Procedures:WIPE UP MATERIAL RESIDUE IS SLIPPERY. APPLY SAWDUST OR SWEEPING COMPOUND TO AREA OF SPILL TO MINIMIZE SLIP.

Neutralizing Agent:NONE

=====
===== Handling and Storage =====
=====

Handling and Storage Precautions:NO SPECIAL PRECAUTIONS ARE KNOWN.

Other Precautions:NONE STATED.

=====
===== Exposure Controls/Personal Protection =====
=====

Respiratory Protection:NONE REQUIRED USUALLY.

Ventilation:NORMAL VENTI

LATION.

Protective Gloves:PLASTIC OR RUBBER

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE

Work Hygienic Practices:NONE STATED.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:572F/300C

Melt/Freeze Pt:M.P/F.P Text:-40F/-40C

Vapor Pres:NILL

Vapor Density:>1

Spec Gravity:0.94

Solubility in Water:INSOLUBLE

Appearance and Odor:CLEAR, COLORLESS LIQUID, ODORLESS.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED BY MANUFACTURER.

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products:CARBON DIOXIDE AND OXIDES OF SILICON.

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION OR LANDFILL IN ACCORDANCE WITH
FEDERAL, STATE, AND LOCAL ENVIRONMENTAL CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.