View NSN Online: https://aerobasegroup.com/nsn/6850-00-592-3283

REXSELLIX LABORATORIES, INC. -- CLEANING COMPOUND, OPTICAL LENS -- 6850-00-592-3283

Product ID:CLEANING COMPOUND, OPTICAL LENS MSDS Date:07/01/1990 FSC:6850 NIIN:00-592-3283 **MSDS Number: BKSSC** === Responsible Party === Company Name: REXSELLIX LABORATORIES, INC. Box:426 City:CAMDEN State:TN ZIP:38320 Country:US Info Phone Num:901-584-7860 **Emergency Phone Num:1-800** -424-9300 CHEMTREC Preparer's Name: JACK BEAUCHAMP CAGE:9J970 === Contractor Identification === Company Name: REXSELLIX LABORATORIES, INC. Box:City:CAMDEN State:TN ZIP:38320 Country:US Phone:901-584-7860 CAGE:9J970

Ingred Name:NON-HAZARDOUS INGREDIENTS Other REC Limits:NONE SPECIFIED

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcino

genicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALE:ANESTHETIC. CAN CAUSE SERIOUS NERVOUS SYSTEM DEPRESSION.
Effects of Overexposure:INHALE:IRRITATES RESPIRATORY TRACT. SKIN:PRIMARY IRRITATION TO SKIN, DEFATTING & DERMATITIS. EYES:IRRITATION TO EYES, REDNESS, TEARING, BLURRED VISION. SWALLOWING:SWALLOWING CAN CAUSE ABDOMINAL IRRITA TION, NAUSEA, VOMITING & DIARRHEA.

First Aid:SKIN:FL

USH W/PLENTY OF WATER. EYES:FLUSH W/PLENTY OF WATER FOR 15 MINUTES & GET MED ATTN. AFTER HIGH VAPOR EXPOSURE, REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT GIVE OXYGEN. IF BREATHING HAS STOPPE D GIVE CPR. SWALLOW:CALL PHYSICIAN IMMEDIATELY! INDUCE VOMITING PROMPTLY FOLLOW PHYSICIAN'S INSTRUCTIONS OR BY HAVING PATIENT STICK FINGER DOWN THROAT. NEVER GIVE ANYTHING BY MOUTH IF UNCONSCIOUS.

Extinguishing

Media:NFPA CLASS B EXTINGUISHERS (CO2 OR FOAM) FOR CLASS III B LIQUID FIRES.

Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE BUT USED TO COOL CLOSED CONTAINER.USE FOG NOZZLES.WEAR FULL BUNKER GEAR.USE APPROVED POSITIVE-PRESS SELF CONTAIN BREATH APPARATUS Unusual Fire/Explosion Hazard:KEEP CONTAINER TIGHTLY CLOSED.ISOLATE FROM OXIDIZERS,HEAT,OPEN FLAME.CLOSED CONTAINER MAY EXPLODE FROM

EXTREME HEAT.HOT SURFACE APPLICATION REQUIRES PRECAUTIONS

Spill Release Procedures:STOP SPILL AT SOURCE. DIKE AREA & CONTAIN. PUMP SPILLED LIQUID & PUT CONTAMINATED SOIL IN DOT APPROVED CONTAINERS FOR DISPOSAL. LABEL IMMEDIATELY. CLEAN UP REMAINDER WITH ABSORBENT MATERIALS.

Handling and Storage Precautions:DO NOT STORE ABOVE 49C/120F. STORE LARGE AMOUNTS IN STRUCTURES MADE FOR OSHA CLASS III B LIQUIDS. AVOID FREE FALL OF LIQUIDS.

Other Precautions: GROUND CONTAINERS WHEN TRANSFERRING. DO NOT FLAME CUT, BRAZE OR WELD. EMPTY CONTAINER VERY HAZARDOUS! CONTINUE ALL LABEL PRECAUTIONS.

====== Exposure Controls/Personal Protection ==========

Ventilation:LOCAL EXHAUST:NECESSARY. MECHANICAL (GENERAL):ACCEPTABLE Protective Gloves:WEAR IMPERVIOUS GLOVES Eye Protection:WEAR GOGGLES OR FACE SHIELD Other Protective Equipment:WEAR GLOVES, APRON & FOOTWEAR IMPERVIOUS TO THIS MATERIAL. Work Hygienic Pra ctices:WASH CLOTHING BEFORE REUSE. Supplemental Safety and Health

HCC:N1 Boiling Pt:B.P. Text:212F,100C Vapor Pres:16.9 Vapor Density:0.6 Spec Gravity:1.0 (WATER=1) Appearance and Odor:LIQUID, WATER-WHITE Percent Volatiles by Volume:96.5

Stability Indicator/Materials to Avoid:YES ISOLATE FROM STRONG OXIDIZERS SUCH AS PERMANGANATES, CHROMATES & PEROXIDES

Stability Condition to Avoid:ISOLATE FROM OXIDIZERS, HEAT & OPEN FLAME. Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE, SILICON DIOXIDE FROM BURNING.

Waste Disposal Methods:DISPOSE OF WASTE BY LEGAL METHODS COMPLY WITH LOCAL, STATE & FEDERAL REGULATIONS. IF QUESTIONS EXIST, CONTACT THE APPROPRIATE AGENCIES.

Disclaimer (provided with this information by the compiling agencies): This informatio n is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.