

EASTMAN KODAK CO. -- 159 5065, FLEXCOLOR BLCH II REPL, PT B -- 6750-01-048-4560

=====
Product Identification
=====

Product ID:159 5065, FLEXCOLOR BLCH II REPL, PT B

MSDS Date:07/06/1990

FSC:6750

NIIN:01-048-4560

Kit Part:Y

MSDS Number: BKTBS

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Em

ergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 65-70%

Ingred Name:AMMONIUM BROMIDE

CAS:12124-97-9

RTECS #:BO9170000

Fraction by Wt: 1-5%

Ingred Name:AMMO

NIUM FERRIC ETHYLENEDIAMINETETRAACETIC ACID

CAS:21265-50-9

Fraction by Wt: 15-20%

Ingred Name:AMMONIUM FERRIC PROPYLENEDIAMINETETRAACETIC ACID

CAS:111687-36-6

Fraction by Wt: 5-10%

Ingred Name:NITRIC ACID (SARA III)

CAS:7697-37-2

RTECS #:QU5775000

Fraction by Wt: 4%

OSHA PEL:2 PPM/4 STEL

ACGIH TLV:2 PPM/4 STEL; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Ca

rcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:LOW HAZARD FOR RECOMMENDED HANDLING.

MAY CAUSE SLIGHT IRRITATION OF EYES. PRODUCT HAS LOW INGESTION HAZARD.

Effects of Overexposure:EYES: IRRITATION. SKIN/INHALATION:LOW HAZARD FOR RECOMMENDED HANDLING.

Medical Cond Aggravated by Exposure:NONE REPORTED BY MANUFACTURER.

=====
===== First Aid Measures =====

First Aid:IMMEDIATELY FLUSH EYES WITH PLENTY OF WAT & GET MEDICAL ATTE

NTION IF ANY SYMPTOMS ARE PRESENT AFTER WASHING. INGESTION: LOW HAZRD, CONSULT A PHYSICION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Lower Limits:NONE

Upper Limits:NONE

Extinguishing Media:USE AGENT APPROPRIATE FOR SURROUNDING FIRE.

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTI OF HAZA

RDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:NEUTALIZE WITH BAKING SODA. FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF WATER.

Neutralizing Agent:SODIUM BICARBONATE

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSE AND AWAY FROM STRONG ALKALI AND STRONG OXIDIZING AGENTS.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED.

Ventilation:GOOD GENERAL VENTILATION SHOULD BE SUFFICIENT (MECHANICAL)

Protective Gloves:IMPERVIOUS FOR PROLONGED/REPEATED HANDLG

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE SPECIFIED BY MFR.

Work Hygienic Practices:USE GOOD CHEMICAL HYGIENE PRACTICES.

Supplemental Safety and Health

THIS IS PART-B OF A TWO-PART KIT. THIS PART B HAS FORMULATOIN CHANGED.

ONE PACKAGE MAKES 12.5 GALLONS OF WORKING SOLUTION.

===== Physical/Chemical Properties =====

HCC:C1

Boiling Pt:B.P. Text:212F, 100C

Vapor Pres:18 MM

Vapor Density:0.6

Spec Gravity:1.177

pH:2.5

Solubility in Water:COMPLETE

Appearance and Odor:DARK BROWN LIQUID. SLIGHT ODOR.

Percent Volatiles by Volume:69

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ALKALI

Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.

Hazardous Decomposit

ion Products:CARBON DIOXIDE,CARBON MONOXIDE, OXIDES
OF NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE I/A/W FEDERAL, STATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims
all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.