View NSN Online: https://aerobasegroup.com/nsn/8040-00-515-2246

Product ID:FA-1030 NEUTRAL MSDS Date:03/21/1989 FSC:8040 NIIN:00-515-2246 MSDS Number: BKYLM === Responsible Party === Company Name: CLIFTON ADHESIVE, INC. Address:BURGESS PLACE **City:WAYNE** State:NJ ZIP:07470 Info Phone Num:(201) 694-0845 Emergency Phone Num: (201) 694-0845 CAGE:79833 === Contractor Iden tification === Company Name: CLIFTON ADHESIVE INC Address:BURGESS PL Box:City:WAYNE State:NJ ZIP:07470 Country:US Phone:201-694-0845; 973-694-0845 CAGE:79833

Ingred Name:TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 Fraction by Wt: 45% Other REC Limits:100 PPM OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name:HEXANE (N-HEXANE) CAS:110-54-3 RTECS #:MN9275000 Fraction by Wt: 30% Other REC Limits:50 PPM OSHA PEL:500 PPM ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:VM&P NAPHTHA (LIGROINE) CAS:8032-32-4 RTECS #:OI6180000 Fraction by Wt: 2% Other REC Limits:STEL 400 PPM OSHA PEL:300 PPM/400 STEL ACGIH TLV:300 PPM; 9192

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:SKIN: DRYNE SS, CRACKING, & IRRITATION. EYE: IRRITATION & MUCOUS MEMBRANES IRRITATION. INHALATION: NAUSEA, NARCOSIS, NERVE DAMAGE, CENTRAL NERVOUS SYSTEM EFFECTS, & PERIPHERAL NERVETISSUE DAMAGE. INGES TION: VOMITING, NUMBNESS, TINGLING, & WEAKNESS OF ARMS OR LEGS. Explanation of Carcinogenicity:NONE Effects of Overexposure:SKIN: DRYNESS, CRACKING, & IRRITATION. EYE: **IRRITATION & MUCOUS MEMBRANES IRRITATION. INHALATION: NAUSEA,** NARCOSIS, NERVE DAMAGE, CENTRAL NERVOUS SYSTEM EFFECTS, & PERIPHERAL NERVE TISSUE DAMAGE. INGE STION: VOMITING, NUMBNESS, TINGLING, & WEAKNESS OF ARMS OR LEGS. Medical Cond Aggravated by Exposure: RESPIRATORY AILMENTS.

First Aid:EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. SKIN: WASH W/SOAP & WATER. INHALATION: REMOVE TO FRESH AIR. GIVE CPR OR OXYGEN IF NEEDED. INGESTION: DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

Flash Point Method:CC Flash Point:AIR & MAY TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION & FLASHBACK.

Spill Release Procedures: ABSORB SPILL IN SAND, EARTH, VERMICULITE, OIL-DRI, OR SOL-SPEED-DRI. SHOVEL ABSORBED MATERIAL INTO STEEL CONTAINER & COVER. CLEAN UP SPILLS IMMEDIATELY.

Handling a

nd Storage Precautions:KEEP CONTAINERS TIGHTLY CLOSED & STORE IN APPROVED SOLVENT STORAGE AREA. KEEP AWAY FROM OPEN FLAME, HEAT, SPARKS, HOT SURFACES, & OXIDIZING AGENTS.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection: USE NIOSH-APPROVED ATMOSPHERE SUPPLYING OR AIR PURIFYING RESPIRATOR FOR ORGANIC VAPORS AS REQUIRED TO MAINTAIN EXPOSURE LEVELS