

DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE -- SD AL POLY ACTIVATOR, 910X376
-- 8010-00-181-8302

===== Product Identification =====

Product ID:SD AL POLY ACTIVATOR, 910X376

MSDS Date:02/09/1991

FSC:8010

NIIN:00-181-8302

Kit Part:Y

MSDS Number: BKZYN

=== Responsible Party ===

Company Name:DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address:1608 4TH ST

City:BERKELEY

State:CA

ZIP:94710

C

Country:US

Info Phone Num:818-549-7823

Emergency Phone Num:800-228-5635 /800-424-9300 CHEMTREC

CAGE:85570

=== Contractor Identification ===

Company Name:DESOTO INC PACIFIC PLANT IS COURTLANDTS AEROSPACE

Address:1608 4TH ST

Box:City:BERKELEY

State:CA

ZIP:94710

Country:US

Phone:800-228-5635 /800-424-9300 CHEMTREC

CAGE:85570

===== Composition/Information on Ingredients =====

Ingred Name:METHYL N-AMYL KETONE

CAS:110-43-0

RTECS #:MJ5075000

Fraction by Wt: 30%

Other REC Limits:NONE

SPECIFIED
OSHA PEL:100 PPM
ACGIH TLV:50 PPM; 9192

Ingred Name:CYCLOHEXANONE (SARA III)
CAS:108-94-1
RTECS #:GW1050000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 25%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 L
BS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ETHYL BENZENE (SARA III)
CAS:100-41-4
RTECS #:DA0700000
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:100 PPM/125 STEL
ACGIH TLV:100 PPM/125STEL 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-8

8-3
RTECS #:XS5250000
Fraction by Wt: < 5%
Other REC Limits:NONE SPECIFIED
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ALIPHATIC POLYISOCYANATE (VP: 0 MM HG)
CAS:28182-81-2
RTECS #:HQ9170000
Fraction by Wt: 30%
Other REC Limits:NONE SPECIFIED

Ingred Name:1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE)
CAS:822-06-0
RTECS #:MO1740000
Other REC Limits:NONE SPECIFIED
ACGIH TLV:0.005 PPM; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred
Name:VOC: 624 GRAMS/LITER
RTECS #:9999999VO
Other REC Limits:NONE SPECIFIED

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:INHALE: NASAL/RESPIR IRRIT, ACUTE
CNTRL NERVE SYS DEPRESSION (HEADACHE, DIZZINESS, STAGGER GAIT,
CONFUSION,UNCONSCIOUS). ASPHYXIATION. ALLERGIC SENSITIZE (MUCOUS
MEMB IRRIT, TIGHT CHEST, RESP TRACT IR RIT).
SKIN:DEFATTING/DERMATITIS.SENSITIZE. EYE
:IRRIT. INGEST:MAY CAUSE
GASTROINTEST IRRIT, NAUSEA, VOMITING & DIARRHEA.*
Effects of Overexposure:*ASPIRATION OF MATERIAL INTO THE LUNGS CAN
CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL. REPORTS HAVE
ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO
SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. EFFECTS
INCLUDE CONCENTRATION DIFFICULTIES, DIMINISHED ACTUAL DEXTERITY AND
MEMORY LOSS.
Medical Cond Aggravated by Exposure:PRE-EXISTING SKIN, LUNG & EY

E

CONDITIONS. LAB ANIMALS EXPOSED TO XYLENE &/OR TOLUENE SHOWED LIVER, KIDNEY, LUNG, SPLEEN, HEART & ADRENALS DAMAGE. PREGNANT MICE/RATS SHOWED EMBRYO/FETOTOXIC EFFECTS.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE PERSON TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF REQUIRED. IF BREATHING IS DIFFICULT, GIVE OXYGEN. KEEP WARM & QUIET. GET MEDICAL ATTN. SKIN: WASH AREAS WITH SOAP & WATER. DO NOT USE SOLVENTS. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE. GET MEDICAL ATTN. EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTN. PREFER AN OPHTHALMOLOGIST. INGESTION: GET MEDICAL ATTENTION.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:22.0F,-5.6C
Lower Limits:1.0%
Extinguishing Media:EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE, USE TO COOL EXPOSED CNTNRS (FOG NOZZLE PREFERRED). USE NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS & PROTECT CLOTHES.
Unusual Fire/Explosion Hazard:VAPORS MAY ACCUMULATE IN CONFINED AREAS, FORM EXPLOSIVE MIX W/AIR, TRAVEL LONG DISTANCES. FLASHBACK/FLAME TO HANDLING SITE MAY OCCUR. CLOSED CNTNRS MAY EXPLODE.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE IGNITE SOURCES. WEAR PROTECT EQUIP. AVOID BREATHING VAPORS & SKIN/EYE CONTACT. USE NON-SPARK TOOLS. EMERGENCY RESPONSE PRO IF MANAGING RELEASE IS BEYOND PERSONNEL CAPABILITY. SM:DIKE & ABSORB W/INERT MATERIAL. PUT IN OPEN DRUM, ISOLATE, FILL **
Neutralizing Agent:**W/SOLUTION OF 90-95% WATER, 2% DETERGENT, 3-8% AMMONIA. NEUTRALIZE SPILL AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CNTNR TIGHTLY CLOSED. KEEP FROM IGNITE SOURCES/MOISTURE. DO NOT STORE @ > 120F (PREFER 64-86F). STORE FLAMM LIQ IN ACCORD W

/NFPA CODES/GOV'T REG.

Other Precautions:FOLLOW GROUND/BOND PROCEDURES WHEN TRANSFERRING.AVOID FREE FALL OF LIQ.DON'T SMOKE WHERE MATERIAL IS USED OR STORED.DO NOT APPLY TO HOT SURFACES.EMPTIES MAY CONTAIN EXPLOSIVE VAPORS.DO NOT CUT, PUNCTURE, WELD ON DRUM.DO NOT TAKE INTERNALLY.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION APPROPRIATE FOR INDICATED COMPONENTS. CONFINED AREAS:NIOSH APPROVED

AIR SUPPLIED RESPIRATORS. OSHA/NIOSH STATE AIR SUPPLIED/SCBA ARE ONLY APPROPRIATE RESPIRATORY PROTECTION OF EXCEEDED ISOCYANATE LEVELS.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST VENTILATION IN VOLUME/PATTERN TO KEEP LEVEL OF HAZARD INGREDIENT BELOW TLV/PEL LIMITS.

Protective Gloves:WEAR CHEMICALLY RESISTANT GLOVES

Eye Protection:SAFETY GLASSES W/SIDESHIELDS OR GOGGLES

Other Protective Equipment:AVOID SKIN CONTACT BY USE OF OTHER PROTECTIVE CLOTHING. A SAFETY SHOWER, EYE BATH & WASHING FACILITIES.

Work Hygienic Practices:WASH CONTAMINATED CLOTHING BEFORE REUSE. AVOID SKIN CONTACT & BREATHING VAPORS OR MIST.

Supplemental Safety and Health

DEPENDING ON AMOUNT & CIRCUMSTANCES, UNAUTHORIZED RELEASE OF MATERIAL INTO ENVIRONMENT MAY BE REPORTABLE UNDER FEDERAL LAW TO THE NATIONAL RESPONSE CENTER(800-424-8802). STATE & LOCAL GOVERNMENTAL AGENCIES MAY ALSO HAVE REPORTING REQUIREMENTS. DO NOT ENTER CONFINED AREAS W/OUT AIR MONITORING, USE OF SCBA & OBSERVER.

=====
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:175 TO 382F

Vapor Density:> AIR

Spec Gravity:0.91

Evaporation Rate & Reference:SLOWER THAN N-BU AC

Appearance and Odor:CLEAR LIQUID, SOLVENT ODOR

Percent Volatiles by Volume:75.4

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID CONTACT WITH WATER, ALCOHOLS AND AMINES.

Stability Condition to Avoid:TEMPERATURES ABOVE MAX

IMUM STORAGE
TEMPERATURES.

Hazardous Decomposition Products: CARBON MONOXIDE & CARBON DIOXIDE.
OXIDES OF NITROGEN & TRACES OF HCN & ISOCYANATE MONOMER. TOXIC
GASES FROM AEROSOLS.

===== Disposal Considerations =====

Waste Disposal Methods: ENSURE MATERIAL IS PACKAGED, STORED, TRANSPORTED
& OTHERWISE MANAGED IN ACCORD W/LOCAL, STATE & FED REGS. NO DISPOSAL
METHOD IS TO BE USED THAT WOULD POSE ENVIR OR HUMAN HEALTH THREAT
INCLUDING ANY WHICH W
OULD CONTAMINATE GROUND/SURFACE WATER.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this
information to their
particular situation.