

ASPEN PAINTS -- STAIN OIL SEMI TRANSPARENT WOOD LT REDWOOD -- 8010-00-837-7964

=====
Product Identification
=====

Product ID:STAIN OIL SEMI TRANSPARENT WOOD LT REDWOOD

MSDS Date:09/01/1991

FSC:8010

NIIN:00-837-7964

MSDS Number: BLBBH

=== Responsible Party ===

Company Name:ASPEN PAINTS

Address:1128 S.W. SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Info Phone Num:206-682-4603 (M-F, 8:3

0-5:00)

Emergency Phone Num:800-424-9300 (CHEMTREC)

Preparer's Name:D. KIER

CAGE:0AL09

=== Contractor Identification ===

Company Name:ASPEN PAINTS

Address:1128 SW SPOKANE STREET

City:SEATTLE

State:WA

ZIP:98134

Country:US

Phone:800-424-9300 CHEMTREC

CAGE:0AL09

Company Name:ASPEN PAINTS/ASAMIPEN AMERICA INC

Address:1128 SPOKANE STREET

Box:City:SEATTLE

State:WA

ZIP:98134-1187

Country:US

Phone:303-573-1014(MED ONLY)

CAGE:0AL09

=====
Composition/Information on Ingredients
=====

In

Product Name:STODDARD SOLVENT
CAS:8052-41-3
RTECS #:WJ8925000
Fraction by Wt: 100%
Other REC Limits:NONE SPECIFIED
OSHA PEL:500 PPM
ACGIH TLV:100 PPM; 9293

=====
Hazards Identification
=====

LD50 LC50 Mixture:SEE INGREDIENTS

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: NASAL & RESPIRATORY

IRRITATION, DIZZINESS, WEAKNESS, FATIGUE, NAUSEA, HEADACHE,

POSSIBLE UNCONSCIOUSNESS, ASPHYXIATION. MAY BE HARMFUL OR FATAL.

SKIN: PROLONGED & REPEATED CONTACT W/SKIN CAN CAUSE DEFATTING &

DRYING OF SKIN RESULTING IN IRRITATION & DERMATITIS. EYE: SEVERE

IRRITATION, REDNESS, TEARING *

Effects of Overexposure:* & BLURRED VISION. INGESTION: CAN CAUSE

GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING & DIARRHEA.

ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS

WHICH CAN BE FATAL. REPORTS HAVE ASSOCIATED REPEATED & PROLO

NGED

OCCUPATIONAL OVEREXPOSURE TO SOLVENT W/PERMANENT BRAIN & NERVOUS

SYSTEM DAMAGE.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE VICTIM FROM FURTHER EXPOSURE & RESTORE

BREATHING IF REQUIRED. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES

WHILE HOLDING EYELIDS OPEN. SKIN: WASH CONTAMINATED SKIN W/MILD

SOAP & WATER . INGESTION: DO NOT INDUCE VOMITING. OBTAIN MEDICAL

ATTENTION IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point Method:TCC

Flash Point:112F,44C

Lower Limits:0.8

Upper Limits:5.0

Extinguishing Media:DRY CHEMICAL, CO2, FOAM AND WATER FOG.

Fire Fighting Procedures:DO NOT ENTER CONFINED FIRE SPACE W/O ADEQUATE

PROTECT CLOTH & APPROVED POSITIVE PRESS SCBA. EXCLUDE AIR. USE

WATER ONLY AS FOG. COOL FIRE EXPOSED CONTNR W/WATER.

Unusual Fire/Explosion Hazard:AVOID EXCESSIVE HEAT, OPEN FLAMES & ALL

IGNITION SOURCES.

=====
Accidental Release
=====

Measures =====

Spill Release Procedures:REMOVE IGNITION SOURCES. VENT AREA. ABSORB SPILL W/ABSORB MAT'L & PLACE IN CLOSED CNTNR. LARGE SPILL-DIKE AREA TO PREVENT MAT'L FROM ENTERING WATER SYSTEMS. WEAR PROTECT EQUIPMENT DURING CLEANUP. NOTI FY PROPER AUTHORITIES IF SPILL EXCEEDS 220 LBS.

===== Handling and Storage =====

Handling and Storage Precautions:COMBUSTIBLE LIQUID. STORE IN A COOL, DRY, WELL-VENTILATED AREA, AWAY FROM HEAT & IGNITION SOURCES. AVOID PROLONGED OR REPEATED CONTACT W/SKIN.

Other Precautions:AVOID BREATHING SPRAY/MIST. LAUNDRER CONTAM CLOTHING PRIOR TO REUSE. GROUND CONTAINERS WHEN POURING. LIMIT FREE FALL TO MINIMIZE STATIC CHARGE BUILD-UP. EMPTY CONTAINERS MAY BE HZDS FROM PRODUCT RESIDU E & VAPORS & ALL CAUTIONS APPLY TO THEM.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:A CANISTER-TYPE RESPIRATOR MUST BE WORN TO PREVENT THE IN HALATION OF VAPORS OR SPRAY MISTS WHEN THE TLV/PEL IS EXCEEDED.

Ventilation:GENERAL VENT IS REQUIRED DURING NORMAL USE. LOCAL VENT MAY BE REQUIRED IN CERTAIN CASES TO KEEP EXPOS LEVEL BELOW LIMIT.

Protective Gloves:CHEM-RESIST NITRILE, NEOPRENE OR RUBBER.

Eye Protection:WEAR FACE SHIELD OR CHEMICAL GOGGLES.

Other Protective Equipment:WEAR PROTECTIVE CLOTHING TO PREVENT SKIN CONTACT. EYE WASH STATION/SAFETY SHOWER SHOULD BE AVAILABLE.

Work Hygienic Practices:USE GOOD PERSONAL HYGIENE.

Supplemental Safety and Health

DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER EACH USE. KEEP AWAY FROM CHILDREN.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:301 TO 402F

Vapor Pres:>7.0 @ 38C

Vapor Density:4.8

Spec Gravity:0.95

Viscosity:10"-25"

Evaporation Rate & Reference:SLOWER THAN BUTYL ACETATE

Solubility in Water:NEGLIGIBLE

Appearance and Odor:THIN LIQUID, MILD ODOR.

Percent Volatiles by Volume:25-27

===== Stability and R

activity Data =====

Stability Indicator/Materials to Avoid: YES

AVOID CONTACT WITH STRONG OXIDIZING AGENTS, LEWIS OR MINERAL ACIDS.

Hazardous Decomposition Products: CARBON MONOXIDE AND CARBON DIOXIDE ARE PRODUCED ON COMBUSTION.

Conditions to Avoid Polymerization: AVOID EXCESSIVE HEAT, OPEN FLAME AND ALL IGNITION SOURCES.

===== Disposal Considerations =====

Waste Disposal Methods: TREAT AS HAZARDOUS WASTE IF NOT POSSIBLE TO RECLAIM. DISPOS

E OF AT A LICENSED WASTE DISPOSAL COMPANY OR

INCINERATE W/APPROVAL OF ENVIRONMENTAL AUTHORITY. ALL DISPOSAL PROCEDURES MUST COMPLY W/LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. An

any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.