View NSN Online: https://aerobasegroup.com/nsn/7930-01-336-7198

COOKE INDUSTRIES, INC. -- TUFF JOB DEGREASER/CLEANER -- 7930-01-336-7198

Product ID:TUFF JOB DEGREASER/CLEANER

MSDS Date:06/14/1990

FSC:7930

NIIN:01-336-7198
MSDS Number: BLBFT
=== Responsible Party ===

Company Name: COOKE INDUSTRIES, INC.

Box:4420

City:KANEOHE

State:HI ZIP:96744 Country:US

Info Phone Num:808-235-1331 OR 808-235-0988

Emergency Phone Num:808-235-0

988

Preparer's Name: FRED HERTLEIN

CAGE:COOKE

=== Contractor Identification ===

Company Name: COOKE INDUSTRIES, INC.

Box:4420

City:KANEOHE

State:HI ZIP:96744 Country:US

Phone:808-235-1331 OR 808-235-0988

CAGE:COOKE

Company Name: INALAB INC

CAGE:0EPR4

======= Composition/Information on Ingredients ========

Ingred Name: DIPROPYLENE GLYCOL BUTOXY ETHER; DOWANOL

Other REC Limits:NONE SPECIFIED OSHA PEL:NONE ESTABLISHED ACGIH TLV:NONE ESTABLISHED

Ingred Name:SODIUM HYDROXIDE

CAS:1310-73-2

ACGIH TLV:C 2 MG/M3; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Health Hazards Acute and Chronic: INHALATION SHOULD NOT POSE A PROBLEM IN NORMAL USE OF THIS PRODUCT. PROLONGED SKIN CONTACT MAY CAUSE DERMATITIS OF EXPOSED AREAS. INGESTION OF LARGE AMOUNTS COULD BE CORROSIVE TO STOMACH AND GA STROINT ESTINAL SYSTEM. Medical Cond Aggravated by Exposure: DERMAL CONDITIONS AND/OR ALLERGIES MAY BE AGGRAVATED. First Aid:FLUSH THE AFFECTED SKIN AREA OR EYES WITH COPIOUS AMOUNTS OF WATER FOR 15 MINUTES. IF PAIN OR REDDENED SKIN/EYES PERSIST, REPORT TO A MEDICAL DOCTOR. Flash Point:>176F,>80C ======= Accidental Release Measures Spill Release Procedures: CONTAIN THE SPILL AND DILUTE WITH LARGE AMOUNT OF FRESH WATER. FLUSH DOWN DRAIN. ============= Handling and Storage ========================== Handling and Storage Precautions: DO NOT STORE OUTDOORS OR NEAR HIGH TEMPERATURE HEAT SOURCES. Other Precautions: DO NOT STORE NEAR INCOMPATIBLE MATERIALS. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NONE REQUIRED Ventilation: MECHANICAL IS RECOMMEN

RTECS #:WB4905000

OSHA PEL:2 MG/M3

Other REC Limits: NONE SPECIFIED

DED.

Protective Gloves:PLASTIC OR RUBBER GLOVES.

Eye Protection: RECOMMENDED

Other Protective Equipment: RUBBER BOOTS ARE RECOMMENDED IF MATERIAL IS USED TO WASH DOWN FLOORS OR OTHER LARGE AREAS.

Work Hygienic Practices: WASH AFTER HANDLING.

Supplemental Safety and Health

AVOID PROLONGED SKIN CONTACT WITH THE CONCENTRATED MATERIAL RIGHT OUT OF ITS SHIPPING CONTAINER. AVOID EYE CONTACT.

======== Physical/Chemical Properties ==========

HCC:N1
Boiling Pt:B.P. Text:349F,17
6C
Melt/Freeze Pt:M.P/F.P Text:95.0F,35.0C
Vapor Pres:0.6 MM HG
Vapor Density:4.1
Spec Gravity:0.902
Evaporation Rate & Description Reference: