

FISKE BROTHERS REFINING CO -- LUBRIPLATE 100 SERIES, 107 -- 9150-00-140-4434

=====
Product Identification
=====

Product ID:LUBRIPLATE 100 SERIES, 107

MSDS Date:01/01/1987

FSC:9150

NIIN:00-140-4434

MSDS Number: BLCXW

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO

Address:129 LOCKWOOD ST

City:NEWARK

State:NJ

ZIP:07105

Info Phone Num:201-589-9150

Emergency Phone Num:201-589-9150

C

AGE:9N579

=== Contractor Identification ===

Company Name:AMPEX CORP

Address:401 BROADWAY

Box:City:REDWOOD CITY

State:CA

ZIP:94063-3126

Country:US

CAGE:92739

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:NON-HAZARDOUS INGREDIENTS.

=====
Hazards Identification
=====

LD50 LC50 Mixture:NON

E SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. PRODUCT CONTACTING THE EYES MAY CAUSE EYE IRRIT. HUMAN HEALTH RISKS VARY FROM PERSON TO PERSON. AS A PRECAUTION, EXPOS TO LIQ, VAPS, MISTS AND FUMES SHOULD BE MINIMIZED. THIS PROD HAS LOW ORDER OF ACUTE ORAL TOXICITY, BUT MINUTE AMTS (SEE EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ: ASPIRATED INTO LUNGS DURING INGESTION MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:EYE: FLUSH W/CLEAR H2O FOR AT LEAST 15 MIN. IF IRRIT PERSISTS, CONSULT PHYS. SKIN: REMOVE ANY CONTAM CLTHG & WASH W/ SOAP & WARM H2O. IF INJECTED BY HIGH PRESS UNDER SKIN, REGARDLESS OF APPEARANCE OR ITS SIZE, CONTACT PHYS IMMED. DELAY MAY CAUSE LOSS OF AFFECTED PART OF BODY. INHAL: VAP PRESS IS VERY LOW & INHAL AT ROOM TEMP IS NOT A PROBLEM. IF OVERCOME BY VAP FROM HOT PROD, (SEE SUPP DATA)

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:360F,182C

Lower Limits:0.9%

Upper Limits:7.0%

Extinguishing Media:FOAM, DRY CHEMICAL, CARBON DIOXIDE OR WATER SPRAY (FOG).

Fire Fighting Procedures:

COOL EXPOSED CONTAINERS WITH WATER. USE NIOSH/MSHA APPROVED AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED OR CONFINED SPACES.

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS. EMPTY CONTAINERS RETAIN RESIDUE. DO NOT CUT, DRILL, GRIND, OR WELD, AS THEY MAY EXPLODE.

===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE, WASH REMAINDER W/SUITABLE PETROLEUM SOLV OR ADD ABSORBENT. KEEP PETROLEUM PRODUCT

S OUT OF

SEWERS AND WATER SOURCES. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS AND WATER COURSES.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME, OR STRONG OXIDANTS.

Other Precautions:REMOVE OIL-SOAKED CLOTHING AND LAUNDRY BEFORE REUSE. CLEANSE SKIN THOROUGHLY AFTER CONTACT.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.

Protective Gloves:OIL-RESISTANT GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:USE OIL-RESISTANT APRON, IF NEEDED.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health

FIRST AID PROC: IMMEDIATELY

REMOVE FROM EXPOSURE AND CALL A PHYSICIAN.

INGESTION: IF INGESTED, CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

=====
===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>550F,>288C

Melt/Freeze Pt:M.P/F.P Text:SEMI-SOLID

Vapor Pres:5

Spec Gravity:0.89-0.93

Evaporation Rate & Reference: