

MINNESOTA MINING & MFG CO ADHESIVES & SEALERS DIV. -- SCOTCH-GRIP BRAND 1300
RUBBER & GASKET ADHE -- 5330-01-063-8373

===== Product Identification =====

Product ID:SCOTCH-GRIP BRAND 1300 RUBBER & GASKET ADHE

MSDS Date:06/01/1984

FSC:5330

NIIN:01-063-8373

Kit Part:Y

MSDS Number: BLFCK

=== Responsible Party ===

Company Name:MINNESOTA MINING & MFG CO ADHESIVES & SEALERS DIV.

Address:3M CENTER

City:S

T. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-5454

Emergency Phone Num:612-733-5454

CAGE:76381

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:JAMISON DOOR CO

Address:55 MAPLE AVE

Box:70

City:HAGERSTOWN

State:MD

ZIP:21741-0070

Country:US

Phone:301-733-3100

CAGE:31670

Company Name:MINNESOTA M

INING AND MFG CO, DBA 3M
Address:3M CENTER BLDG 224-5S-04
Box:City:SAINT PAUL
State:MN
ZIP:55144-1000
Country:US
Phone:866-556 5712 / 612-733-1110
CAGE:76381

=====
===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM DISTILLATE
CAS:8030-30-6
RTECS #:DE3030000
Fraction by Wt: 36%
Other REC Limits:200 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 21%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/30
OSTEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 2.5
Spec Gravity:0.88
Evaporation Rate & Reference:>2 (ETHER = 1)
Solubility in Water:LOW
Appearance and Odor:YELLOW, LOW VISCOSITY LIQUID, SOLVENT ODOR.
Percent Volatiles by Volume:100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE SPECIFIED BY MANUFACTURER.
Stability Condition to Avoid:NON

E SPECIFIED BY MANUFACTURER.

Hazardous Decomposition Products: THERMAL DECOMPOSITION OR BURNING MAY PRODUCE CARBON MONOXIDE, CARBON DIOXIDE AND CHLORINATED DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods: RECLAMATION OR INCINERATION IN A PERMITTED HAZARDOUS WASTE FACILITY CAPABLE OF MEETING APPLICABLE REGULATORY REQUIREMENTS FOR DESTRUCTION & REMOVAL IS PREFERRED. OTHERWISE DISPOSE OF IN ACCORDANCE WITH APPLICABLE REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.