

STEVEN INDUSTRIES -- CORROSION PREVENTIVE COMPOUND -- 8030-01-313-7033

=====  
Product Identification  
=====

Product ID:CORROSION PREVENTIVE COMPOUND

MSDS Date:01/22/1981

FSC:8030

NIIN:01-313-7033

MSDS Number: BLFDC

=== Responsible Party ===

Company Name:STEVEN INDUSTRIES

Address:39 AVE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002

Country:US

Info Phone Num:201-437-6500

Emergency Phone Num:201-437-6500

CA

GE:33150

=== Contractor Identification ===

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 57%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:CHROMIUM ZINC OXIDE (ZINC CHOMITE)

CAS:12018-19-8

RTECS #:GB7595000

Fraction by

Wt: 16%  
OSHA PEL:0.1 MG(CRO\*3)/M3,C  
ACGIH TLV:0.01 MG(CR)/M3

Ingred Name:ZINC OXIDE  
CAS:1314-13-2  
RTECS #:ZH4810000  
OSHA PEL:15MG/M3 TDUST/5 FUME  
ACGIH TLV:10MG/M3 TDUST; 9293

Ingred Name:CHROMIUM (SARA III)  
CAS:7440-47-3  
RTECS #:GB4200000  
OSHA PEL:1 MG/M3  
ACGIH TLV:0.5 MG/M3; 9192  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:GRAPHITE, NATURAL  
CAS:7782-42-5  
RTECS #:MD9659600  
Fraction by Wt: 6%  
OSHA PEL:15 MPPCF RDUST  
ACGIH TLV:2 MG/M3 RDUST; 9293

=====  
ion =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.  
Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:NO KNOWN ADVERSE EFFECTS FROM  
EXPOSURE.  
Explanation of Carcinogenicity:NOT RELEVANT.  
Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER.  
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

=====  
First Aid Measures =====

First Aid:EYES: IMMEDIATELY FLUSH EYES WITH POTABLE WATER FOR A MINIMUM OF 15  
MIN, SEEK ASSISTANCE FROM MD . SKIN: FLUSH WITH COPIOUS AMOUNTS OF  
WATER. CALL MD . INHAL: REMOVE TO FRESH AIR. SUPPORT BREATHING. GIVE  
O<sub>2</sub>/ARTF RESP) . INGEST: CALL MD IMMEDIATELY .

=====  
Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:360F,182C  
Lower Limits:1%  
Upper Limits:6%  
Extinguishing Media:WATER FOG, WATER, FOAM, CO<sub>2</sub>, DRY CHEMICAL.  
Fire Fighting Procedures:USE NIOSH/

MSHA APPROVED SCBA & FULL PROTECTIVE  
EQUIPMENT FOR ENCLOSED AREAS.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:CONTAIN AND RECOVER. USE OIL SOLUBLE SOLVENTS  
TO AFFECT CLEAN-UP.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CONTAINER AWAY FROM  
OPEN FLAME.

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:UNNECESSARY IN NORMAL USE. USE NIOSH/MSHA  
APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:LOCAL EXHAUST: SUFFICIENT TO MAINTAIN LEVELS BELOW TLV OF  
COMPONENT IF USED AT HIGH TEMPERATURE.

Protective Gloves:OIL IMPERVIOUS GLOVES.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.

Work Hygienic Practices:USE GOOD INDUSTRIAL HY  
GIENIC PRACTICES.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:600F,316C

Vapor Pres:8

Spec Gravity:1.4

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TAN IN COLOR AND WITH LITTLE ODOR.

Percent Volatiles by Volume: