

SPRAYON PRODUCTS DIV OF THE SHERWIN-WILLIAMS CO -- VV-L-800A -- 9150-00-458-0075
===== Product Identification =====

Product ID:VV-L-800A
MSDS Date:10/29/1991
FSC:9150

NIIN:00-458-0075

MSDS Number: BLFFQ

=== Responsible Party ===

Company Name:SPRAYON PRODUCTS DIV OF THE SHERWIN-WILLIAMS CO

Address:3818 CORONADO ST

City:ANAHEIM

State:CA

ZIP:92806

Country:US

Emergency Phone Num:714-630-1337

CAGE:5N0

04

=== Contractor Identification ===

Company Name:SPRAYON PRODUCTS DIV OF THE SHERWIN-WILLIAMS CO

Address:3818 CORONADO ST

Box:City:ANAHEIM

State:CA

ZIP:92806

Country:US

Phone:714-632-1242

CAGE:5N004

===== Composition/Information on Ingredients =====

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)

CAS:75-71-8

RTECS #:PA8200000

Fraction by Wt: 30%

Other REC Limits:NONE SPECIFIED

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ozone Depletin

=====
===== Hazards Identification =====

LD50 LC50 Mixture:TLV IS 1000 PPM

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-IN A CONFINED AREA VAPORS IN HIGH CONCENTRATION ARE ANESTHETIC, IRRITANT TO SKIN AND UPPER RESPIRATORY SYSTEM. CHRONIC-REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERV

OUS SYSTEM DAMAGE, ALSO KIDNEY AND LIVER DAMAGE.

Explanation of Carcinogenicity:NONE OF THE CHEMICALS IN THIS PRODUCT IS LISTED BY IARC, NTP OR OSHA AS A CARCINOGEN.

Effects of Overexposure:OVER-EXPOSURE MAY RESULT IN LIGHT- HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA. HARMFUL OR FATAL IF SWALLOWED.

Medical Cond Aggravated by Exposure:NONE ESTABLISHED.

=====
===== First Aid Measures =====

First Aid:EYE: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR 15 MINUTES.

GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR. INGESTION: DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =====

Flash Point:NONE

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. COOL FIRE EXPOSED CONTAINERS WITH WATER SPRAY.

Unusual Fire/Explosion Hazard:KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEAT MAY CAUSE BURSTING.

===

=====
===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA-ESPECIALLY LOW PLACES WHERE VAPORS WILL COLLECT. AVOID BREATHING VAPORS AND REMOVE WITH INERT ABSORBENT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAUSE BURSTING.

Other Precautions:KEEP AWAY FROM CHILDREN. DO NOT PUNCTURE OR

INCINERATE. DO NOT SPRAY NEAR FIRE OR OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF PERSONAL EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS, WEAR A PROPERLY FITTED RESPIRATOR APPROVED BY NIOSH/MSHA FOR PROTECTION.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO CONTROL TLV'S.

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES WITH UNPERFORATED SIDES

Other Protective Equipment:SAFETY S

HOWER AND EYE BATH. INDUSTRIAL TYPE

WORK CLOTHING AND APRON AS REQUIRED TO AVOID PROLONGED OR REPEATED CONTACT.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING AND BEFORE EATING OR DRINKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V2

Boiling Pt:B.P. Text: