

HULS AMERICA INC -- MIL-H-6083E -- 9150-00-935-9807

=====
Product Identification
=====

Product ID:MIL-H-6083E

MSDS Date:01/16/1989

FSC:9150

NIIN:00-935-9807

MSDS Number: BLJLL

=== Responsible Party ===

Company Name:HULS AMERICA INC

Address:80 CENTENNIAL AVE

Box:456

City:PISCATAWAY

State:NJ

ZIP:08855-0456

Country:US

Info Phone Num:201-980-6800

Emergency Phone Num:201-980-6800

CAGE:63182

=== Contra

ctor Identification ===

Company Name:HULS AMERICA INC

Address:TURNER PLACE

Box:365

City:PISCATAWAY

State:NJ

ZIP:08855

Country:US

Phone:201-763-7173

CAGE:63182

=====
Composition/Information on Ingredients
=====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE
PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingesti

on:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:LOW ORAL AND DERMAL TOXICITY. MISTS OR FUMES FROM EXCESSIVE HEATING AMY CAUSE EYE AND SKIN IRRITATION. MAY ALSO CAUSE RESPIRATORY TRACT IRRITATION.
Effects of Overexposure:MIST OR FUMES FROM EXCESSIVE HEATING MAY CAUSE NAUSEA AND/OR VOMITING.
Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER.

===== First Aid Measures =====

First Aid:CONT
ACT- WASH SKIN WITH SOAP AND EATER; FLUSH EYES WITH WATER FOR 25 MIN. CALL A PHYSICIAN IF IRRITATION DEVELOPS. INHALATION- REMOVE VICTIM TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION OR OXYGEN IF NEEDED. INGESTION- DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:200F,93C
Lower Limits:1
Upper Limits:6
Extinguishing Media:WATER FOG, DRY CHEMICAL, FOAM OR CARBON DIOXIDE.
Fire Fightin
g Procedures:BURNING WILL PRODUCE TOXIC FUMES. WEAR SELF-CONTAINED BREATHING APPARATUS AND FULL TURN-OUT GEAR TO FIGHT FIRE. AVOID SPREADING LIQUIE AND FIRE WITH WATER.
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS. COOL WITH WATER SPRAY.

===== Accidental Release Measures =====

Spill Release Procedures:COVER WITH AN INERT ABSORBENT MATERIAL AND REMOVE TO DISPOSAL CONTAINER.
Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE OIL ABOVE THE MAXIMUM RECOMMENDED OPERATING TEMPERATURE OF 200F. MAY SOFTEN SOME PLASTIC AND PAINT SURFACES.
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF OVERHEATED, USE APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTIVE EQUIPMENT.
Ventilation:LOCAL EXHAUST AND MECHANICAL VENTILATION RECOMMENDED.
Protective Glov

es:IMPERMEABLE GLOVES

Eye Protection:CHEMICAL SPLASH GOGGLES OR FACE SHIELD

Other Protective Equipment:EYEWASH FOUNTAIN, SAFETY SHOWER. WASH
CONTAMINATED CLOTHING BEFORE REUSE.

Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.

Supplemental Safety and Health
NONE

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:420F,216C

Vapor Pres:0.07 MM HG

Vapor Density:>1

Spec Gravity: