View NSN Online: https://aerobasegroup.com/nsn/9150-01-123-4746 COOPER INDUSTRIES INC -- W-K-M NO. 24 SEALANT -- 9150-01-123-4746 Product ID:W-K-M NO. 24 SEALANT MSDS Date:08/01/1991 FSC:9150 NIIN:01-123-4746 MSDS Number: BLJMY === Responsible Party === Company Name: COOPER INDUSTRIES INC Address:16500 SOUTH MAIN City:MISSOURI CITY State:TX ZIP:77459 Country:US Info Phone Num:713-499-8511 Emergency Phone Num:713-499-8511 Prep arer's Name:W J SUTTON CAGE:01957 === Contractor Identification === Company Name: COOPER INDUSTRIES INC Address:16500 SOUTH MAIN Box:419 City:MISSOURI CITY State:TX ZIP:77459 Country:US Phone:713-499-8511 CAGE:01957 ======= Composition/Information on Ingredients ========

Ingred Name: NON HAZARDOUS INGREDIENTS

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: NO Ingestion: YES

| Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NONE SPECIFIED BY MANUFACTURER. Explanation of Carcinogenicity:NOT RELEVANT. Effects of Overexposure:NONE SPECIFIED BY MANUFACTURER. Medical Cond Aggravated by Exposure:NONE SPECIFIED BY MANUFACTURER. |
|--|
| ====================================== |
| First Aid:INGEST:CALL A DOCTOR. NO. 24 SEALANT IS SOLUBLE IN MINERAL OIL. INHAL:REMOVE TO FRESH AIR. SUPPORT BREATHING (GIVE O*2/ARTI |
| FICIAL RESPIRATION) . EYE:IMMEDIATELY FLUSH EYES W/POTABLE WATER FOR A MINIMUM OF 15 MINS, SEEK ASSISTANCE FROM MD . SKIN:FLUSH W/COPIOUS AMOUNTS OF WATER. CALL MD . |
| ====================================== |
| Flash Point Method:COC Flash Point:400F,204C Extinguishing Media:CARBON DIOXIDE & DRY CHEMICAL. Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT. Unusual Fire/Explosion Hazard:NONE. |
| ======== Accidental R elease Measures ==================================== |
| Spill Release Procedures:MAY BE WASHED OR CLEANED UP W/KEROSENE OR OTHER HYDROCARBON SOLVENTS, USING STANDARD SAFETY PRECAUTIONS, SUCH AS GOOD VENTILATION, IN THE ABSENCE OF OPEN FLAMES & WEARING SUITABLE GLOVES WHILE HANDLIN G CLEAN-UP SOLVENTS. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER. |
| =========== Handling and Storage ============= |
| Handling and Storage Precautions:NO SPECIAL HANDLING. KEEP IN COOL, DRY PLACE F |
| OR BEST STORAGE LIFE. Other Precautions:NONE SPECIFIED BY MANUFACTURER. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:NONE NEEDED. Ventilation:LOCAL EXHAUST STANDARD. Protective Gloves:NONE NEEDED. Eye Protection:NONE NEEDED. Other Protective Equipment:NONE NEEDED. Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER. Supplemental Safety and Health NONE SPECIFIED BY MANUFACTURER. |
| ========== Physical/Chemical Properties ========== |

| Spec Gravity:>1 Evaporation Rate & Deference:>1% Solubility in Water:>1% Appearance and Odor:OFF-WHITE COLOR W/NEUTRAL ODOR. Percent Volatiles by Volume:0 |
|--|
| ====================================== |
| Stability Indicator/Materials to Avoid:YES |

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS/CHEMICAL & ORGANIC SOLVENTS.
Stability Condition to Avoid:NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomposition Products:NONE SPECIFIED BY MANUFACTURER.

======= Disposal Considerations ========

Waste Disposal Methods:STANDARD DISPOSAL. DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.